



## ***Linux Ubuntu 26.04 Manual Pages on command 'babeljs-7-node.1'***

***\$ man babeljs-7-node.1***

BABEL-NODE.JS(1)

User Commands

BABEL-NODE.JS(1)

### NAME

babel-node.js - CLI that works exactly the same as the Node.js CLI, with the added benefit of compiling with Babel presets and plugins before running it

### SYNOPSIS

babel-node [options] [ -e script | script.js ] [arguments]

### OPTIONS

-e, --eval [script]

Evaluate script

--no-babelrc

Specify whether or not to use .babelrc and .babelignore files

-r, --require [module]

Require module

-p, --print [code]

Evaluate script and print result

-o, --only [globs]

A comma-separated list of glob patterns to compile

-i, --ignore [globs]

A comma-separated list of glob patterns to skip compiling

-x, --extensions [extensions]

List of extensions to hook into [.es6,.js,.es,.jsx,.mjs]

--config-file [path]

Path to the babel config file to use. Defaults to working directory babel.config.js

`--env-name [name]`

The name of the 'env' to use when loading configs and plugins. Defaults to the value of `BABEL_ENV`, or else `NODE_ENV`, or else 'development'.

`--root-mode [mode]`

The project-root resolution mode. One of 'root' (the default), 'upward', or 'upward-optional'.

`-w, --plugins [string]`

`-b, --presets [string]`

`-V, --version`

output the version number

`-h, --help`

display help for command

babel-node.js 7.20.15+ds1+~cs214.269.168 March 2026

BABEL-NODE.JS(1)