



Linux Ubuntu 26.04 Manual Pages on command 'backtrace_symbols_fd.3'

\$ man backtrace_symbols_fd.3

backtrace(3) Library Functions Manual backtrace(3)

NAME

backtrace, backtrace_symbols, backtrace_symbols_fd - support for application self-debugging

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <execinfo.h>

int backtrace(int size;
              void *buffer[size], int size);

char **backtrace_symbols(int size;
                         void *const buffer[size], int size);

void backtrace_symbols_fd(int size;
                         void *const buffer[size], int size, int fd);
```

DESCRIPTION

backtrace() returns a backtrace for the calling program, in the array pointed to by buffer.

A backtrace is the series of currently active function calls for the program. Each item in the array pointed to by buffer is of type void *, and is the return address from the corresponding stack frame. The size argument specifies the maximum number of addresses that can be stored in buffer. If the backtrace is larger than size, then the addresses corresponding to the size most recent function calls are returned; to obtain the complete backtrace, make sure that buffer and size are large enough.

Given the set of addresses returned by backtrace() in buffer, backtrace_symbols() translates the addresses into an array of strings that describe the addresses symbolically. The size

`backtrace_symbols_fd()` takes the same buffer and size arguments as `backtrace_symbols()`, but instead of returning an array of strings to the caller, it writes the strings, one per line, to the file descriptor `fd`. `backtrace_symbols_fd()` does not call `malloc(3)`, and so can be employed in situations where the latter function might fail, but see NOTES.

`backtrace()` returns the number of addresses returned in `buffer`, which is not greater than `size`. If the return value is less than `size`, then the full backtrace was stored; if it is equal to `size`, then it may have been truncated, in which case, the addresses of the oldest stack frames are not returned.

For an explanation of the terms used in this section, see `attributes(7)`.

?	Interface	?	Attribute	?	Value	?
---	-----------	---	-----------	---	-------	---

? backtrace(), backtrace_symbols(), backtrace_symbols_fd() ? Thread safety ? MT-Safe ?

GNU.

glibc 2.1.

These functions make some assumptions about how a function's return address is stored on the stack. Note the following:

? Inlined functions do not have stack frames.

? Tail-call optimization causes one stack frame to replace another.

? `backtrace()` and `backtrace_symbols_fd()` don't call `malloc()` explicitly, but they are part of `libgcc`, which gets loaded dynamically when first used. Dynamic loading usually triggers a call to `malloc(3)`. If you need certain calls to these two functions to not allocate memory (in signal handlers, for example), you need to make sure `libgcc` is loaded beforehand.

The symbol names may be unavailable without the use of special linker options. For systems using the GNU linker, it is necessary to use the `-rdynamic` linker option. Note that names of "static" functions are not exposed, and won't be available in the backtrace.

EXAMPLES

The program below demonstrates the use of `backtrace()` and `backtrace_symbols()`. The following shell session shows what we might see when running the program:

```
$ cc -rdynamic prog.c -o prog
$ ./prog 3
backtrace() returned 8 addresses
./prog(myfunc3+0x5c) [0x80487f0]
./prog [0x8048871]
./prog(myfunc+0x21) [0x8048894]
./prog(myfunc+0x1a) [0x804888d]
./prog(myfunc+0x1a) [0x804888d]
./prog(main+0x65) [0x80488fb]
/lib/libc.so.6(__libc_start_main+0xdc) [0xb7e38f9c]
./prog [0x8048711]
```

Program source

```
#include <execinfo.h>

#include <stdio.h>

#include <stdlib.h>

#include <unistd.h>

#define BT_BUF_SIZE 100

void
myfunc3(void)
{
```

```

int nptrs;

void *buffer[BT_BUF_SIZE];

char **strings;

nptrs = backtrace(buffer, BT_BUF_SIZE);

printf("backtrace() returned %d addresses\n", nptrs);

/* The call backtrace_symbols_fd(buffer, nptrs, STDOUT_FILENO)
   would produce similar output to the following: */

strings = backtrace_symbols(buffer, nptrs);

if (strings == NULL) {
    perror("backtrace_symbols");
    exit(EXIT_FAILURE);
}

for (size_t j = 0; j < nptrs; j++)
    printf("%s\n", strings[j]);

free(strings);
}

static void /* "static" means don't export the symbol. */
myfunc2(void)
{
    myfunc3();
}

void
myfunc(int ncalls)
{
    if (ncalls > 1)
        myfunc(ncalls - 1);
    else
        myfunc2();
}

int
main(int argc, char *argv[])
{
    if (argc != 2) {

```

```
fprintf(stderr, "%s num-calls\n", argv[0]);  
exit(EXIT_FAILURE);  
}  
myfunc(atoi(argv[1]));  
exit(EXIT_SUCCESS);  
}
```

SEE ALSO

[addr2line\(1\)](#), [gcc\(1\)](#), [gdb\(1\)](#), [ld\(1\)](#), [dlopen\(3\)](#), [malloc\(3\)](#)

Linux man-pages 6.17

2026-02-08

[backtrace\(3\)](#)