



Linux Ubuntu 26.04 Manual Pages on command 'bcopy.3'

\$ man bcopy.3

bcopy(3) Library Functions Manual bcopy(3)

NAME

bcopy - copy byte sequence

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <strings.h>

[[deprecated]] void bcopy(size_t n;
                          const void src[n], void dest[n], size_t n);
```

DESCRIPTION

The bcopy() function copies n bytes from src to dest. The result is correct, even when both areas overlap.

RETURN VALUE

None.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

? Interface ? Attribute ? Value ?

??

? bcopy() ? Thread safety ? MT-Safe ?

??

STANDARDS

None.

HISTORY

4.3BSD.

Marked as LEGACY in POSIX.1-2001: use `memcpy(3)` or `memmove(3)` in new programs. Note that the first two arguments are interchanged for `memcpy(3)` and `memmove(3)`. POSIX.1-2008 removes the specification of `bcopy()`.

SEE ALSO

`bstring(3)`, `memccpy(3)`, `memcpy(3)`, `memmove(3)`, `strcpy(3)`, `strncpy(3)`

Linux man-pages 6.17

2026-02-08

`bcopy(3)`