



Linux Ubuntu 26.04 Manual Pages on command 'certbot.1'

\$ man certbot.1

CERTBOT(1) Certbot CERTBOT(1)

NAME

certbot - Automatically configure HTTPS using Let's Encrypt

SYNOPSIS

The objective of Certbot, Let's Encrypt, and the ACME (Automated Certificate Management Environment) protocol is to make it possible to set up an HTTPS server and have it automatically obtain a browser-trusted certificate, without any human intervention. This is accomplished by running a certificate management agent on the web server.

This agent is used to:

- ? Automatically prove to the Let's Encrypt CA that you control the website
- ? Obtain a browser-trusted certificate and set it up on your web server
- ? Keep track of when your certificate is going to expire, and renew it
- ? Help you revoke the certificate if that ever becomes necessary.

OPTIONS

usage:

certbot [SUBCOMMAND] [options] [-d DOMAIN] [-d DOMAIN] ...

Certbot can obtain and install HTTPS/TLS/SSL certificates. By default, it will attempt to use a webserver both for obtaining and installing the certificate. The most common SUBCOMMANDS and flags are:

obtain, install, and renew certificates:

(default) run Obtain & install a certificate in your current webserver

certonly Obtain or renew a certificate, but do not install it

renew Renew all previously obtained certificates that are near expiry

enhance Add security enhancements to your existing configuration
 -d DOMAINS Comma-separated list of domains to obtain a certificate for
 --apache Use the Apache plugin for authentication & installation
 --standalone Run a standalone webserver for authentication
 --nginx Use the Nginx plugin for authentication & installation
 --webroot Place files in a server's webroot folder for authentication
 --manual Obtain certificates interactively, or using shell script hooks
 -n Run non-interactively
 --test-cert Obtain a test certificate from a staging server
 --dry-run Test "renew" or "certonly" without saving any certificates to disk

manage certificates:

certificates Display information about certificates you have from Certbot
 revoke Revoke a certificate (supply --cert-name or --cert-path)
 delete Delete a certificate (supply --cert-name)
 reconfigure Update a certificate's configuration (supply --cert-name)

manage your account:

register Create an ACME account
 unregister Deactivate an ACME account
 update_account Update an ACME account
 show_account Display account details
 --agree-tos Agree to the ACME server's Subscriber Agreement
 -m EMAIL Email address for important account notifications

optional arguments:

-h, --help show this help message and exit
 -c CONFIG_FILE, --config CONFIG_FILE
 path to config file (default: /etc/letsencrypt/cli.ini
 and ~/.config/letsencrypt/cli.ini)
 -v, --verbose This flag can be used multiple times to incrementally
 increase the verbosity of output, e.g. -vvv. (default:
 0)
 --max-log-backups MAX_LOG_BACKUPS
 Specifies the maximum number of backup logs that
 should be kept by Certbot's built in log rotation.

Setting this flag to 0 disables log rotation entirely,
causing Certbot to always append to the same log file.

(default: 1000)

`-n, --non-interactive, --noninteractive`

Run without ever asking for user input. This may
require additional command line flags; the client will
try to explain which ones are required if it finds one
missing (default: False)

`--force-interactive` Force Certbot to be interactive even if it detects
it's not being run in a terminal. This flag cannot be
used with the `renew` subcommand. (default: False)

`-d DOMAIN, --domains DOMAIN, --domain DOMAIN`

Domain names to include. For multiple domains you can
use multiple `-d` flags or enter a comma separated list
of domains as a parameter. All domains will be
included as Subject Alternative Names on the
certificate. The first domain will be used as the
certificate name, unless otherwise specified or if you
already have a certificate with the same name. In the
case of a name conflict, a number like `-0001` will be
appended to the certificate name. (default: Ask)

`--eab-kid EAB_KID` Key Identifier for External Account Binding (default:
None)

`--eab-hmac-key EAB_HMAC_KEY`

HMAC key for External Account Binding (default: None)

`--cert-name CERTNAME` Certificate name to apply. This name is used by
Certbot for housekeeping and in file paths; it doesn't
affect the content of the certificate itself.

Certificate name cannot contain filepath separators
(i.e. `'/'` or `'\'`, depending on the platform). To see
certificate names, run `'certbot certificates'`. When
creating a new certificate, specifies the new
certificate's name. (default: the first provided

domain or the name of an existing certificate on your system for the same domains)

`--dry-run` Perform a test run against the Let's Encrypt staging server, obtaining test (invalid) certificates but not saving them to disk. This can only be used with the 'certonly' and 'renew' subcommands. It may trigger webserver reloads to temporarily modify & roll back configuration files. `--pre-hook` and `--post-hook` commands run by default. `--deploy-hook` commands do not run, unless enabled by `--run-deploy-hooks`. The test server may be overridden with `--server`. (default: False)

`--debug-challenges` After setting up challenges, wait for user input before submitting to CA. When used in combination with the `-v`` option, the challenge URLs or FQDNs and their expected return values are shown. (default: False)

`--preferred-chain` PREFERRED_CHAIN

Set the preferred certificate chain. If the CA offers multiple certificate chains, prefer the chain whose topmost certificate was issued from this Subject Common Name. If no match, the default offered chain will be used. (default: None)

`--preferred-challenges` PREF_CHALLS

A sorted, comma delimited list of the preferred challenge to use during authorization with the most preferred challenge listed first (Eg, "dns" or "http,dns"). Not all plugins support all challenges. See <https://certbot.eff.org/docs/using.html#plugins> for details. ACME Challenges are versioned, but if you pick "http" rather than "http-01", Certbot will select the latest version automatically. (default: [])

`--issuance-timeout` ISSUANCE_TIMEOUT

This option specifies how long (in seconds) Certbot

will wait for the server to issue a certificate.

(default: 90)

`--user-agent USER_AGENT`

Set a custom user agent string for the client. User agent strings allow the CA to collect high level statistics about success rates by OS, plugin and use case, and to know when to deprecate support for past Python versions and flags. If you wish to hide this information from the Let's Encrypt server, set this to `""`. (default: `CertbotACMEClient/3.3.0 (certbot; OS_NAME OS_VERSION) Authenticator/XXX Installer/YYY (SUBCOMMAND; flags: FLAGS) Py/major.minor.patchlevel`). The flags encoded in the user agent are: `--duplicate`, `--force-renew`, `--allow-subset-of-names`, `-n`, and whether any hooks are set.

`--user-agent-comment USER_AGENT_COMMENT`

Add a comment to the default user agent string. May be used when repackaging Certbot or calling it from another tool to allow additional statistical data to be collected. Ignored if `--user-agent` is set. (Example: `Foo-Wrapper/1.0`) (default: `None`)

automation:

Flags for automating execution & other tweaks

`--keep-until-expiring`, `--keep`, `--reinstall`

If the requested certificate matches an existing certificate, always keep the existing one until it is due for renewal (for the 'run' subcommand this means reinstall the existing certificate). (default: `Ask`)

`--expand` If an existing certificate is a strict subset of the requested names, always expand and replace it with the additional names. (default: `Ask`)

`--version` show program's version number and exit

`--force-renewal`, `--renew-by-default`

If a certificate already exists for the requested domains, renew it now, regardless of whether it is near expiry. (Often `--keep-until-expiring` is more appropriate). Also implies `--expand`. (default: False)

`--renew-with-new-domains`

If a certificate already exists for the requested certificate name but does not match the requested domains, renew it now, regardless of whether it is near expiry. (default: False)

`--reuse-key` When renewing, use the same private key as the existing certificate. (default: False)

`--no-reuse-key` When renewing, do not use the same private key as the existing certificate. Not reusing private keys is the default behavior of Certbot. This option may be used to unset `--reuse-key` on an existing certificate. (default: False)

`--new-key` When renewing or replacing a certificate, generate a new private key, even if `--reuse-key` is set on the existing certificate. Combining `--new-key` and `--reuse-key` will result in the private key being replaced and then reused in future renewals. (default: False)

`--allow-subset-of-names`

When performing domain validation, do not consider it a failure if authorizations can not be obtained for a strict subset of the requested domains. This may be useful for allowing renewals for multiple domains to succeed even if some domains no longer point at this system. This option cannot be used with `--csr`. (default: False)

`--agree-tos` Agree to the ACME Subscriber Agreement (default: Ask)

`--duplicate` Allow making a certificate lineage that duplicates an existing one (both can be renewed in parallel) (default: False)

-q, --quiet Silence all output except errors. Useful for automation via cron. Implies --non-interactive.
(default: False)

security:

Security parameters & server settings

--rsa-key-size N Size of the RSA key. (default: 2048)

--key-type {rsa,ecdsa}

Type of generated private key. Only *ONE* per invocation can be provided at this time. (default: ecdsa)

--elliptic-curve N The SECG elliptic curve name to use. Please see RFC 8446 for supported values. (default: secp256r1)

--must-staple Adds the OCSP Must-Staple extension to the certificate. Autoconfigures OCSP Stapling for supported setups (Apache version >= 2.3.3). (default: False)

--redirect Automatically redirect all HTTP traffic to HTTPS for the newly authenticated vhost. (default: redirect enabled for install and run, disabled for enhance)

--no-redirect Do not automatically redirect all HTTP traffic to HTTPS for the newly authenticated vhost. (default: redirect enabled for install and run, disabled for enhance)

--hsts Add the Strict-Transport-Security header to every HTTP response. Forcing browser to always use SSL for the domain. Defends against SSL Stripping. (default: False)

--uir Add the "Content-Security-Policy: upgrade-insecure-requests" header to every HTTP response. Forcing the browser to use https:// for every http:// resource. (default: False)

--staple-ocsp Enables OCSP Stapling. A valid OCSP response is stapled to the certificate that the server offers

during TLS. (default: False)

`--strict-permissions` Require that all configuration files are owned by the current user; only needed if your config is somewhere unsafe like `/tmp/` (default: False)

`--auto-hsts` Gradually increasing max-age value for HTTP Strict Transport Security security header (default: False)

testing:

The following flags are meant for testing and integration purposes only.

`--run-deploy-hooks` When performing a test run using `--dry-run`` or ``reconfigure``, run any applicable deploy hooks. This includes hooks set on the command line, saved in the certificate's renewal configuration file, or present in the renewal-hooks directory. To exclude directory hooks, use `--no-directory-hooks`. The hook(s) will only be run if the dry run succeeds, and will use the current active certificate, not the temporary test certificate acquired during the dry run. This flag is recommended when modifying the deploy hook using ``reconfigure``. (default: False)

`--test-cert, --staging`
Use the Let's Encrypt staging server to obtain or revoke test (invalid) certificates; equivalent to `--server https://acme-staging-v02.api.letsencrypt.org/directory` (default: False)

`--debug` Show tracebacks in case of errors (default: False)

`--no-verify-ssl` Disable verification of the ACME server's certificate. The root certificates trusted by Certbot can be overridden by setting the `REQUESTS_CA_BUNDLE` environment variable. (default: False)

`--http-01-port HTTP01_PORT`
Port used in the http-01 challenge. This only affects the port Certbot listens on. A conforming ACME server

will still attempt to connect on port 80. (default:
80)

--http-01-address HTTP01_ADDRESS

The address the server listens to during http-01
challenge. (default:)

--https-port HTTPS_PORT

Port used to serve HTTPS. This affects which port
Nginx will listen on after a LE certificate is
installed. (default: 443)

--break-my-certs Be willing to replace or renew valid certificates with
invalid (testing/staging) certificates (default:
False)

paths:

Flags for changing execution paths & servers

--cert-path CERT_PATH

Path to where certificate is saved (with certonly
--csr), installed from, or revoked (default: None)

--key-path KEY_PATH Path to private key for certificate installation or
revocation (if account key is missing) (default: None)

--fullchain-path FULLCHAIN_PATH

Accompanying path to a full certificate chain
(certificate plus chain). (default: None)

--chain-path CHAIN_PATH

Accompanying path to a certificate chain. (default:
None)

--config-dir CONFIG_DIR

Configuration directory. (default: /etc/letsencrypt)

--work-dir WORK_DIR Working directory. (default: /var/lib/letsencrypt)

--logs-dir LOGS_DIR Logs directory. (default: /var/log/letsencrypt)

--server SERVER ACME Directory Resource URI. (default:
<https://acme-v02.api.letsencrypt.org/directory>)

manage:

Various subcommands and flags are available for managing your

certificates:

certificates	List certificates managed by Certbot
delete	Clean up all files related to a certificate
renew	Renew all certificates (or one specified with --cert-name)
revoke	Revoke a certificate specified with --cert-path or --cert-name
reconfigure	Update renewal configuration for a certificate specified by --cert-name

run:

Options for obtaining & installing certificates

certonly:

Options for modifying how a certificate is obtained

--csr CSR Path to a Certificate Signing Request (CSR) in DER or PEM format. Currently --csr only works with the 'certonly' subcommand. (default: None)

renew:

The 'renew' subcommand will attempt to renew any certificates previously obtained if they are close to expiry, and print a summary of the results.

By default, 'renew' will reuse the plugins and options used to obtain or most recently renew each certificate. You can test whether future renewals will succeed with '--dry-run'. Individual certificates can be renewed with the '--cert-name' option. Hooks are available to run commands before and after renewal; see <https://certbot.eff.org/docs/using.html#renewal> for more information on these.

--pre-hook PRE_HOOK Command to be run in a shell before obtaining any certificates. Unless --disable-hook-validation is used, the command's first word must be the absolute pathname of an executable or one found via the PATH environment variable. Intended primarily for renewal, where it can be used to temporarily shut down a webserver that might conflict with the standalone plugin. This will only be called if a certificate is

actually to be obtained/renewed. When renewing several certificates that have identical pre-hooks, only the first will be executed. (default: None)

`--post-hook POST_HOOK`

Command to be run in a shell after attempting to obtain/renew certificates. Unless `--disable-hook-validation` is used, the command's first word must be the absolute pathname of an executable or one found via the PATH environment variable. Can be used to deploy renewed certificates, or to restart any servers that were stopped by `--pre-hook`. This is only run if an attempt was made to obtain/renew a certificate. If multiple renewed certificates have identical post-hooks, only one will be run. (default: None)

`--deploy-hook DEPLOY_HOOK`

Command to be run in a shell once for each successfully issued certificate. Unless `--disable-hook-validation` is used, the command's first word must be the absolute pathname of an executable or one found via the PATH environment variable. For this command, the shell variable `$RENEWED_LINEAGE` will point to the config live subdirectory (for example, `"/etc/letsencrypt/live/example.com"`) containing the new certificates and keys; the shell variable `$RENEWED_DOMAINS` will contain a space-delimited list of renewed certificate domains (for example, `"example.com www.example.com"`) (default: None)

`--disable-hook-validation`

Ordinarily the commands specified for `--pre-hook`/`--post-hook`/`--deploy-hook` will be checked for validity, to see if the programs being run are in the `$PATH`, so that mistakes can be caught early, even when the hooks aren't being run just yet. The validation is

rather simplistic and fails if you use more advanced
shell constructs, so you can use this switch to
disable it. (default: False)

`--no-directory-hooks` Disable running executables found in Certbot's hook
directories. (default: False)

`--disable-renew-updates`

Disable automatic updates to your server configuration
that would otherwise be done by the selected installer
plugin, and triggered when the user executes "certbot
renew", regardless of if the certificate is renewed.
This setting does not apply to important TLS
configuration updates. (default: False)

`--no-autorenew` Disable auto renewal of certificates. (default: False)

certificates:

List certificates managed by Certbot

delete:

Options for deleting a certificate

revoke:

Options for revocation of certificates

`--reason {unspecified,keycompromise,affiliationchanged,superseded,cessationofoperation}`

Specify reason for revoking certificate. (default:
unspecified)

`--delete-after-revoke`

Delete certificates after revoking them, along with
all previous and later versions of those certificates.
(default: Ask)

`--no-delete-after-revoke`

Do not delete certificates after revoking them. This
option should be used with caution because the 'renew'
subcommand will attempt to renew undeleted revoked
certificates. (default: Ask)

register:

Options for account registration

-m EMAIL, --email EMAIL

Email used for registration and recovery contact. Use comma to register multiple emails, ex:
u1@example.com,u2@example.com. (default: Ask).

--eff-email Share your e-mail address with EFF (default: Ask)

--no-eff-email Don't share your e-mail address with EFF (default: Ask)

update_account:

Options for account modification

unregister:

Options for account deactivation.

--account ACCOUNT_ID Account ID to use (default: None)

install:

Options for modifying how a certificate is deployed

rollback:

Options for rolling back server configuration changes

--checkpoints N Revert configuration N number of checkpoints.
(default: 1)

plugins:

Options for the "plugins" subcommand

--init Initialize plugins. (default: False)

--prepare Initialize and prepare plugins. (default: False)

--authenticators Limit to authenticator plugins only. (default: None)

--installers Limit to installer plugins only. (default: None)

enhance:

Helps to harden the TLS configuration by adding security enhancements to already existing configuration.

show_account:

Options useful for the "show_account" subcommand:

reconfigure:

Common options that may be updated with the "reconfigure" subcommand:

plugins:

Plugin Selection: Certbot client supports an extensible plugins

architecture. See 'certbot plugins' for a list of all installed plugins and their names. You can force a particular plugin by setting options provided below. Running `--help <plugin_name>` will list flags specific to that plugin.

`--configurator CONFIGURATOR`

Name of the plugin that is both an authenticator and an installer. Should not be used together with `--authenticator` or `--installer`. (default: Ask)

`-a AUTHENTICATOR, --authenticator AUTHENTICATOR`

Authenticator plugin name. (default: None)

`-i INSTALLER, --installer INSTALLER`

Installer plugin name (also used to find domains).
(default: None)

`--apache` Obtain and install certificates using Apache (default: False)

`--nginx` Obtain and install certificates using Nginx (default: False)

`--standalone` Obtain certificates using a "standalone" webserver.
(default: False)

`--manual` Provide laborious manual instructions for obtaining a certificate (default: False)

`--webroot` Obtain certificates by placing files in a webroot directory. (default: False)

`--dns-cloudflare` Obtain certificates using a DNS TXT record (if you are using Cloudflare for DNS). (default: False)

`--dns-digitalocean` Obtain certificates using a DNS TXT record (if you are using DigitalOcean for DNS). (default: False)

`--dns-dnssimple` Obtain certificates using a DNS TXT record (if you are using DNSimple for DNS). (default: False)

`--dns-dnsmadeeasy` Obtain certificates using a DNS TXT record (if you are using DNS Made Easy for DNS). (default: False)

`--dns-gehirn` Obtain certificates using a DNS TXT record (if you are using Gehirn Infrastructure Service for DNS).

(default: False)

`--dns-google` Obtain certificates using a DNS TXT record (if you are using Google Cloud DNS). (default: False)

`--dns-linode` Obtain certificates using a DNS TXT record (if you are using Linode for DNS). (default: False)

`--dns-luadns` Obtain certificates using a DNS TXT record (if you are using LuaDNS for DNS). (default: False)

`--dns-nsone` Obtain certificates using a DNS TXT record (if you are using NS1 for DNS). (default: False)

`--dns-ovh` Obtain certificates using a DNS TXT record (if you are using OVH for DNS). (default: False)

`--dns-rfc2136` Obtain certificates using a DNS TXT record (if you are using BIND for DNS). (default: False)

`--dns-route53` Obtain certificates using a DNS TXT record (if you are using Route53 for DNS). (default: False)

`--dns-sakuracloud` Obtain certificates using a DNS TXT record (if you are using Sakura Cloud for DNS). (default: False)

apache:

Apache Web Server plugin (Please note that the default values of the Apache plugin options change depending on the operating system Certbot is run on.)

`--apache-enmod` APACHE_ENMOD

Path to the Apache 'a2enmod' binary (default: None)

`--apache-dismod` APACHE_DISMOD

Path to the Apache 'a2dismod' binary (default: None)

`--apache-le-vhost-ext` APACHE_LE_VHOST_EXT

SSL vhost configuration extension (default: -le-ssl.conf)

`--apache-server-root` APACHE_SERVER_ROOT

Apache server root directory (default: /etc/apache2)

`--apache-vhost-root` APACHE_VHOST_ROOT

Apache server VirtualHost configuration root (default: None)

--apache-logs-root APACHE_LOGS_ROOT

Apache server logs directory (default:
/var/log/apache2)

--apache-challenge-location APACHE_CHALLENGE_LOCATION

Directory path for challenge configuration (default:
/etc/apache2)

--apache-handle-modules APACHE_HANDLE_MODULES

Let installer handle enabling required modules for you
(Only Ubuntu/Debian currently) (default: False)

--apache-handle-sites APACHE_HANDLE_SITES

Let installer handle enabling sites for you (Only
Ubuntu/Debian currently) (default: False)

--apache-ctl APACHE_CTL

Full path to Apache control script (default:
apache2ctl)

--apache-bin APACHE_BIN

Full path to apache2/httpd binary (default: None)

dns-cloudflare:

Obtain certificates using a DNS TXT record (if you are using Cloudflare
for DNS).

--dns-cloudflare-propagation-seconds DNS_CLOUDFLARE_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 10)

--dns-cloudflare-credentials DNS_CLOUDFLARE_CREDENTIALS

Cloudflare credentials INI file. (default: None)

dns-digitalocean:

Obtain certificates using a DNS TXT record (if you are using DigitalOcean
for DNS).

--dns-digitalocean-propagation-seconds DNS_DIGITALOCEAN_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 10)

--dns-digitalocean-credentials DNS_DIGITALOCEAN_CREDENTIALS

DigitalOcean credentials INI file. (default: None)

dns-dnsimple:

Obtain certificates using a DNS TXT record (if you are using DNSimple for DNS).

--dns-dnsimple-propagation-seconds DNS_DNSIMPLE_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 30)

--dns-dnsimple-credentials DNS_DNSIMPLE_CREDENTIALS

DNSimple credentials INI file. (default: None)

dns-dnsmadeeasy:

Obtain certificates using a DNS TXT record (if you are using DNS Made Easy for DNS).

--dns-dnsmadeeasy-propagation-seconds DNS_DNSMADEEASY_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 60)

--dns-dnsmadeeasy-credentials DNS_DNSMADEEASY_CREDENTIALS

DNS Made Easy credentials INI file. (default: None)

dns-gehirn:

Obtain certificates using a DNS TXT record (if you are using Gehirn Infrastructure Service for DNS).

--dns-gehirn-propagation-seconds DNS_GEHIRN_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 30)

--dns-gehirn-credentials DNS_GEHIRN_CREDENTIALS

Gehirn Infrastructure Service credentials file.
(default: None)

dns-google:

Obtain certificates using a DNS TXT record (if you are using Google Cloud DNS for DNS).

--dns-google-propagation-seconds DNS_GOOGLE_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate before asking the ACME server to verify the DNS record. (default: 60)

--dns-google-credentials DNS_GOOGLE_CREDENTIALS

Path to Google Cloud DNS service account JSON file to use instead of relying on Application Default Credentials (ADC). (See <https://cloud.google.com/docs/authentication/application-default-credentials> for information about ADC, <https://developers.google.com/identity/protocols/OAuth2ServiceAccount#creatinganaccount> for information about creating a service account, and https://cloud.google.com/dns/access-control#permissions_and_roles for information about the permissions required to modify Cloud DNS records.) (default: None)

--dns-google-project DNS_GOOGLE_PROJECT

The ID of the Google Cloud project that the Google Cloud DNS managed zone(s) reside in. This will be determined automatically if not specified. (default: None)

dns-linode:

Obtain certificates using a DNS TXT record (if you are using Linode for DNS).

--dns-linode-propagation-seconds DNS_LINODE_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate before asking the ACME server to verify the DNS record. (default: 120)

--dns-linode-credentials DNS_LINODE_CREDENTIALS

Linode credentials INI file. (default: None)

dns-luadns:

Obtain certificates using a DNS TXT record (if you are using LuaDNS for DNS).

--dns-luadns-propagation-seconds DNS_LUADNS_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 30)

--dns-luadns-credentials DNS_LUADNS_CREDENTIALS

LuaDNS credentials INI file. (default: None)

dns-nsone:

Obtain certificates using a DNS TXT record (if you are using NS1 for DNS).

--dns-nsone-propagation-seconds DNS_NSONE_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 30)

--dns-nsone-credentials DNS_NSONE_CREDENTIALS

NS1 credentials file. (default: None)

dns-ovh:

Obtain certificates using a DNS TXT record (if you are using OVH for DNS).

--dns-ovh-propagation-seconds DNS_OVH_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 120)

--dns-ovh-credentials DNS_OVH_CREDENTIALS

OVH credentials INI file. (default: None)

dns-rfc2136:

Obtain certificates using a DNS TXT record (if you are using BIND for
DNS).

--dns-rfc2136-propagation-seconds DNS_RFC2136_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate
before asking the ACME server to verify the DNS
record. (default: 60)

--dns-rfc2136-credentials DNS_RFC2136_CREDENTIALS

RFC 2136 credentials INI file. (default: None)

dns-route53:

Obtain certificates using a DNS TXT record (if you are using AWS Route53

for DNS).

dns-sakuracloud:

Obtain certificates using a DNS TXT record (if you are using Sakura Cloud for DNS).

--dns-sakuracloud-propagation-seconds DNS_SAKURACLOUD_PROPAGATION_SECONDS

The number of seconds to wait for DNS to propagate before asking the ACME server to verify the DNS record. (default: 90)

--dns-sakuracloud-credentials DNS_SAKURACLOUD_CREDENTIALS

Sakura Cloud credentials file. (default: None)

manual:

Authenticate through manual configuration or custom shell scripts. When using shell scripts, an authenticator script must be provided. The environment variables available to this script depend on the type of challenge. \$CERTBOT_DOMAIN will always contain the domain being authenticated. For HTTP-01 and DNS-01, \$CERTBOT_VALIDATION is the validation string, and \$CERTBOT_TOKEN is the filename of the resource requested when performing an HTTP-01 challenge. An additional cleanup script can also be provided and can use the additional variable \$CERTBOT_AUTH_OUTPUT which contains the stdout output from the auth script. For both authenticator and cleanup script, on HTTP-01 and DNS-01 challenges, \$CERTBOT_REMAINING_CHALLENGES will be equal to the number of challenges that remain after the current one, and \$CERTBOT_ALL_DOMAINS contains a comma-separated list of all domains that are challenged for the current certificate.

--manual-auth-hook MANUAL_AUTH_HOOK

Path or command to execute for the authentication script (default: None)

--manual-cleanup-hook MANUAL_CLEANUP_HOOK

Path or command to execute for the cleanup script (default: None)

nginx:

Nginx Web Server plugin

`--nginx-server-root NGINX_SERVER_ROOT`

Nginx server root directory. (default: /etc/nginx or
/usr/local/etc/nginx)

`--nginx-ctl NGINX_CTL`

Path to the 'nginx' binary, used for 'configtest' and
retrieving nginx version number. (default: nginx)

`--nginx-sleep-seconds NGINX_SLEEP_SECONDS`

Number of seconds to wait for nginx configuration
changes to apply when reloading. (default: 1)

null:

Null Installer

standalone:

Runs an HTTP server locally which serves the necessary validation files
under the /.well-known/acme-challenge/ request path. Suitable if there is
no HTTP server already running. HTTP challenge only (wildcards not
supported).

webroot:

Saves the necessary validation files to a .well-known/acme-challenge/
directory within the nominated webroot path. A separate HTTP server must
be running and serving files from the webroot path. HTTP challenge only
(wildcards not supported).

`--webroot-path WEBROOT_PATH, -w WEBROOT_PATH`

public_html / webroot path. This can be specified
multiple times to handle different domains; each
domain will have the webroot path that preceded it.

For instance: ``-w /var/www/example -d example.com -d
www.example.com -w /var/www/thing -d thing.net -d
m.thing.net`` (default: Ask)

`--webroot-map WEBROOT_MAP`

JSON dictionary mapping domains to webroot paths; this
implies -d for each entry. You may need to escape this
from your shell. E.g.: `--webroot-map`

`'{"eg1.is,m.eg1.is":"/www/eg1/", "eg2.is":"/www/eg2"}'`

This option is merged with, but takes precedence over,
-w / -d entries. At present, if you put webroot-map in
a config file, it needs to be on a single line, like:
webroot-map = {"example.com":"/var/www"}. (default:
{})

Author

Certbot

Copyright

2014-2018 - The Certbot software and documentation are licensed under the Apache 2.0 license
as described at <https://eff.org/cb-license>.

4.0

Feb 19, 2026

CERTBOT(1)