



### ***Linux Ubuntu 26.04 Manual Pages on command 'dlsym.3'***

#### ***\$ man dlsym.3***

dlsym(3) Library Functions Manual dlsym(3)

#### NAME

dlsym, dlvsym - obtain address of a symbol in a shared object or executable

#### LIBRARY

Dynamic linking library (libdl, -ldl)

#### SYNOPSIS

```
#include <dlfcn.h>

void *dlsym(void *restrict handle, const char *restrict symbol);

#define _GNU_SOURCE

#include <dlfcn.h>

void *dlvsym(void *restrict handle, const char *restrict symbol,
             const char *restrict version);
```

#### DESCRIPTION

The function `dlsym()` takes a "handle" of a dynamic loaded shared object returned by `dlopen(3)` along with a null-terminated symbol name, and returns the address where that symbol is loaded into memory. If the symbol is not found, in the specified object or any of the shared objects that were automatically loaded by `dlopen(3)` when that object was loaded, `dlsym()` returns `NULL`. (The search performed by `dlsym()` is breadth first through the dependency tree of these shared objects.)

In unusual cases (see NOTES) the value of the symbol could actually be `NULL`. Therefore, a `NULL` return from `dlsym()` need not indicate an error. The correct way to distinguish an error from a symbol whose value is `NULL` is to call `dlerror(3)` to clear any old error conditions, then call `dlsym()`, and then call `dlerror(3)` again, saving its return value into a

There are two special pseudo-handles that may be specified in handle:

Find the first occurrence of the desired symbol using the default shared object search order. The search will include global symbols in the executable and its dependencies, as well as symbols in shared objects that were dynamically loaded with the RTLD\_GLOBAL flag.

Find the next occurrence of the desired symbol in the search order after the current object. This allows one to provide a wrapper around a function in another shared object, so that, for example, the definition of a function in a preloaded shared object (see `LD_PRELOAD` in `ld.so(8)`) can find and invoke the "real" function provided in another shared object (or for that matter, the "next" definition of the function in cases where there are multiple layers of preloading).

The `_GNU_SOURCE` feature test macro must be defined in order to obtain the definitions of `RTLD_DEFAULT` and `RTLD_NEXT` from `<dlfcn.h>`.

The function `dlvsym()` does the same as `dlsym()` but takes a version string as an additional argument.

On success, these functions return the address associated with symbol. On failure, they return NULL; the error can be diagnosed using `dlerror(3)`.

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

| ? | Interface | ? | Attribute | ? | Value | ? |
|---|-----------|---|-----------|---|-------|---|
|---|-----------|---|-----------|---|-------|---|

[illegible]

? dlsym(), dlvsym()                      ? Thread safety ? MT-Safe ?

[illegible]

dlsym()

POSIX.1-2008.

dlvsym()

GNU.

## HISTORY

`dlsym()`

glibc 2.0. POSIX.1-2001.

`dlvsym()`

glibc 2.1.

## NOTES

There are several scenarios when the address of a global symbol is `NULL`. For example, a symbol can be placed at zero address by the linker, via a linker script or with `--defsym` command-line option. Undefined weak symbols also have `NULL` value. Finally, the symbol value may be the result of a GNU indirect function (IFUNC) resolver function that returns `NULL` as the resolved value. In the latter case, `dlsym()` also returns `NULL` without error. However, in the former two cases, the behavior of GNU dynamic linker is inconsistent: relocation processing succeeds and the symbol can be observed to have `NULL` value, but `dlsym()` fails and `dlerror()` indicates a lookup error.

### History

The `dlsym()` function is part of the `dlopen` API, derived from SunOS. That system does not have `dlvsym()`.

## EXAMPLES

See `dlopen(3)`.

## SEE ALSO

`dl_iterate_phdr(3)`, `dladdr(3)`, `dlerror(3)`, `dlinfo(3)`, `dlopen(3)`, `ld.so(8)`

Linux man-pages 6.17

2026-02-08

`dlsym(3)`