



Linux Ubuntu 26.04 Manual Pages on command 'env.1'

\$ man env.1

ENV(1) General Commands Manual ENV(1)

NAME

env - Set each NAME to VALUE in the environment and run COMMAND

SYNOPSIS

env [-i|--ignore-environment] [-C|--chdir] [-O|--null] [-f|--file] [-u|--unset] [-v|--de?
bug]... [-S|--split-string] [-a|--argv0] [--ignore-signal] [--default-signal] [--block-sig?
nal] [--list-signal-handling] [-h|--help] [-V|--version] [vars]

DESCRIPTION

Set each NAME to VALUE in the environment and run COMMAND

OPTIONS

-i, --ignore-environment

start with an empty environment

-C, --chdir <DIR>

change working directory to DIR

-O, --null

end each output line with a 0 byte rather than a newline (only valid when printing
the environment)

-f, --file <PATH>

read and set variables from a ".env"-style configuration file (prior to any unset
and/or set)

-u, --unset <NAME>

remove variable from the environment

-v, --debug

print verbose information for each processing step

-S, --split-string <S>

process and split S into separate arguments; used to pass multiple arguments on she?

bang lines

-a, --argv0 <a>

Override the zeroth argument passed to the command being executed. Without this op?

tion a default value of `command` is used.

--ignore-signal[=<SIG>]

set handling of SIG signal(s) to do nothing

--default-signal[=<SIG>]

reset handling of SIG signal(s) to the default action

--block-signal[=<SIG>]

block delivery of SIG signal(s) while running COMMAND

--list-signal-handling

list signal handling changes requested by preceding options

-h, --help

Print help

-V, --version

Print version

[vars]

EXTRA

A mere - implies -i. If no COMMAND, print the resulting environment.

VERSION

v(utils coreutils) 0.8.0

2026-04-16

ENV(1)