



Linux Ubuntu 26.04 Manual Pages on command 'eslint.1'

\$ man eslint.1

ESLINT(1) User Commands ESLINT(1)

NAME

eslint - JavaScript

DESCRIPTION

eslint [options] file.js [file.js] [dir]

Basic configuration:

--no-eslintrc

Disable use of configuration from .eslintrc.*

-c, --config path::String

Use this configuration, overriding .eslintrc.* config options if present

--env [String]

Specify environments

--ext [String]

Specify JavaScript file extensions - default: .js

--global [String]

Define global variables

--parser String

Specify the parser to be used

--parser-options Object

Specify parser options

--resolve-plugins-relative-to path::String

A folder where plugins should be resolved from, CWD by default

Specifying rules and plugins:

`--rulesdir [path::String]`

Use additional rules from this directory

`--plugin [String]`

Specify plugins

`--rule Object`

Specify rules

Fixing problems:

`--fix` Automatically fix problems

`--fix-dry-run`

Automatically fix problems without saving the changes to the file system

`--fix-type Array`

Specify the types of fixes to apply (problem, suggestion, layout)

Ignoring files:

`--ignore-path path::String`

Specify path of ignore file

`--no-ignore`

Disable use of ignore files and patterns

`--ignore-pattern [String]`

Pattern of files to ignore (in addition to those in .eslintignore)

Using stdin:

`--stdin`

Lint code provided on <STDIN> - default: false

`--stdin-filename String`

Specify filename to process STDIN as

Handling warnings:

`--quiet`

Report errors only - default: false

`--max-warnings Int`

Number of warnings to trigger nonzero exit code - default: -1

Output:

`-o, --output-file path::String`

Specify file to write report to

`-f, --format String`

Use a specific output format - default: stylish

--color, --no-color

Force enabling/disabling of color

Inline configuration comments:

--no-inline-config

Prevent comments from changing config or rules

--report-unused-disable-directives

Adds reported errors for unused eslint-disable directives

Caching:

--cache

Only check changed files - default: false

--cache-file path::String

Path to the cache file. Deprecated: use --cache-location - default: .eslintcache

--cache-location path::String

Path to the cache file or directory

Miscellaneous:

--init Run config initialization wizard - default: false

--debug

Output debugging information

-h, --help

Show help

-v, --version

Output the version number

--print-config path::String

Print the configuration for the given file