



Linux Ubuntu 26.04 Manual Pages on command 'eventfd.2'

\$ man eventfd.2

eventfd(2) System Calls Manual eventfd(2)

NAME

eventfd - create a file descriptor for event notification

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <sys/eventfd.h>
```

```
int eventfd(unsigned int initval, int flags);
```

DESCRIPTION

eventfd() creates an "eventfd object" that can be used as an event wait/notify mechanism by user-space applications, and by the kernel to notify user-space applications of events. The object contains an unsigned 64-bit integer (uint64_t) counter that is maintained by the kernel. This counter is initialized with the value specified in the argument initval.

As its return value, eventfd() returns a new file descriptor that can be used to refer to the eventfd object.

The following values may be bitwise ORed in flags to change the behavior of eventfd():

EFD_CLOEXEC (since Linux 2.6.27)

Set the close-on-exec (FD_CLOEXEC) flag on the new file descriptor. See the description of the O_CLOEXEC flag in open(2) for reasons why this may be useful.

EFD_NONBLOCK (since Linux 2.6.27)

Set the O_NONBLOCK file status flag on the open file description (see open(2)) referred to by the new file descriptor. Using this flag saves extra calls to fcntl(2) to achieve the same result.

EFD_SEMAPHORE (since Linux 2.6.30)

Provide semaphore-like semantics for reads from the new file descriptor. See below.

Up to Linux 2.6.26, the flags argument is unused, and must be specified as zero.

The following operations can be performed on the file descriptor returned by eventfd():

read(2)

Each successful read(2) returns an 8-byte integer. A read(2) fails with the error EINVAL if the size of the supplied buffer is less than 8 bytes.

The value returned by read(2) is in host byte order—that is, the native byte order for integers on the host machine.

The semantics of read(2) depend on whether the eventfd counter currently has a nonzero value and whether the EFD_SEMAPHORE flag was specified when creating the eventfd file descriptor:

? If EFD_SEMAPHORE was not specified and the eventfd counter has a nonzero value, then a read(2) returns 8 bytes containing that value, and the counter's value is reset to zero.

? If EFD_SEMAPHORE was specified and the eventfd counter has a nonzero value, then a read(2) returns 8 bytes containing the value 1, and the counter's value is decremented by 1.

? If the eventfd counter is zero at the time of the call to read(2), then the call either blocks until the counter becomes nonzero (at which time, the read(2) proceeds as described above) or fails with the error EAGAIN if the file descriptor has been made nonblocking.

write(2)

A write(2) call adds the 8-byte integer value supplied in its buffer to the counter.

The maximum value that may be stored in the counter is the largest unsigned 64-bit value minus 1 (i.e., 0xffffffffffff). If the addition would cause the counter's value to exceed the maximum, then the write(2) either blocks until a read(2) is performed on the file descriptor, or fails with the error EAGAIN if the file descriptor has been made nonblocking.

A write(2) fails with the error EINVAL if the size of the supplied buffer is less than 8 bytes, or if an attempt is made to write the value 0xffffffffffff.

poll(2)

select(2)

(and similar)

The returned file descriptor supports `poll(2)` (and analogously `epoll(7)`) and `select(2)`, as follows:

- ? The file descriptor is readable (the `select(2)` `readfds` argument; the `poll(2)` `POLLIN` flag) if the counter has a value greater than 0.
- ? The file descriptor is writable (the `select(2)` `writfds` argument; the `poll(2)` `POLLOUT` flag) if it is possible to write a value of at least "1" without blocking.
- ? If an overflow of the counter value was detected, then `select(2)` indicates the file descriptor as being both readable and writable, and `poll(2)` returns a `POLLERR` event. As noted above, `write(2)` can never overflow the counter. However an overflow can occur if 2^{64} eventfd "signal posts" were performed by the KAIO subsystem (theoretically possible, but practically unlikely). If an overflow has occurred, then `read(2)` will return that maximum `uint64_t` value (i.e., `0xffffffffffff`).

The eventfd file descriptor also supports the other file-descriptor multiplexing APIs: `pselect(2)` and `ppoll(2)`.

`close(2)`

When the file descriptor is no longer required it should be closed. When all file descriptors associated with the same eventfd object have been closed, the resources for object are freed by the kernel.

A copy of the file descriptor created by `eventfd()` is inherited by the child produced by `fork(2)`. The duplicate file descriptor is associated with the same eventfd object. File descriptors created by `eventfd()` are preserved across `execve(2)`, unless the `close-on-exec` flag has been set.

RETURN VALUE

On success, `eventfd()` returns a new eventfd file descriptor. On error, -1 is returned and `errno` is set to indicate the error.

ERRORS

EINVAL An unsupported value was specified in flags.

EMFILE The per-process limit on the number of open file descriptors has been reached.

ENFILE The system-wide limit on the total number of open files has been reached.

ENODEV Could not mount (internal) anonymous inode device.

ENOMEM There was insufficient memory to create a new eventfd file descriptor.

ATTRIBUTES

Interface	Attribute	Value
eventfd()	Thread safety	MT-Safe

When used in the kernel, an eventfd file descriptor can provide a bridge from kernel to user space, allowing, for example, functionalities like KAIO (kernel AIO) to signal to a file descriptor that some operation is complete.

A key point about an eventfd file descriptor is that it can be monitored just like any other file descriptor using `select(2)`, `poll(2)`, or `epoll(7)`. This means that an application can simultaneously monitor the readiness of "traditional" files and the readiness of other kernel mechanisms that support the eventfd interface. (Without the eventfd() interface, these mechanisms could not be multiplexed via `select(2)`, `poll(2)`, or `epoll(7)`.)

The current value of an eventfd counter can be viewed via the entry for the corresponding file descriptor in the process's `/proc/pid/fdinfo` directory. See `proc(5)` for further details.

EXAMPLES

The following program creates an eventfd file descriptor and then forks to create a child process. While the parent briefly sleeps, the child writes each of the integers supplied in the program's command-line arguments to the eventfd file descriptor. When the parent has finished sleeping, it reads from the eventfd file descriptor.

The following shell session shows a sample run of the program:

```
$ ./a.out 1 2 4 7 14
Child writing 1 to efd
Child writing 2 to efd
Child writing 4 to efd
Child writing 7 to efd
Child writing 14 to efd
Child completed write loop
Parent about to read
Parent read 28 (0x1c) from efd
```

Program source

```
#include <err.h>
#include <inttypes.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/eventfd.h>
#include <sys/types.h>
```

```

#include <unistd.h>

int
main(int argc, char *argv[])
{
    int    efd;

    uint64_t u;

    ssize_t s;

    if (argc < 2) {
        fprintf(stderr, "Usage: %s <num>...\n", argv[0]);
        exit(EXIT_FAILURE);
    }

    efd = eventfd(0, 0);

    if (efd == -1)
        err(EXIT_FAILURE, "eventfd");

    switch (fork()) {
    case 0:

        for (size_t j = 1; j < argc; j++) {
            printf("Child writing %s to efd\n", argv[j]);

            u = strtoull(argv[j], NULL, 0);

            /* strtoull() allows various bases */

            s = write(efd, &u, sizeof(uint64_t));

            if (s != sizeof(uint64_t))
                err(EXIT_FAILURE, "write");
        }

        printf("Child completed write loop\n");

        exit(EXIT_SUCCESS);

    default:

        sleep(2);

        printf("Parent about to read\n");

        s = read(efd, &u, sizeof(uint64_t));

        if (s != sizeof(uint64_t))
            err(EXIT_FAILURE, "read");

        printf("Parent read %\"PRIu64\" (%\"#\"PRIx64\") from efd\n", u, u);
    }
}

```

```
    exit(EXIT_SUCCESS);  
case -1:  
    err(EXIT_FAILURE, "fork");  
}  
}
```

SEE ALSO

futex(2), pipe(2), poll(2), read(2), select(2), signalfd(2), timerfd_create(2), write(2),
epoll(7), sem_overview(7)

Linux man-pages 6.17

2026-02-08

eventfd(2)