



Linux Ubuntu 26.04 Manual Pages on command 'fish_indent.1'

\$ man fish_indent.1

FISH_INDENT(1) fish-shell FISH_INDENT(1)

NAME

fish_indent - indenter and prettifier

SYNOPSIS

fish_indent [OPTIONS] [FILE ...]

DESCRIPTION

fish_indent is used to indent a piece of fish code. fish_indent reads commands from standard input or the given filenames and outputs them to standard output or a specified file (if -w is given).

The following options are available:

-w or --write

Indents a specified file and immediately writes to that file.

-i or --no-indent

Do not indent commands; only reformat to one job per line.

--only-indent

Do not reformat, only indent each line.

--only-unindent

Do not reformat, only unindent each line.

-c or --check

Do not indent, only return 0 if the code is already indented as fish_indent would, the number of failed files otherwise. Also print the failed filenames if not reading from standard input.

-v or --version

Displays the current fish version and then exits.

`--ansi` Colorizes the output using ANSI escape sequences using the colors defined in the environment (such as `fish_color_command` `<#envvar-fish_color_command>`).

`--html` Outputs HTML, which supports syntax highlighting if the appropriate CSS is defined.

The CSS class names are the same as the variable names, such as `fish_color_command`.

`--dump-parse-tree`

Dumps information about the parsed statements to standard error. This is likely to be of interest only to people working on the fish source code.

`-h` or `--help`

Displays help about using this command.

Copyright

fish-shell developers

4.2

Jan 02, 2026

FISH_INDENT(1)