



Linux Ubuntu 26.04 Manual Pages on command 'free_hugepages.2'

\$ man free_hugepages.2

alloc_hugepages(2) System Calls Manual alloc_hugepages(2)

NAME

alloc_hugepages, free_hugepages - allocate or free huge pages

SYNOPSIS

```
void *syscall(size_t size;
               SYS_alloc_hugepages, int key,
               void addr[size], size_t size,
               int prot, int flag);

int syscall(SYS_free_hugepages, void *addr);
```

Note: glibc provides no wrappers for these system calls, necessitating the use of
syscall(2).

DESCRIPTION

The system calls alloc_hugepages() and free_hugepages() were introduced in Linux 2.5.36 and removed again in Linux 2.5.54. They existed only on i386 and ia64 (when built with CON? FIG_HUGETLB_PAGE). In Linux 2.4.20, the syscall numbers exist, but the calls fail with the error ENOSYS.

On i386 the memory management hardware knows about ordinary pages (4 KiB) and huge pages (2 or 4 MiB). Similarly ia64 knows about huge pages of several sizes. These system calls serve to map huge pages into the process's memory or to free them again. Huge pages are locked into memory, and are not swapped.

The key argument is an identifier. When zero the pages are private, and not inherited by children. When positive the pages are shared with other applications using the same key, and inherited by child processes.

The `addr` argument of `free_hugepages()` tells which page is being freed: it was the return value of a call to `alloc_hugepages()`. (The memory is first actually freed when all users have released it.) The `addr` argument of `alloc_hugepages()` is a hint, that the kernel may or may not follow. Addresses must be properly aligned.

The `size` argument is the size of the required segment. It must be a multiple of the huge page size.

The `prot` argument specifies the memory protection of the segment. It is one of `PROT_READ`, `PROT_WRITE`, `PROT_EXEC`.

The `flag` argument is ignored, unless `key` is positive. In that case, if `flag` is `IPC_CREAT`, then a new huge page segment is created when none with the given `key` existed. If this flag is not set, then `ENOENT` is returned when no segment with the given `key` exists.

RETURN VALUE

On success, `alloc_hugepages()` returns the allocated virtual address, and `free_hugepages()` returns zero. On error, `-1` is returned, and `errno` is set to indicate the error.

ERRORS

`ENOSYS` The system call is not supported on this kernel.

FILES

`/proc/sys/vm/nr_hugepages`

Number of configured hugetlb pages. This can be read and written.

`/proc/meminfo`

Gives info on the number of configured hugetlb pages and on their size in the three variables `HugePages_Total`, `HugePages_Free`, `Hugepagesize`.

STANDARDS

Linux on Intel processors.

HISTORY

These system calls are gone; they existed only in Linux 2.5.36 through to Linux 2.5.54.

NOTES

Now the hugetlbfs filesystem can be used instead. Memory backed by huge pages (if the CPU supports them) is obtained by using `mmap(2)` to map files in this virtual filesystem.

The maximal number of huge pages can be specified using the `hugepages=` boot parameter.