



Linux Ubuntu 26.04 Manual Pages on command 'getcpu.2'

\$ man getcpu.2

getcpu(2) System Calls Manual getcpu(2)

NAME

getcpu - determine CPU and NUMA node on which the calling thread is running

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#define _GNU_SOURCE          /* See feature_test_macros(7) */
#include <sched.h>

int getcpu(unsigned int *_Nullable cpu, unsigned int *_Nullable node);
```

DESCRIPTION

The `getcpu()` system call identifies the processor and node on which the calling thread or process is currently running and writes them into the integers pointed to by the `cpu` and `node` arguments. The processor is a unique small integer identifying a CPU. The node is a unique small identifier identifying a NUMA node. When either `cpu` or `node` is `NULL` nothing is written to the respective pointer.

The information placed in `cpu` is guaranteed to be current only at the time of the call: unless the CPU affinity has been fixed using `sched_setaffinity(2)`, the kernel might change the CPU at any time. (Normally this does not happen because the scheduler tries to minimize movements between CPUs to keep caches hot, but it is possible.) The caller must allow for the possibility that the information returned in `cpu` and `node` is no longer current by the time the call returns.

RETURN VALUE

On success, 0 is returned. On error, -1 is returned, and `errno` is set to indicate the error.

ror.

ERRORS

EFAULT Arguments point outside the calling process's address space.

STANDARDS

Linux.

HISTORY

Linux 2.6.19 (x86-64 and i386), glibc 2.29.

C library/kernel differences

The kernel system call has a third argument:

```
int getcpu(unsigned int *cpu, unsigned int *node,  
            struct getcpu_cache *tcache);
```

The `tcache` argument is unused since Linux 2.6.24, and (when invoking the system call directly) should be specified as `NULL`, unless portability to Linux 2.6.23 or earlier is required.

In Linux 2.6.23 and earlier, if the `tcache` argument was non-`NULL`, then it specified a pointer to a caller-allocated buffer in thread-local storage that was used to provide a caching mechanism for `getcpu()`. Use of the cache could speed `getcpu()` calls, at the cost that there was a very small chance that the returned information would be out of date. The caching mechanism was considered to cause problems when migrating threads between CPUs, and so the argument is now ignored.

NOTES

Linux makes a best effort to make this call as fast as possible. (On some architectures, this is done via an implementation in the `vdso(7)`.) The intention of `getcpu()` is to allow programs to make optimizations with per-CPU data or for NUMA optimization.

SEE ALSO

`mbind(2)`, `sched_setaffinity(2)`, `set_mempolicy(2)`, `sched_getcpu(3)`, `cpuset(7)`, `vdso(7)`

Linux man-pages 6.17

2026-02-08

`getcpu(2)`