



Linux Ubuntu 26.04 Manual Pages on command 'getdents64.2'

\$ man getdents64.2

getdents(2) System Calls Manual getdents(2)

NAME

getdents, getdents64 - get directory entries

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <sys/syscall.h>    /* Definition of SYS_* constants */
#include <unistd.h>

long syscall(SYS_getdents, unsigned int fd, struct linux_dirent *dirp,
            unsigned int count);

#define _GNU_SOURCE          /* See feature_test_macros(7) */
#include <dirent.h>

ssize_t getdents64(size_t count;
                  int fd, void dirp[count], size_t count);
```

Note: glibc provides no wrapper for getdents(), necessitating the use of syscall(2).

Note: There is no definition of struct linux_dirent in glibc; see NOTES.

DESCRIPTION

These are not the interfaces you are interested in. Look at readdir(3) for the POSIX-conforming C library interface. This page documents the bare kernel system call interfaces.

getdents()

The system call getdents() reads several linux_dirent structures from the directory referred to by the open file descriptor fd into the buffer pointed to by dirp. The argument count specifies the size of that buffer.

The linux_dirent structure is declared as follows:

```
struct linux_dirent {
    unsigned long d_ino;    /* Inode number */
    unsigned long d_off;    /* Not an offset; see below */
    unsigned short d_reclen; /* Length of this linux_dirent */
    char          d_name[]; /* Filename (null-terminated) */
                        /* length is actually (d_reclen - 2 -
                        /* offsetof(struct linux_dirent, d_name)) */

    /*
    char          pad;      // Zero padding byte
    char          d_type;   // File type (only since Linux
                        // 2.6.4); offset is (d_reclen - 1)
    */
}
```

d_ino is an inode number. d_off is a filesystem-specific value with no specific meaning to user space, though on older filesystems it used to be the distance from the start of the directory to the start of the next linux_dirent; see readdir(3). d_reclen is the size of this entire linux_dirent. d_name is a null-terminated filename.

d_type is a byte at the end of the structure that indicates the file type. It contains one of the following values (defined in <dirent.h>):

DT_BLK	This is a block device.
DT_CHR	This is a character device.
DT_DIR	This is a directory.
DT_FIFO	This is a named pipe (FIFO).
DT_LNK	This is a symbolic link.
DT_REG	This is a regular file.
DT SOCK	This is a UNIX domain socket.
DT_UNKNOWN	The file type is unknown.

The d_type field is implemented since Linux 2.6.4. It occupies a space that was previously a zero-filled padding byte in the linux_dirent structure. Thus, on kernels up to and including Linux 2.6.3, attempting to access this field always provides the value 0 (DT_UNKNOWN).

Currently, only some filesystems (among them: Btrfs, ext2, ext3, and ext4) have full support

for returning the file type in `d_type`. All applications must properly handle a return of `DT_UNKNOWN`.

getdents64()

The original Linux `getdents()` system call did not handle large filesystems and large file offsets. Consequently, Linux 2.4 added `getdents64()`, with wider types for the `d_ino` and `d_off` fields. In addition, `getdents64()` supports an explicit `d_type` field.

The `getdents64()` system call is like `getdents()`, except that its second argument is a pointer to a buffer containing structures of the following type:

```
struct linux_dirent64 {
    ino64_t    d_ino; /* 64-bit inode number */
    off64_t    d_off; /* Not an offset; see getdents() */
    unsigned short d_reclen; /* Size of this dirent */
    unsigned char d_type; /* File type */
    char        d_name[]; /* Filename (null-terminated) */
};
```

RETURN VALUE

On success, the number of bytes read is returned. On end of directory, 0 is returned. On error, -1 is returned, and `errno` is set to indicate the error.

ERRORS

`EBADF` Invalid file descriptor `fd`.

`EFAULT` Argument points outside the calling process's address space.

`EINVAL` Result buffer is too small.

`ENOENT` No such directory.

ENOTDIR

File descriptor does not refer to a directory.

STANDARDS

None.

HISTORY

SVr4.

`getdents64()`

glibc 2.30.

NOTES

glibc does not provide a wrapper for `getdents()`; call `getdents()` using `syscall(2)`. In that

case you will need to define the linux_dirent or linux_dirent64 structure yourself.

Probably, you want to use readdir(3) instead of these system calls.

These calls supersede readdir(2).

EXAMPLES

The program below demonstrates the use of getdents(). The following output shows an example of what we see when running this program on an ext2 directory:

```
$ ./a.out /testfs/
----- nread=120 -----
inode#  file type  d_reclen  d_off  d_name
    2  directory   16       12  .
    2  directory   16       24  ..
   11  directory   24       44  lost+found
   12  regular     16       56  a
228929 directory   16       68  sub
 16353 directory   16       80  sub2
130817 directory   16     4096  sub3
```

Program source

```
#define _GNU_SOURCE

#include <dirent.h> /* Defines DT_* constants */
#include <err.h>
#include <fcntl.h>
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/syscall.h>
#include <sys/types.h>
#include <unistd.h>

struct linux_dirent {
    unsigned long d_ino;
    off_t        d_off;
    unsigned short d_reclen;
    char          d_name[];
};
```

```

#define BUF_SIZE 1024

int

main(int argc, char *argv[])
{
    int          fd;

    char          d_type;

    char          buf[BUF_SIZE];

    long          nread;

    struct linux_dirent *d;

    fd = open(argc > 1 ? argv[1] : ".", O_RDONLY | O_DIRECTORY);

    if (fd == -1)
        err(EXIT_FAILURE, "open");

    for (;;) {

        nread = syscall(SYS_getdents, fd, buf, BUF_SIZE);

        if (nread == -1)
            err(EXIT_FAILURE, "getdents");

        if (nread == 0)
            break;

        printf("----- nread=%ld -----\\n", nread);

        printf("inode#   file type  d_reclen  d_off  d_name\\n");

        for (size_t bpos = 0; bpos < nread;) {

            d = (struct linux_dirent *) (buf + bpos);

            printf("%8lu ", d->d_ino);

            d_type = *(buf + bpos + d->d_reclen - 1);

            printf("%-10s ", (d_type == DT_REG) ? "regular" :

                (d_type == DT_DIR) ? "directory" :

                (d_type == DT_FIFO) ? "FIFO" :

                (d_type == DT_SOCKET) ? "socket" :

                (d_type == DT_LNK) ? "symlink" :

                (d_type == DT_BLK) ? "block dev" :

                (d_type == DT_CHR) ? "char dev" : "???");

            printf("%4d %10jd  %s\\n", d->d_reclen,

                (intmax_t) d->d_off, d->d_name);

```

```
        bpos += d->d_reclen;
    }
}
exit(EXIT_SUCCESS);
}
```

SEE ALSO

readdir(2), readdir(3), inode(7)

Linux man-pages 6.17

2026-02-08

getdents(2)