



Linux Ubuntu 26.04 Manual Pages on command 'getppid.2'

\$ man getppid.2

getpid(2) System Calls Manual getpid(2)

NAME

getpid, getppid - get process identification

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <unistd.h>

pid_t getpid(void);

pid_t getppid(void);
```

DESCRIPTION

getpid() returns the process ID (PID) of the calling process. (This is often used by routines that generate unique temporary filenames.)

getppid() returns the process ID of the parent of the calling process. This will be either the ID of the process that created this process using fork(), or, if that process has already terminated, the ID of the process to which this process has been reparented (either init(1) or a "subreaper" process defined via the prctl(2) PR_SET_CHILD_SUBREAPER operation).

ERRORS

These functions are always successful.

VERSIONS

On Alpha, instead of a pair of getpid() and getppid() system calls, a single getxpid() system call is provided, which returns a pair of PID and parent PID. The glibc getpid() and getppid() wrapper functions transparently deal with this. See syscall(2) for details regarding register mapping.

STANDARDS

POSIX.1-2024.

HISTORY

4.3BSD, SVr4, POSIX.1-1988.

C library/kernel differences

From glibc 2.3.4 up to and including glibc 2.24, the glibc wrapper function for `getpid()` cached PIDs, with the goal of avoiding additional system calls when a process calls `getpid()` repeatedly. Normally this caching was invisible, but its correct operation relied on support in the wrapper functions for `fork(2)`, `vfork(2)`, and `clone(2)`: if an application bypassed the glibc wrappers for these system calls by using `syscall(2)`, then a call to `getpid()` in the child would return the wrong value (to be precise: it would return the PID of the parent process). In addition, there were cases where `getpid()` could return the wrong value even when invoking `clone(2)` via the glibc wrapper function. (For a discussion of one such case, see [BUGS](#) in `clone(2)`.) Furthermore, the complexity of the caching code had been the source of a few bugs within glibc over the years.

Because of the aforementioned problems, since glibc 2.25, the PID cache is removed: calls to `getpid()` always invoke the actual system call, rather than returning a cached value.

NOTES

If the caller's parent is in a different PID namespace (see `pid_namespaces(7)`), `getppid()` returns 0.

From a kernel perspective, the PID (which is shared by all of the threads in a multithreaded process) is sometimes also known as the thread group ID (TGID). This contrasts with the kernel thread ID (TID), which is unique for each thread. For further details, see `gettid(2)` and the discussion of the `CLONE_THREAD` flag in `clone(2)`.

SEE ALSO

`clone(2)`, `fork(2)`, `gettid(2)`, `kill(2)`, `exec(3)`, `mkstemp(3)`, `tempnam(3)`, `tmpfile(3)`, `tmpnam(3)`, `credentials(7)`, `pid_namespaces(7)`