



Linux Ubuntu 26.04 Manual Pages on command 'git-branch.1'

\$ man git-branch.1

GIT-BRANCH(1) Git Manual GIT-BRANCH(1)

NAME

git-branch - List, create, or delete branches

SYNOPSIS

```
git branch [--color[=<when>] | --no-color] [--show-current]
           [-v [--abbrev=<n> | --no-abbrev]]
           [--column[=<options>] | --no-column] [--sort=<key>]
           [--merged [<commit>]] [--no-merged [<commit>]]
           [--contains [<commit>]] [--no-contains [<commit>]]
           [--points-at <object>] [--format=<format>]
           [(-r|--remotes) | (-a|--all)]
           [--list] [<pattern>...]

git branch [--track[=(direct|inherit)] | --no-track] [-f]
           [--recurse-submodules] <branch-name> [<start-point>]

git branch (--set-upstream-to=<upstream>|-u <upstream>) [<branch-name>]

git branch --unset-upstream [<branch-name>]

git branch (-m|-M) [<old-branch>] <new-branch>

git branch (-c|-C) [<old-branch>] <new-branch>

git branch (-d|-D) [-r] <branch-name>...

git branch --edit-description [<branch-name>]
```

DESCRIPTION

If --list is given, or if there are no non-option arguments, existing branches are listed; the current branch will be highlighted in green and marked with an asterisk. Any branches

checked out in linked worktrees will be highlighted in cyan and marked with a plus sign.

Option `-r` causes the remote-tracking branches to be listed, and option `-a` shows both local and remote branches.

If a `<pattern>` is given, it is used as a shell wildcard to restrict the output to matching branches. If multiple patterns are given, a branch is shown if it matches any of the patterns.

Note that when providing a `<pattern>`, you must use `--list`; otherwise the command may be interpreted as branch creation.

With `--contains`, shows only the branches that contain the named commit (in other words, the branches whose tip commits are descendants of the named commit), `--no-contains` inverts it.

With `--merged`, only branches merged into the named commit (i.e. the branches whose tip commits are reachable from the named commit) will be listed. With `--no-merged` only branches not merged into the named commit will be listed. If the `<commit>` argument is missing it defaults to `HEAD` (i.e. the tip of the current branch).

The command's second form creates a new branch head named `<branch-name>` which points to the current `HEAD`, or `<start-point>` if given. As a special case, for `<start-point>`, you may use `<rev-A>...<rev-B>` as a shortcut for the merge base of `<rev-A>` and `<rev-B>` if there is exactly one merge base. You can leave out at most one of `<rev-A>` and `<rev-B>`, in which case it defaults to `HEAD`.

Note that this will create the new branch, but it will not switch the working tree to it; use `git switch <new-branch>` to switch to the new branch.

When a local branch is started off a remote-tracking branch, Git sets up the branch (specifically the `branch.<name>.remote` and `branch.<name>.merge` configuration entries) so that `git pull` will appropriately merge from the remote-tracking branch. This behavior may be changed via the global `branch.autoSetupMerge` configuration flag. That setting can be overridden by using the `--track` and `--no-track` options, and changed later using `git branch --set-upstream-to`.

With a `-m` or `-M` option, `<old-branch>` will be renamed to `<new-branch>`. If `<old-branch>` had a corresponding reflog, it is renamed to match `<new-branch>`, and a reflog entry is created to remember the branch renaming. If `<new-branch>` exists, `-M` must be used to force the rename to happen.

The `-c` and `-C` options have the exact same semantics as `-m` and `-M`, except instead of the branch being renamed, it will be copied to a new name, along with its config and reflog.

With a `-d` or `-D` option, `<branch-name>` will be deleted. You may specify more than one branch for deletion. If the branch currently has a reflog then the reflog will also be deleted.

Use `-r` together with `-d` to delete remote-tracking branches. Note, that it only makes sense to delete remote-tracking branches if they no longer exist in the remote repository or if `git fetch` was configured not to fetch them again. See also the `prune` subcommand of `git-remote(1)` for a way to clean up all obsolete remote-tracking branches.

OPTIONS

`-d, --delete`

Delete a branch. The branch must be fully merged in its upstream branch, or in HEAD if no upstream was set with `--track` or `--set-upstream-to`.

`-D`

Shortcut for `--delete --force`.

`--create-reflog`

Create the branch's reflog. This activates recording of all changes made to the branch ref, enabling use of date based sha1 expressions such as `<branch-name>@{yesterday}`. Note that in non-bare repositories, reflogs are usually enabled by default by the `core.logAllRefUpdates` config option. The negated form `--no-create-reflog` only overrides an earlier `--create-reflog`, but currently does not negate the setting of `core.logAllRefUpdates`.

`-f, --force`

Reset `<branch-name>` to `<start-point>`, even if `<branch-name>` exists already. Without `-f`, `git branch` refuses to change an existing branch. In combination with `-d` (or `--delete`), allow deleting the branch irrespective of its merged status, or whether it even points to a valid commit. In combination with `-m` (or `--move`), allow renaming the branch even if the new branch name already exists, the same applies for `-c` (or `--copy`).

Note that `git branch -f <branch-name> [<start-point>]`, even with `-f`, refuses to change an existing branch `<branch-name>` that is checked out in another worktree linked to the same repository.

`-m, --move`

Move/rename a branch, together with its config and reflog.

`-M`

Shortcut for `--move --force`.

`-c, --copy`

Copy a branch, together with its config and reflog.

-C

Shortcut for `--copy --force`.

--color[=<when>]

Color branches to highlight current, local, and remote-tracking branches. The value must be always (the default), never, or auto.

--no-color

Turn off branch colors, even when the configuration file gives the default to color output. Same as `--color=never`.

-i, --ignore-case

Sorting and filtering branches are case insensitive.

--omit-empty

Do not print a newline after formatted refs where the format expands to the empty string.

--column[=<options>], --no-column

Display branch listing in columns. See configuration variable `column.branch` for option syntax. `--column` and `--no-column` without options are equivalent to always and never respectively.

This option is only applicable in non-verbose mode.

--sort=<key>

Sort based on `<key>`. Prefix `-` to sort in descending order of the value. You may use the `--sort=<key>` option multiple times, in which case the last key becomes the primary key.

The keys supported are the same as those in `git-for-each-ref(1)`. Sort order defaults to the value configured for the `branch.sort` variable if it exists, or to sorting based on the full refname (including `refs/...` prefix). This lists detached HEAD (if present) first, then local branches and finally remote-tracking branches. See `git-config(1)`.

-r, --remotes

List or delete (if used with `-d`) the remote-tracking branches. Combine with `--list` to match the optional pattern(s).

-a, --all

List both remote-tracking branches and local branches. Combine with `--list` to match optional pattern(s).

-l, --list

List branches. With optional <pattern>..., e.g. `git branch --list 'maint-*`, list only the branches that match the pattern(s).

`--show-current`

Print the name of the current branch. In detached HEAD state, nothing is printed.

`-v, -vv, --verbose`

When in list mode, show sha1 and commit subject line for each head, along with relationship to upstream branch (if any). If given twice, print the path of the linked worktree (if any) and the name of the upstream branch, as well (see also `git remote show <remote>`). Note that the current worktree's HEAD will not have its path printed (it will always be your current directory).

`-q, --quiet`

Be more quiet when creating or deleting a branch, suppressing non-error messages.

`--abbrev=<n>`

In the verbose listing that show the commit object name, show the shortest prefix that is at least <n> hexdigits long that uniquely refers the object. The default value is 7 and can be overridden by the `core.abbrev` config option.

`--no-abbrev`

Display the full sha1s in the output listing rather than abbreviating them.

`-t, --track[=(direct|inherit)]`

When creating a new branch, set up `branch.<name>.remote` and `branch.<name>.merge` configuration entries to set "upstream" tracking configuration for the new branch. This configuration will tell git to show the relationship between the two branches in `git status` and `git branch -v`. Furthermore, it directs `git pull` without arguments to pull from the upstream when the new branch is checked out.

The exact upstream branch is chosen depending on the optional argument: `-t`, `--track`, or

`--track=direct` means to use the start-point branch itself as the upstream;

`--track=inherit` means to copy the upstream configuration of the start-point branch.

The `branch.autoSetupMerge` configuration variable specifies how `git switch`, `git checkout` and `git branch` should behave when neither `--track` nor `--no-track` are specified:

The default option, `true`, behaves as though `--track=direct` were given whenever the start-point is a remote-tracking branch. `false` behaves as if `--no-track` were given.

`always` behaves as though `--track=direct` were given. `inherit` behaves as though

`--track=inherit` were given. `simple` behaves as though `--track=direct` were given only

when the <start-point> is a remote-tracking branch and the new branch has the same name as the remote branch.

See git-pull(1) and git-config(1) for additional discussion on how the branch.<name>.remote and branch.<name>.merge options are used.

--no-track

Do not set up "upstream" configuration, even if the branch.autoSetupMerge configuration variable is set.

--recurse-submodules

THIS OPTION IS EXPERIMENTAL! Cause the current command to recurse into submodules if submodule.propagateBranches is enabled. See submodule.propagateBranches in git-config(1). Currently, only branch creation is supported.

When used in branch creation, a new branch <branch-name> will be created in the superproject and all of the submodules in the superproject's <start-point>. In submodules, the branch will point to the submodule commit in the superproject's <start-point> but the branch's tracking information will be set up based on the submodule's branches and remotes e.g. git branch --recurse-submodules topic origin/main will create the submodule branch "topic" that points to the submodule commit in the superproject's "origin/main", but tracks the submodule's "origin/main".

--set-upstream

As this option had confusing syntax, it is no longer supported. Please use --track or --set-upstream-to instead.

-u <upstream>, --set-upstream-to=<upstream>

Set up <branch-name>'s tracking information so <upstream> is considered <branch-name>'s upstream branch. If no <branch-name> is specified, then it defaults to the current branch.

--unset-upstream

Remove the upstream information for <branch-name>. If no branch is specified it defaults to the current branch.

--edit-description

Open an editor and edit the text to explain what the branch is for, to be used by various other commands (e.g. format-patch, request-pull, and merge (if enabled)).

Multi-line explanations may be used.

--contains [<commit>]

Only list branches which contain <commit> (HEAD if not specified). Implies --list.

--no-contains [<commit>]

Only list branches which don't contain <commit> (HEAD if not specified). Implies --list.

--merged [<commit>]

Only list branches whose tips are reachable from <commit> (HEAD if not specified).

Implies --list.

--no-merged [<commit>]

Only list branches whose tips are not reachable from <commit> (HEAD if not specified).

Implies --list.

--points-at <object>

Only list branches of <object>.

--format <format>

A string that interpolates %(fieldname) from a branch ref being shown and the object it points at. <format> is the same as that of git-for-each-ref(1).

<branch-name>

The name of the branch to create or delete. The new branch name must pass all checks defined by git-check-ref-format(1). Some of these checks may restrict the characters allowed in a branch name.

<start-point>

The new branch head will point to this commit. It may be given as a branch name, a commit-id, or a tag. If this option is omitted, the current HEAD will be used instead.

<old-branch>

The name of an existing branch. If this option is omitted, the name of the current branch will be used instead.

<new-branch>

The new name for an existing branch. The same restrictions as for <branch-name> apply.

CONFIGURATION

pager.branch is only respected when listing branches, i.e., when --list is used or implied.

The default is to use a pager. See git-config(1).

Everything above this line in this section isn't included from the git-config(1) documentation. The content that follows is the same as what's found there:

branch.autoSetupMerge

Tells git branch, git switch and git checkout to set up new branches so that git-pull(1)

will appropriately merge from the starting point branch. Note that even if this option is not set, this behavior can be chosen per-branch using the `--track` and `--no-track` options. This option defaults to true. The valid settings are:

false

no automatic setup is done

true

automatic setup is done when the starting point is a remote-tracking branch

always

automatic setup is done when the starting point is either a local branch or remote-tracking branch

inherit

if the starting point has a tracking configuration, it is copied to the new branch

simple

automatic setup is done only when the starting point is a remote-tracking branch and the new branch has the same name as the remote branch.

branch.autoSetupRebase

When a new branch is created with `git branch`, `git switch` or `git checkout` that tracks another branch, this variable tells Git to set up pull to rebase instead of merge (see `branch.<name>.rebase`). The valid settings are:

never

rebase is never automatically set to true.

local

rebase is set to true for tracked branches of other local branches.

remote

rebase is set to true for tracked branches of remote-tracking branches.

always

rebase will be set to true for all tracking branches.

See `branch.autoSetupMerge` for details on how to set up a branch to track another branch.

This option defaults to never.

branch.sort

This variable controls the sort ordering of branches when displayed by `git-branch(1)`.

Without the `--sort=<value>` option provided, the value of this variable will be used as the default. See `git-for-each-ref(1)` field names for valid values.

branch.<name>.remote

When on branch <name>, it tells git fetch and git push which remote to fetch from or push to. The remote to push to may be overridden with remote.pushDefault (for all branches). The remote to push to, for the current branch, may be further overridden by branch.<name>.pushRemote. If no remote is configured, or if you are not on any branch and there is more than one remote defined in the repository, it defaults to origin for fetching and remote.pushDefault for pushing. Additionally, . (a period) is the current local repository (a dot-repository), see branch.<name>.merge's final note below.

branch.<name>.pushRemote

When on branch <name>, it overrides branch.<name>.remote for pushing. It also overrides remote.pushDefault for pushing from branch <name>. When you pull from one place (e.g. your upstream) and push to another place (e.g. your own publishing repository), you would want to set remote.pushDefault to specify the remote to push to for all branches, and use this option to override it for a specific branch.

branch.<name>.merge

Defines, together with branch.<name>.remote, the upstream branch for the given branch. It tells git fetch/git pull/git rebase which branch to merge and can also affect git push (see push.default). When in branch <name>, it tells git fetch the default refspec to be marked for merging in FETCH_HEAD. The value is handled like the remote part of a refspec, and must match a ref which is fetched from the remote given by branch.<name>.remote. The merge information is used by git pull (which first calls git fetch) to lookup the default branch for merging. Without this option, git pull defaults to merge the first refspec fetched. Specify multiple values to get an octopus merge. If you wish to setup git pull so that it merges into <name> from another branch in the local repository, you can point branch.<name>.merge to the desired branch, and use the relative path setting . (a period) for branch.<name>.remote.

branch.<name>.mergeOptions

Sets default options for merging into branch <name>. The syntax and supported options are the same as those of git-merge(1), but option values containing whitespace characters are currently not supported.

branch.<name>.rebase

When true, rebase the branch <name> on top of the fetched branch, instead of merging the default branch from the default remote when git pull is run. See pull.rebase for doing

this in a non branch-specific manner.

When merges (or just m), pass the --rebase-merges option to git rebase so that the local merge commits are included in the rebase (see git-rebase(1) for details).

When the value is interactive (or just i), the rebase is run in interactive mode.

NOTE: this is a possibly dangerous operation; do not use it unless you understand the implications (see git-rebase(1) for details).

branch.<name>.description

Branch description, can be edited with git branch --edit-description. Branch description is automatically added to the format-patch cover letter or request-pull summary.

EXAMPLES

Start development from a known tag

```
$ git clone git://git.kernel.org/pub/scm/.../linux-2.6 my2.6
```

```
$ cd my2.6
```

```
$ git branch my2.6.14 v2.6.14 (1)
```

```
$ git switch my2.6.14
```

1. This step and the next one could be combined into a single step with "checkout -b my2.6.14 v2.6.14".

Delete an unneeded branch

```
$ git clone git://git.kernel.org/.../git.git my.git
```

```
$ cd my.git
```

```
$ git branch -d -r origin/todo origin/html origin/man (1)
```

```
$ git branch -D test (2)
```

1. Delete the remote-tracking branches "todo", "html" and "man". The next git fetch or git pull will create them again unless you configure them not to. See git-fetch(1).

2. Delete the "test" branch even if the "master" branch (or whichever branch is currently checked out) does not have all commits from the test branch.

Listing branches from a specific remote

```
$ git branch -r -l '<remote>/<pattern>' (1)
```

```
$ git for-each-ref 'refs/remotes/<remote>/<pattern>' (2)
```

1. Using -a would conflate <remote> with any local branches you happen to have been prefixed with the same <remote> pattern.
2. for-each-ref can take a wide range of options. See git-for-each-ref(1)

Patterns will normally need quoting.

NOTES

If you are creating a branch that you want to switch to immediately, it is easier to use the `git switch` command with its `-c` option to do the same thing with a single command.

The options `--contains`, `--no-contains`, `--merged` and `--no-merged` serve four related but different purposes:

- ? `--contains <commit>` is used to find all branches which will need special attention if `<commit>` were to be rebased or amended, since those branches contain the specified `<commit>`.
- ? `--no-contains <commit>` is the inverse of that, i.e. branches that don't contain the specified `<commit>`.
- ? `--merged` is used to find all branches which can be safely deleted, since those branches are fully contained by HEAD.
- ? `--no-merged` is used to find branches which are candidates for merging into HEAD, since those branches are not fully contained by HEAD.

When combining multiple `--contains` and `--no-contains` filters, only references that contain at least one of the `--contains` commits and contain none of the `--no-contains` commits are shown.

When combining multiple `--merged` and `--no-merged` filters, only references that are reachable from at least one of the `--merged` commits and from none of the `--no-merged` commits are shown.

SEE ALSO

`git-check-ref-format(1)`, `git-fetch(1)`, `git-remote(1)`, "Understanding history: What is a branch?"^[1] in the Git User's Manual.

GIT

Part of the `git(1)` suite

NOTES

1. "Understanding history: What is a branch?"

`file:///usr/share/doc/git/html/user-manual.html#what-is-a-branch`