



Linux Ubuntu 26.04 Manual Pages on command 'git-fmt-merge-msg.1'

\$ man git-fmt-merge-msg.1

GIT-FMT-MERGE-MSG(1)

Git Manual

GIT-FMT-MERGE-MSG(1)

NAME

git-fmt-merge-msg - Produce a merge commit message

SYNOPSIS

git fmt-merge-msg [-m <message>] [--into-name <branch>] [--log[=<n>] | --no-log]

git fmt-merge-msg [-m <message>] [--log[=<n>] | --no-log] -F <file>

DESCRIPTION

Takes the list of merged objects on stdin and produces a suitable commit message to be used for the merge commit, usually to be passed as the <merge-message> argument of git merge.

This command is intended mostly for internal use by scripts automatically invoking git merge.

OPTIONS

--log[=<n>]

In addition to branch names, populate the log message with one-line descriptions from the actual commits that are being merged. At most <n> commits from each merge parent will be used (20 if <n> is omitted). This overrides the merge.log configuration variable.

--no-log

Do not list one-line descriptions from the actual commits being merged.

--summary, --no-summary

Synonyms to --log and --no-log; these are deprecated and will be removed in the future.

-m <message>, --message <message>

Use <message> instead of the branch names for the first line of the log message. For use

with --log.

--into-name <branch>

Prepare the merge message as if merging to the branch <branch>, instead of the name of the real branch to which the merge is made.

-F <file>, --file <file>

Take the list of merged objects from <file> instead of stdin.

CONFIGURATION

merge.branchdesc

In addition to branch names, populate the log message with the branch description text associated with them. Defaults to false.

merge.log

In addition to branch names, populate the log message with at most the specified number of one-line descriptions from the actual commits that are being merged. Defaults to false, and true is a synonym for 20.

merge.suppressDest

By adding a glob that matches the names of integration branches to this multi-valued configuration variable, the default merge message computed for merges into these integration branches will omit "into <branch-name>" from its title.

An element with an empty value can be used to clear the list of globs accumulated from previous configuration entries. When there is no merge.suppressDest variable defined, the default value of master is used for backward compatibility.

merge.summary

Synonym to merge.log; this is deprecated and will be removed in the future.

EXAMPLES

```
$ git fetch origin master
```

```
$ git fmt-merge-msg --log <$GIT_DIR/FETCH_HEAD
```

Print a log message describing a merge of the "master" branch from the "origin" remote.

SEE ALSO

git-merge(1)

GIT

Part of the git(1) suite