



Linux Ubuntu 26.04 Manual Pages on command 'gnome-session-inhibit.1'

\$ man gnome-session-inhibit.1

GNOME-SESSION-INHI(1)

User Commands

GNOME-SESSION-INHI(1)

NAME

gnome-session-inhibit - Inhibit gnome-session functionality

SYNOPSIS

gnome-session-inhibit [OPTION...] [COMMAND]

DESCRIPTION

gnome-session-inhibit can inhibit certain gnome-session functionality while executing the given COMMAND. To achieve this, it calls the Inhibit() method of the gnome-session D-Bus API and creates an inhibitor. The inhibitor is automatically removed when gnome-session-inhibit exits.

A typical use case is to prevent the session from going idle (and thus locking the screen) while a movie player is running.

OPTIONS

-h, --help

Print help and exit

--version

Print version information and exit

--app-id ID

The application id to use when calling the gnome-session Inhibit() method. If this option is not specified, "unknown" is used.

--reason REASON

A human-readable reason to pass along when calling the gnome-session Inhibit() method.

If this option is not specified, "not specified" is used.

--inhibit ACTION

ACTION specifies the actions to inhibit. This option can be repeated to inhibit multiple actions. The possible values for an ACTION are: logout, switch-user, suspend, idle, automount. If this option is not specified, "idle" is assumed.

--inhibit-only

Do not launch COMMAND and wait forever instead

-l, --list

List the existing inhibitions and exit

SEE ALSO

systemd-inhibit(1)

gnome-session

GNOME-SESSION-INHI(1)