



Linux Ubuntu 26.04 Manual Pages on command 'gnuenv.1'

\$ man gnuenv.1

ENV(1) User Commands ENV(1)

NAME

env - run a program in a modified environment

SYNOPSIS

env [OPTION]... [-] [NAME=VALUE]... [COMMAND [ARG]...]

DESCRIPTION

Set each NAME to VALUE in the environment and run COMMAND.

Mandatory arguments to long options are mandatory for short options too.

-a, --argv0=ARG

pass ARG as the zeroth argument of COMMAND

-i, --ignore-environment

start with an empty environment

-0, --null

end each output line with NUL, not newline

-u, --unset=NAME

remove variable from the environment

-C, --chdir=DIR

change working directory to DIR

-S, --split-string=S

process and split S into separate arguments; used to pass multiple arguments on she?

bang lines

--block-signal[=SIG]

block delivery of SIG signal(s) to COMMAND

--default-signal[=SIG]

reset handling of SIG signal(s) to the default

--ignore-signal[=SIG]

set handling of SIG signal(s) to do nothing

--list-signal-handling

list non default signal handling to stderr

-v, --debug

print verbose information for each processing step

--help display this help and exit

--version

output version information and exit

A mere - implies -i. If no COMMAND, print the resulting environment.

SIG may be a signal name like 'PIPE', or a signal number like '13'. Without SIG, all known signals are included. Multiple signals can be comma-separated. An empty SIG argument is a no-op.

Exit status:

125 if the env command itself fails

126 if COMMAND is found but cannot be invoked

127 if COMMAND cannot be found

- the exit status of COMMAND otherwise

SCRIPT OPTION HANDLING

The -S option allows specifying multiple arguments in a script. Running a script named 1.pl containing the following first line:

```
#!/usr/bin/env -S perl -w -T
```

...

Will execute perl -w -T 1.pl

Without the '-S' parameter the script will likely fail with:

```
/usr/bin/env: 'perl -w -T': No such file or directory
```

See the full documentation for more details.

NOTES

POSIX's exec(3p) pages says:

"many existing applications wrongly assume that they start with certain signals set to the default action and/or unblocked.... Therefore, it is best not to block or ig?

nore signals across execs without explicit reason to do so, and especially not to block signals across execs of arbitrary (not closely cooperating) programs."

AUTHOR

Written by Richard Mlynarik, David MacKenzie, and Assaf Gordon.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

SEE ALSO

sigaction(2), sigprocmask(2), signal(7)

Full documentation <<https://www.gnu.org/software/coreutils/env>>

or available locally via: info '(coreutils) env invocation'

Packaged by Ubuntu (9.7-3ubuntu2)

Copyright ? 2025 Free Software Foundation, Inc.

License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

GNU coreutils 9.7

January 2026

ENV(1)