



Linux Ubuntu 26.04 Manual Pages on command 'go-clean.1'

\$ man go-clean.1

GO-CLEAN(1) Go programming tools and commands GO-CLEAN(1)

NAME

go-clean - remove object files and cached files

SYNOPSIS

go clean [-i] [-r] [-cache] [-testcache] [-modcache] [-fuzzcache] [build flags] [packages]

DESCRIPTION

Clean removes object files from package source directories. The go command builds most ob?

jects in a temporary directory, so go clean is mainly concerned with object files left by

other tools or by manual invocations of go build.

If a package argument is given or the -i or -r flag is set, clean removes the following

files from each of the source directories corresponding to the import paths:

_obj/ old object directory, left from Makefiles

_test/ old test directory, left from Makefiles

_testmain.go

old gotest file, left from Makefiles

test.out

old test log, left from Makefiles

build.out

old test log, left from Makefiles

*.[568ao]

object files, left from Makefiles

DIR(.exe)

from go build

DIR.test(.exe)

from go test -c

MAINFILE(.exe)

from go build MAINFILE.go

*.so from SWIG

In the list, DIR represents the final path element of the directory, and MAINFILE is the base name of any Go source file in the directory that is not included when building the package.

OPTIONS

The -i flag causes clean to remove the corresponding installed archive or binary (what ``go install'` would create).

The -n flag causes clean to print the remove commands it would execute, but not run them.

The -r flag causes clean to be applied recursively to all the dependencies of the packages named by the import paths.

The -x flag causes clean to print remove commands as it executes them.

The -cache flag causes clean to remove the entire go build cache.

The -testcache flag causes clean to expire all test results in the go build cache.

The -modcache flag causes clean to remove the entire module download cache, including unpacked source code of versioned dependencies.

The -fuzzcache flag causes clean to remove files stored in the Go build cache for fuzz testing. The fuzzing engine caches files that expand code coverage, so removing them may make fuzzing less effective until new inputs are found that provide the same coverage. These files are distinct from those stored in testdata directory; clean does not remove those files.

For more about build flags, see ``go help build'`.

For more about specifying packages, see ``go help packages'`.

AUTHOR

This manual page was created using help2man and afterwards updating the output. It is maintained by the Debian Go Compiler Team <team+go-compiler@tracker.debian.org> for the Debian project (and may be used by others).