



Linux Ubuntu 26.04 Manual Pages on command 'gtk4-broadwayd.1'

\$ man gtk4-broadwayd.1

gtk4-broadwayd(1) GTK commands gtk4-broadwayd(1)

Name

gtk4-broadwayd - The Broadway display server

SYNOPSIS

gtk4-broadwayd [OPTIONS...] <DISPLAY>

gtk4-broadwayd --port=PORT --address=ADDRESS <DISPLAY>

gtk4-broadwayd --unixaddress=ADDRESS <DISPLAY>

DESCRIPTION

gtk4-broadwayd is a display server for the Broadway GDK backend. It allows multiple GTK applications to display their windows in the same web browser, by connecting to gtk4-broadwayd.

When using gtk4-broadwayd, specify the display number to use, prefixed with a colon, similar to X. The default display number is 0.

gtk4-broadwayd :5

Then point your web browser at <http://127.0.0.1:8085>.

Start your applications like this:

GDK_BACKEND=broadway BROADWAY_DISPLAY=:5 gtk4-demo

OPTIONS

--port PORT

Use the given PORT for the HTTP connection, instead of the default 8080 + (DISPLAY - 1).

--address ADDRESS

Use the given address for the HTTP connection, instead of the default <http://127.0.0.1>.

--unixsocket ADDRESS

Use the given address as the unix domain socket address. This option overrides --address and --port, and it is available only on Unix-like systems.

GTK

gtk4-broadwayd(1)