



Linux Ubuntu 26.04 Manual Pages on command 'localedef.1'

\$ man localedef.1

localedef(1) General Commands Manual localedef(1)

NAME

localedef - compile locale definition files

SYNOPSIS

localedef [options] outputpath
localedef --add-to-archive [options] compiledpath
localedef --delete-from-archive [options] localename ...
localedef --list-archive [options]
localedef --help
localedef --usage
localedef --version

DESCRIPTION

The localedef program reads the indicated charmap and input files, compiles them to a binary form quickly usable by the locale functions in the C library (setlocale(3), localeconv(3), etc.), and places the output in outputpath.

The outputpath argument is interpreted as follows:

- ? If outputpath contains a slash character ('/'), it is interpreted as the name of the directory where the output definitions are to be stored. In this case, there is a separate output file for each locale category (LC_TIME, LC_NUMERIC, and so on).
- ? If the --no-archive option is used, outputpath is the name of a subdirectory in /usr/lib/locale where per-category compiled files are placed.
- ? Otherwise, outputpath is the name of a locale and the compiled locale data is added to the archive file /usr/lib/locale/locale-archive. A locale archive is a memory-mapped

file which contains all the system-provided locales; it is used by all localized programs when the environment variable LOCPATH is not set.

In any case, localedef aborts if the directory in which it tries to write locale files has not already been created.

If no charmapfile is given, the value ANSI_X3.4-1968 (for ASCII) is used by default. If no inputfile is given, or if it is given as a dash (-), localedef reads from standard input.

OPTIONS

Operation-selection options

A few options direct localedef to do something other than compile locale definitions. Only one of these options should be used at a time.

--add-to-archive

Add the compiledpath directories to the locale archive file. The directories should have been created by previous runs of localedef, using --no-archive.

--delete-from-archive

Delete the named locales from the locale archive file.

--list-archive

List the locales contained in the locale archive file.

Other options

Some of the following options are sensible only for certain operations; generally, it should be self-evident which ones. Notice that -f and -c are reversed from what you might expect; that is, -f is not the same as --force.

-f charmapfile

--charmap=charmapfile

Specify the file that defines the character set that is used by the input file. If charmapfile contains a slash character (/), it is interpreted as the name of the character map. Otherwise, the file is sought in the current directory and the default directory for character maps. If the environment variable I18NPATH is set, \$I18NPATH/charmaps/ and \$I18NPATH/ are also searched after the current directory.

The default directory for character maps is printed by localedef --help.

-i inputfile

--inputfile=inputfile

Specify the locale definition file to compile. The file is sought in the current directory and the default directory for locale definition files. If the environment

variable `LC_ALL` is set, `LC_ALL/locales/` and `LC_ALL` are also searched after the current directory. The default directory for locale definition files is printed by `localedef --help`.

`-u repertoirefile`

`--repertoire-map=repertoirefile`

Read mappings from symbolic names to Unicode code points from `repertoirefile`. If `repertoirefile` contains a slash character ('/'), it is interpreted as the pathname of the repertoire map. Otherwise, the file is sought in the current directory and the default directory for repertoire maps. If the environment variable `LC_ALL` is set, `LC_ALL/repertoiremaps/` and `LC_ALL` are also searched after the current directory. The default directory for repertoire maps is printed by `localedef --help`.

`-A aliasfile`

`--alias-file=aliasfile`

Use `aliasfile` to look up aliases for locale names. There is no default aliases file.

`--force`

`-c` Write the output files even if warnings were generated about the input file.

`--verbose`

`-v` Generate extra warnings about errors that are normally ignored.

`--big-endian`

Generate big-endian output.

`--little-endian`

Generate little-endian output.

`--no-archive`

Do not use the locale archive file, instead create `outputpath` as a subdirectory in the same directory as the locale archive file, and create separate output files for locale categories in it. This is helpful to prevent system locale archive updates from overwriting custom locales created with `localedef`.

`--no-hard-links`

Do not create hard links between installed locales.

`--no-warnings=warnings`

Comma-separated list of warnings to disable. Supported warnings are `ascii` and `intcurrsym`.

`--posix`

Conform strictly to POSIX. Implies --verbose. This option currently has no other effect. POSIX conformance is assumed if the environment variable POSIXLY_CORRECT is set.

--prefix=pathname

Set the prefix to be prepended to the full archive pathname. By default, the prefix is empty. Setting the prefix to foo, the archive would be placed in foo/usr/lib/locale/locale-archive.

--quiet

Suppress all notifications and warnings, and report only fatal errors.

--replace

Replace a locale in the locale archive file. Without this option, if the locale is in the archive file already, an error occurs.

--warnings=warnings

Comma-separated list of warnings to enable. Supported warnings are ascii and intcurrsym.

--help

-? Print a usage summary and exit. Also prints the default paths used by localedef.

--usage

Print a short usage summary and exit.

--version

-V Print the version number, license, and disclaimer of warranty for localedef.

EXIT STATUS

One of the following exit values can be returned by localedef:

- 0 Command completed successfully.
- 1 Warnings or errors occurred, output files were written.
- 4 Errors encountered, no output created.

ENVIRONMENT

POSIXLY_CORRECT

The --posix flag is assumed if this environment variable is set.

I18NPATH

A colon-separated list of search directories for files.

FILES

/usr/share/i18n/charmaps

Usual default character map path.

/usr/share/i18n/locales

Usual default path for locale definition files.

/usr/share/i18n/repertoiremaps

Usual default repertoire map path.

/usr/lib/locale/locale-archive

Usual default locale archive location.

/usr/lib/locale

Usual default path for compiled individual locale data files.

outputpath/LC_ADDRESS

An output file that contains information about formatting of addresses and geography-related items.

outputpath/LC_COLLATE

An output file that contains information about the rules for comparing strings.

outputpath/LC_CTYPE

An output file that contains information about character classes.

outputpath/LC_IDENTIFICATION

An output file that contains metadata about the locale.

outputpath/LC_MEASUREMENT

An output file that contains information about locale measurements (metric versus US customary).

outputpath/LC_MESSAGES/SYS_LC_MESSAGES

An output file that contains information about the language messages should be printed in, and what an affirmative or negative answer looks like.

outputpath/LC_MONETARY

An output file that contains information about formatting of monetary values.

outputpath/LC_NAME

An output file that contains information about salutations for persons.

outputpath/LC_NUMERIC

An output file that contains information about formatting of nonmonetary numeric values.

outputpath/LC_PAPER

An output file that contains information about settings related to standard paper

size.

outputpath/LC_TELEPHONE

An output file that contains information about formats to be used with telephone services.

outputpath/LC_TIME

An output file that contains information about formatting of data and time values.

STANDARDS

POSIX.1-2008.

EXAMPLES

Compile the locale files for Finnish in the UTF-8 character set and add it to the default locale archive with the name fi_FI.UTF-8:

```
localedef -f UTF-8 -i fi_FI fi_FI.UTF-8
```

The next example does the same thing, but generates files into the fi_FI.UTF-8 directory which can then be used by programs when the environment variable LOCPATH is set to the current directory (note that the last argument must contain a slash):

```
localedef -f UTF-8 -i fi_FI ./fi_FI.UTF-8
```

SEE ALSO

locale(1), charmap(5), locale(5), repertoiremap(5), locale(7)

Linux man-pages 6.17

2026-02-08

localedef(1)