



Linux Ubuntu 26.04 Manual Pages on command 'login.1'

\$ man login.1

LOGIN(1) User Commands LOGIN(1)

NAME

login - begin session on the system

SYNOPSIS

login [-p] [-h host] [-H] [-f username|username]

DESCRIPTION

login is used when signing onto a system. If no argument is given, login prompts for the username.

The user is then prompted for a password, where appropriate. Echoing is disabled to prevent revealing the password. Only a number of password failures are permitted before login exits and the communications link is severed. See LOGIN_RETRIES in the CONFIG FILE ITEMS section.

If password aging has been enabled for the account, the user may be prompted for a new password before proceeding. In such case old password must be provided and the new password entered before continuing. Please refer to passwd(1) for more information.

The user and group ID will be set according to their values in the /etc/passwd file. There is one exception if the user ID is zero. In this case, only the primary group ID of the account is set. This should allow the system administrator to login even in case of network problems. The environment variable values for \$HOME, \$USER, \$SHELL, \$PATH, \$LOGNAME, and \$MAIL are set according to the appropriate fields in the password entry. \$PATH defaults to /usr/local/bin:/bin:/usr/bin for normal users, and to /usr/local/sbin:/usr/local/bin:/sbin:/bin:/usr/sbin:/usr/bin for root, if not otherwise configured.

The environment variable \$TERM will be preserved, if it exists, else it will be initialized

to the terminal type on your tty. Other environment variables are preserved if the -p option is given.

The environment variables defined by PAM are always preserved.

Then the user's shell is started. If no shell is specified for the user in /etc/passwd, then /bin/sh is used. If the specified shell contains a space, it is treated as a shell script.

If there is no home directory specified in /etc/passwd, then / is used, followed by .hushlogin check as described below.

If the file .hushlogin exists, then a "quiet" login is performed. This disables the checking of mail and the printing of the last login time and message of the day. Otherwise, if /var/log/lastlog exists, the last login time is printed, and the current login is recorded.

OPTIONS

-p

Used by getty(8) to tell login to preserve the environment. See also LOGIN_ENV_SAFELIST config file item.

-f

Used to skip a login authentication. This option is usually used by the getty(8) autologin feature.

-h

Used by other servers (such as telnetd(8)) to pass the name of the remote host to login so that it can be placed in utmp and wtmp. Only the superuser is allowed use this option.

Note that the -h option has an impact on the PAM service name. The standard service name is login, but with the -h option, the name is remote. It is necessary to create proper PAM config files (for example, /etc/pam.d/login and /etc/pam.d/remote).

-H

Used by other servers (for example, telnetd(8)) to tell login that printing the hostname should be suppressed in the login: prompt. See also LOGIN_PLAIN_PROMPT below.

-h, --help

Display help text and exit.

-V, --version

Display version and exit.

CONFIG FILE ITEMS

login reads the /etc/login.defs configuration file (see login.defs(5)). Note that the

configuration file could be distributed with another package (usually shadow-utils). The following configuration items are relevant for login:

MOTD_FILE (string)

Specifies a ":" delimited list of "message of the day" files and directories to be displayed upon login. If the specified path is a directory then displays all files with .motd file extension in version-sort order from the directory.

The default value is /usr/share/misc/motd:/run/motd:/etc/motd. If the MOTD_FILE item is empty or a quiet login is enabled, then the message of the day is not displayed. Note that the same functionality is also provided by the pam_motd(8) PAM module.

The directories in the MOTD_FILE are supported since version 2.36.

Note that login does not implement any filenames overriding behavior like pam_motd (see also MOTD_FIRSTONLY), but all content from all files is displayed. It is recommended to keep extra logic in content generators and use /run/motd.d rather than rely on overriding behavior hardcoded in system tools.

MOTD_FIRSTONLY (boolean)

Forces login to stop display content specified by MOTD_FILE after the first accessible item in the list. Note that a directory is one item in this case. This option allows login semantics to be configured to be more compatible with pam_motd. The default value is no.

LOGIN_ENV_SAFELIST (string)

Forces login to protect the specified environment variables if -p is not used. The string value is a comma-separated list of variable names. For example: "LANG,LC_MESSAGES,LC_COLLATE". The safelist is ignored for the environment variables HOME, SHELL and USER.

LOGIN_PLAIN_PROMPT (boolean)

Tell login that printing the hostname should be suppressed in the login: prompt. This is an alternative to the -H command line option. The default value is no.

LOGIN_TIMEOUT (number)

Maximum time in seconds for login. The default value is 60.

LOGIN_RETRIES (number)

Maximum number of login retries in case of a bad password. The default value is 3.

LOGIN_KEEP_USERNAME (boolean)

Tell login to only re-prompt for the password if authentication failed, but the username

is valid. The default value is no.

FAIL_DELAY (number)

Delay in seconds before being allowed another three tries after a login failure. The default value is 5.

TTYPERM (string)

The terminal permissions. The default value is 0600 or 0620 if tty group is used. See also `mesg(1)`.

TTYGROUP (string)

The login tty will be owned by the TTYGROUP. The default value is tty. If the TTYGROUP does not exist, then the ownership of the terminal is set to the user's primary group.

The TTYGROUP can be either the name of a group or a numeric group identifier. See also `mesg(1)`.

HUSHLOGIN_FILE (string)

If defined, this file can inhibit all the usual chatter during the login sequence. If a full pathname (for example, `/etc/hushlogins`) is specified, then hushed mode will be enabled if the user's name or shell are found in the file. If this global hush login file is empty then the hushed mode will be enabled for all users.

If a full pathname is not specified, then hushed mode will be enabled if the file exists in the user's home directory.

The default is to check `/etc/hushlogins` and if it does not exist then `~/.hushlogin`.

If the HUSHLOGIN_FILE item is empty, then all the checks are disabled.

DEFAULT_HOME (boolean)

Indicate if login is allowed if we cannot change directory to the home directory. If set to yes, the user will login in the root (`/`) directory if it is not possible to change directory to their home. The default value is yes.

LASTLOG_UID_MAX (unsigned number)

Highest user ID number for which the lastlog entries should be updated. As higher user IDs are usually tracked by remote user identity and authentication services there is no need to create a huge sparse lastlog file for them. No LASTLOG_UID_MAX option present in the configuration means that there is no user ID limit for writing lastlog entries. The default value is `ULONG_MAX`.

LOG_UNKFAIL_ENAB (boolean)

Enable display of unknown usernames when login failures are recorded. The default value

is no.

Note that logging unknown usernames may be a security issue if a user enters their password instead of their login name.

ENV_PATH (string)

If set, it will be used to define the PATH environment variable when a regular user logs in. The default value is /usr/local/bin:/bin:/usr/bin.

ENV_ROOTPATH (string), ENV_SUPATH (string)

If set, it will be used to define the PATH environment variable when the superuser logs in. ENV_ROOTPATH takes precedence. The default value is /usr/local/sbin:/usr/local/bin:/sbin:/bin:/usr/sbin:/usr/bin.

FILES

/var/run/utmp, /var/log/wtmp, /var/log/lastlog, /var/spool/mail/*, /etc/motd, /etc/passwd, /etc/nologin, /etc/pam.d/login, /etc/pam.d/remote, /etc/hushlogins, \$HOME/.hushlogin

CREDENTIALS

login supports configuration via systemd credentials (see <https://systemd.io/CREDENTIALS/>).

login reads the following systemd credentials:

login.noauth (boolean)

If set, configures login to skip login authentication, similarly to the -f option.

BUGS

The undocumented BSD -r option is not supported. This may be required by some rlogind(8) programs.

A recursive login, as used to be possible in the good old days, no longer works; for most purposes su(1) is a satisfactory substitute. Indeed, for security reasons, login does a vhangup(2) system call to remove any possible listening processes on the tty. This is to avoid password sniffing. If one uses the command login, then the surrounding shell gets killed by vhangup(2) because it's no longer the true owner of the tty. This can be avoided by using exec login in a top-level shell or xterm.

AUTHORS

Derived from BSD login 5.40 (5/9/89) by Michael Glad <glad@daimi.dk> for HP-UX. Ported to Linux 0.12: Peter Orbaek <poe@daimi.aau.dk>. Rewritten to a PAM-only version by Karel Zak <kzak@redhat.com>

SEE ALSO

mail(1), passwd(1), passwd(5), utmp(5), environ(7), getty(8), init(8), lastlog(8),

shutdown(8)

REPORTING BUGS

For bug reports, use the issue tracker <<https://github.com/util-linux/util-linux/issues>>.

AVAILABILITY

The login command is part of the util-linux package which can be downloaded from Linux

Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.

util-linux 2.41.3

2025-12-15

LOGIN(1)