



Linux Ubuntu 26.04 Manual Pages on command 'lremovexattr.2'

\$ man lremovexattr.2

removexattr(2) System Calls Manual removexattr(2)

NAME

removexattr, lremovexattr, fremovexattr - remove an extended attribute

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <sys/xattr.h>

int removexattr(const char *path, const char *name);

int lremovexattr(const char *path, const char *name);

int fremovexattr(int fd, const char *name);
```

DESCRIPTION

Extended attributes are name:value pairs associated with inodes (files, directories, symbolic links, etc.). They are extensions to the normal attributes which are associated with all inodes in the system (i.e., the stat(2) data). A complete overview of extended attributes concepts can be found in xattr(7).

removexattr() removes the extended attribute identified by name and associated with the given path in the filesystem.

lremovexattr() is identical to removexattr(), except in the case of a symbolic link, where the extended attribute is removed from the link itself, not the file that it refers to.

fremovexattr() is identical to removexattr(), only the extended attribute is removed from the open file referred to by fd (as returned by open(2)) in place of path.

An extended attribute name is a null-terminated string. The name includes a namespace prefix; there may be several, disjoint namespaces associated with an individual inode.

RETURN VALUE

On success, zero is returned. On failure, -1 is returned and `errno` is set to indicate the error.

ERRORS

ENODATA

The named attribute does not exist.

ENOTSUP

Extended attributes are not supported by the filesystem, or are disabled.

In addition, the errors documented in `stat(2)` can also occur.

STANDARDS

Linux.

HISTORY

Linux 2.4, glibc 2.3.

SEE ALSO

`getfattr(1)`, `setfattr(1)`, `getxattr(2)`, `listxattr(2)`, `open(2)`, `setxattr(2)`, `stat(2)`, `sym?`
`link(7)`, `xattr(7)`

Linux man-pages 6.17

2026-02-08

`removexattr(2)`