



Linux Ubuntu 26.04 Manual Pages on command 'mkostemps.3'

\$ man mkostemps.3

mkstemp(3) Library Functions Manual mkstemp(3)

NAME

mkstemp, mkostemp, mkstemp, mkostemps - create a unique temporary file

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <stdlib.h>

int mkstemp(char *template);

int mkostemp(char *template, int flags);

int mkstemp(char *template, int suffixlen);

int mkostemps(char *template, int suffixlen, int flags);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
mkstemp():
    _XOPEN_SOURCE >= 500
    || /* glibc >= 2.12: */ _POSIX_C_SOURCE >= 200809L
    || /* glibc <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE
```

```
mkostemp():
    _GNU_SOURCE
```

```
mkstemp():
    /* glibc >= 2.19: */ _DEFAULT_SOURCE
    || /* glibc <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE
```

```
mkostemps():
    _GNU_SOURCE
```

DESCRIPTION

The `mkstemp()` function generates a unique temporary filename from `template`, creates and opens the file, and returns an open file descriptor for the file.

The last six characters of template must be "XXXXXX" and these are replaced with a string that makes the filename unique. Since it will be modified, template must not be a string constant, but should be declared as a character array.

The file is created with permissions 0600, that is, read plus write for owner only. The returned file descriptor provides both read and write access to the file. The file is opened with the `open(2)` `O_EXCL` flag, guaranteeing that the caller is the process that creates the file.

The `mkostemp()` function is like `mkstemp()`, with the difference that the following bits with the same meaning as for `open(2)` may be specified in flags: `O_APPEND`, `O_CLOEXEC`, and `O_SYNC`. Note that when creating the file, `mkostemp()` includes the values `O_RDWR`, `O_CREAT`, and `O_EXCL` in the flags argument given to `open(2)`; including these values in the flags argument given to `mkostemp()` is unnecessary, and produces errors on some systems.

The `mkstemp()` function is like `mkstemp()`, except that the string in `template` contains a suffix of `suffixlen` characters. Thus, `template` is of the form `prefixXXXXXXsuffix`, and the string `XXXXXX` is modified as for `mkstemp()`.

The `mkostemps()` function is to `mkstemps()` as `mkostemp()` is to `mkstemp()`.

RETURN VALUE

On success, these functions return the file descriptor of the temporary file. On error, -1 is returned, and `errno` is set to indicate the error.

ERRORS

EEXIST Could not create a unique temporary filename. Now the contents of template are unde-
fined.

EINVAL For mkstemp() and mkostemp(): The last six characters of template were not XXXXXX;
now template is unchanged.

For `mkstemps()` and `mkostemps()`: `template` is less than $(6 + \text{suffixlen})$ characters long, or the last 6 characters before the suffix in `template` were not `XXXXXX`.

These functions may also fail with any of the errors described for `open(2)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

Interface	Attribute	Value
mkstemp(), mkostemp(), mkstemps(), mkostemps()	Thread safety	MT-Safe

STANDARDS

mkstemp()
 POSIX.1-2001.

mkstemps()
 BSD.

mkostemp()
 mkostemps()
 GNU.

HISTORY

mkstemp()
 4.3BSD, POSIX.1-2001.

mkstemps()
 glibc 2.11. BSD, Mac OS X, Solaris, Tru64.

mkostemp()
 glibc 2.7.

mkostemps()
 glibc 2.11.

In glibc versions 2.06 and earlier, the file is created with permissions 0666, that is, read and write for all users. This old behavior may be a security risk, especially since other UNIX flavors use 0600, and somebody might overlook this detail when porting programs. POSIX.1-2008 adds a requirement that the file be created with mode 0600.

More generally, the POSIX specification of mkstemp() does not say anything about file modes, so the application should make sure its file mode creation mask (see umask(2)) is set appropriately before calling mkstemp() (and mkostemp()).

SEE ALSO

mkdtemp(3), mktemp(3), tempnam(3), tmpfile(3), tmpnam(3)