



Linux Ubuntu 26.04 Manual Pages on command 'mysql.1'

\$ man mysql.1

MYSQL(1) MySQL Database System MYSQL(1)

NAME

mysql - the MySQL command-line client

SYNOPSIS

mysql [options] db_name

DESCRIPTION

mysql is a simple SQL shell with input line editing capabilities. It supports interactive and noninteractive use. When used interactively, query results are presented in an ASCII-table format. When used noninteractively (for example, as a filter), the result is presented in tab-separated format. The output format can be changed using command options.

If you have problems due to insufficient memory for large result sets, use the --quick option. This forces mysql to retrieve results from the server a row at a time rather than retrieving the entire result set and buffering it in memory before displaying it. This is done by returning the result set using the mysql_use_result() C API function in the client/server library rather than mysql_store_result().

Note

Alternatively, MySQL Shell offers access to the X DevAPI. For details, see MySQL Shell 8.4[1].

Using mysql is very easy. Invoke it from the prompt of your command interpreter as follows:

mysql db_name

Or:

mysql --user=user_name --password db_name

In this case, you'll need to enter your password in response to the prompt that mysql

displays:

Enter password: your_password

Then type an SQL statement, end it with ;, \g, or \G and press Enter.

Typing Control+C interrupts the current statement if there is one, or cancels any partial input line otherwise.

You can execute SQL statements in a script file (batch file) like this:

```
mysql db_name < script.sql > output.tab
```

On Unix, the mysql client logs statements executed interactively to a history file. See the section called "MYSQL CLIENT LOGGING".

MYSQL CLIENT OPTIONS

mysql supports the following options, which can be specified on the command line or in the [mysql] and [client] groups of an option file. For information about option files used by MySQL programs, see Section 6.2.2.2, "Using Option Files".

? --help, -?

????????????????????????????????

? Command-Line Format ? --help ?

????????????????????????????????

Display a help message and exit.

? --authentication-oci-client-config-profile

??

? Command-Line Format ? --authentication-oci-client- ?

? ? config-profile=profileName ?

??

? Type ? String ?

??

Specify the name of the OCI configuration profile to use. If not set, the default profile is used.

? --auto-rehash

??

? Command-Line Format ? --auto-rehash ?

??

? Disabled by ? skip-auto-rehash ?

??

Enable automatic rehashing. This option is on by default, which enables database, table, and column name completion. Use --disable-auto-rehash to disable rehashing. That causes mysql to start faster, but you must issue the rehash command or its \# shortcut if you want to use name completion.

To complete a name, enter the first part and press Tab. If the name is unambiguous, mysql completes it. Otherwise, you can press Tab again to see the possible names that begin with what you have typed so far. Completion does not occur if there is no default database.

Note

This feature requires a MySQL client that is compiled with the readline library.

Typically, the readline library is not available on Windows.

? --auto-vertical-output

??

? Command-Line Format ? --auto-vertical-output ?

??

Cause result sets to be displayed vertically if they are too wide for the current window, and using normal tabular format otherwise. (This applies to statements terminated by ; or \G.)

? --batch, -B

??

? Command-Line Format ? --batch ?

??

Print results using tab as the column separator, with each row on a new line. With this option, mysql does not use the history file.

Batch mode results in nontabular output format and escaping of special characters.

Escaping may be disabled by using raw mode; see the description for the --raw option.

? --binary-as-hex

??

? Command-Line Format ? --binary-as-hex ?

??

? Type ? Boolean ?

??

? Default Value ? FALSE in noninteractive mode ?

??

When this option is given, mysql displays binary data using hexadecimal notation (0xvalue). This occurs whether the overall output display format is tabular, vertical, HTML, or XML.

--binary-as-hex when enabled affects display of all binary strings, including those returned by functions such as CHAR() and UNHEX(). The following example demonstrates this using the ASCII code for A (65 decimal, 41 hexadecimal):

? --binary-as-hex disabled:

```
mysql> SELECT CHAR(0x41), UNHEX('41');

+-----+-----+
| CHAR(0x41) | UNHEX('41') |
+-----+-----+
| A         | A         |
+-----+-----+
```

? --binary-as-hex enabled:

```
mysql> SELECT CHAR(0x41), UNHEX('41');

+-----+-----+
| CHAR(0x41) | UNHEX('41') |
+-----+-----+
| 0x41       | 0x41       |
+-----+-----+
```

To write a binary string expression so that it displays as a character string regardless of whether --binary-as-hex is enabled, use these techniques:

? The CHAR() function has a USING charset clause:

```
mysql> SELECT CHAR(0x41 USING utf8mb4);

+-----+
| CHAR(0x41 USING utf8mb4) |
+-----+
| A                         |
+-----+
```

? More generally, use CONVERT() to convert an expression to a given character set:

```
mysql> SELECT CONVERT(UNHEX('41') USING utf8mb4);

+-----+
```

```
| CONVERT(UNHEX('41') USING utf8mb4) |
```

```
+-----+
```

```
| A          |
```

```
+-----+
```

When mysql operates in interactive mode, this option is enabled by default. In addition, output from the status (or \s) command includes this line when the option is enabled implicitly or explicitly:

```
Binary data as: Hexadecimal
```

To disable hexadecimal notation, use --skip-binary-as-hex

? --binary-mode

```
????????????????????????????????????????
```

? Command-Line Format ? --binary-mode ?

```
????????????????????????????????????????
```

This option helps when processing mysqlbinlog output that may contain BLOB values. By default, mysql translates \r\n in statement strings to \n and interprets \0 as the statement terminator. --binary-mode disables both features. It also disables all mysql commands except charset and delimiter in noninteractive mode (for input piped to mysql or loaded using the source command).

(MySQL 8.4.6 and later:) --binary-mode, when enabled, causes the server to disregard any setting for --commands .

? --bind-address=ip_address

```
????????????????????????????????????????
```

? Command-Line Format ? --bind-address=ip_address ?

```
????????????????????????????????????????
```

On a computer having multiple network interfaces, use this option to select which interface to use for connecting to the MySQL server.

? --character-sets-dir=dir_name

```
????????????????????????????????????????
```

? Command-Line Format ? --character-sets-dir=dir_name ?

```
????????????????????????????????????????
```

? Type ? Directory name ?

```
????????????????????????????????????????
```

The directory where character sets are installed. See Section 12.15, ?Character Set

Configuration?.

? --column-names

??

? Command-Line Format ? --column-names ?

??

Write column names in results.

? --column-type-info

??

? Command-Line Format ? --column-type-info ?

??

Display result set metadata. This information corresponds to the contents of C API
MYSQL_FIELD data structures. See C API Basic Data Structures[2].

? --commands

??

? Command-Line Format ? --commands ?

??

? Type ? Boolean ?

??

? Default Value ? TRUE ?

??

Whether to enable or disable processing of local mysql client commands. Setting this
option to FALSE disables such processing, and has the effects listed here:

? The following mysql client commands are disabled:

? charset (/C remains enabled)

? clear

? connect

? edit

? ego

? exit

? go

? help

? nopager

? notee

- ? nowarning
- ? pager
- ? print
- ? prompt
- ? query_attributes
- ? quit
- ? rehash
- ? resetconnection
- ? ssl_session_data_print
- ? source
- ? status
- ? system
- ? tee
- ? \u (use is passed to the server)
- ? warnings

? The \C and delimiter commands remain enabled.

? The --system-command option is ignored, and has no effect.

This option has no effect when --binary-mode is enabled.

When --commands is enabled, it is possible to disable (only) the system command using the --system-command option.

This option was added in MySQL 8.4.6.

? --comments, -c

??

? Command-Line Format ? --comments ?

??

? Type ? Boolean ?

??

? Default Value ? TRUE ?

??

Whether to preserve or strip comments in statements sent to the server. The default is to preserve them; to strip them, start mysql with --skip-comments.

Note

The mysql client always passes optimizer hints to the server, regardless of whether

this option is given.

Comment stripping is deprecated. Expect this feature and the options to control it to be removed in a future MySQL release.

? --compress, -C

??

? Command-Line Format ? --compress[={OFF|ON}] ?

??

? Deprecated ? Yes ?

??

? Type ? Boolean ?

??

? Default Value ? OFF ?

??

Compress all information sent between the client and the server if possible. See Section 6.2.8, "Connection Compression Control".

This option is deprecated. Expect it to be removed in a future version of MySQL. See the section called "Configuring Legacy Connection Compression".

? --compression-algorithms=value

??

? Command-Line Format ? --compression-algorithms=value ?

??

? Type ? Set ?

??

? Default Value ? uncompressed ?

??

? Valid Values ? ?

? ? zlib ?

? ? ?

? ? zstd ?

? ? ?

? ? uncompressed ?

??

The permitted compression algorithms for connections to the server. The available

algorithms are the same as for the `protocol_compression_algorithms` system variable. The default value is `uncompressed`.

For more information, see Section 6.2.8, “Connection Compression Control”.

? `--connect-expired-password`

??

? Command-Line Format ? `--connect-expired-password` ?

??

Indicate to the server that the client can handle sandbox mode if the account used to connect has an expired password. This can be useful for noninteractive invocations of `mysql` because normally the server disconnects noninteractive clients that attempt to connect using an account with an expired password. (See Section 8.2.16, “Server Handling of Expired Passwords”.)

? `--connect-timeout=value`

??

? Command-Line Format ? `--connect-timeout=value` ?

??

? Type ? Numeric ?

??

? Default Value ? 0 ?

??

The number of seconds before connection timeout. (Default value is 0.)

? `--database=db_name, -D db_name`

??

? Command-Line Format ? `--database=dbname` ?

??

? Type ? String ?

??

The database to use. This is useful primarily in an option file.

? `--debug[=debug_options], -# [debug_options]`

??

? Command-Line Format ? `--debug[=debug_options]` ?

??

? Type ? String ?

??

? Default Value ? d:t:o,/tmp/mysql.trace ?

??

Write a debugging log. A typical debug_options string is d:t:o,file_name. The default is d:t:o,/tmp/mysql.trace.

This option is available only if MySQL was built using WITH_DEBUG. MySQL release binaries provided by Oracle are not built using this option.

? --debug-check

??

? Command-Line Format ? --debug-check ?

??

? Type ? Boolean ?

??

? Default Value ? FALSE ?

??

Print some debugging information when the program exits.

This option is available only if MySQL was built using WITH_DEBUG. MySQL release binaries provided by Oracle are not built using this option.

? --debug-info, -T

??

? Command-Line Format ? --debug-info ?

??

? Type ? Boolean ?

??

? Default Value ? FALSE ?

??

Print debugging information and memory and CPU usage statistics when the program exits.

This option is available only if MySQL was built using WITH_DEBUG. MySQL release binaries provided by Oracle are not built using this option.

? --default-auth=plugin

??

? Command-Line Format ? --default-auth=plugin ?

??

? Type ? String ?
??

A hint about which client-side authentication plugin to use. See Section 8.2.17,
?Pluggable Authentication?.

? --default-character-set=charset_name
??

? Command-Line Format ? --default-character- ?

? ? set=charset_name ?
??

? Type ? String ?
??

Use charset_name as the default character set for the client and connection.
This option can be useful if the operating system uses one character set and the mysql
client by default uses another. In this case, output may be formatted incorrectly. You
can usually fix such issues by using this option to force the client to use the system
character set instead.
For more information, see Section 12.4, ?Connection Character Sets and Collations?, and
Section 12.15, ?Character Set Configuration?.

? --defaults-extra-file=file_name
??

? Command-Line Format ? --defaults-extra-file=file_name ?

??
? Type ? File name ?

??
Read this option file after the global option file but (on Unix) before the user option
file. If the file does not exist or is otherwise inaccessible, an error occurs. If
file_name is not an absolute path name, it is interpreted relative to the current
directory.
For additional information about this and other option-file options, see
Section 6.2.2.3, ?Command-Line Options that Affect Option-File Handling?.

? --defaults-file=file_name
??

? Command-Line Format ? --defaults-file=file_name ?

??

? Type ? File name ?

??

Use only the given option file. If the file does not exist or is otherwise inaccessible, an error occurs. If file_name is not an absolute path name, it is interpreted relative to the current directory.

Exception: Even with --defaults-file, client programs read .mylogin.cnf.

For additional information about this and other option-file options, see

Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --defaults-group-suffix=str

??

? Command-Line Format ? --defaults-group-suffix=str ?

??

? Type ? String ?

??

Read not only the usual option groups, but also groups with the usual names and a suffix of str. For example, mysql normally reads the [client] and [mysql] groups. If this option is given as --defaults-group-suffix=_other, mysql also reads the [client_other] and [mysql_other] groups.

For additional information about this and other option-file options, see

Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --delimiter=str

??

? Command-Line Format ? --delimiter=str ?

??

? Type ? String ?

??

? Default Value ? ; ?

??

Set the statement delimiter. The default is the semicolon character (;).

? --disable-named-commands Disable named commands. Use the * form only, or use named commands only at the beginning of a line ending with a semicolon (;). mysql starts with this option enabled by default. However, even with this option, long-format commands

still work from the first line. See the section called "MYSQL CLIENT COMMANDS".

? --dns-srv-name=name

??

? Command-Line Format ? --dns-srv-name=name ?

??

? Type ? String ?

??

Specifies the name of a DNS SRV record that determines the candidate hosts to use for establishing a connection to a MySQL server. For information about DNS SRV support in MySQL, see Section 6.2.6, "Connecting to the Server Using DNS SRV Records".

Suppose that DNS is configured with this SRV information for the example.com domain:

Name	TTL	Class	Priority	Weight	Port	Target
_mysql._tcp.example.com.	86400	IN	SRV	0	5	3306 host1.example.com
_mysql._tcp.example.com.	86400	IN	SRV	0	10	3306 host2.example.com
_mysql._tcp.example.com.	86400	IN	SRV	10	5	3306 host3.example.com
_mysql._tcp.example.com.	86400	IN	SRV	20	5	3306 host4.example.com

To use that DNS SRV record, invoke mysql like this:

```
mysql --dns-srv-name=_mysql._tcp.example.com
```

mysql then attempts a connection to each server in the group until a successful connection is established. A failure to connect occurs only if a connection cannot be established to any of the servers. The priority and weight values in the DNS SRV record determine the order in which servers should be tried.

When invoked with --dns-srv-name, mysql attempts to establish TCP connections only.

The --dns-srv-name option takes precedence over the --host option if both are given.

--dns-srv-name causes connection establishment to use the mysql_real_connect_dns_srv() C API function rather than mysql_real_connect(). However, if the connect command is subsequently used at runtime and specifies a host name argument, that host name takes precedence over any --dns-srv-name option given at mysql startup to specify a DNS SRV record.

? --enable-cleartext-plugin

??

? Command-Line Format ? --enable-cleartext-plugin ?

??

? Type ? Boolean ?
??
? Default Value ? FALSE ?
??

Enable the mysql_clear_password cleartext authentication plugin. (See Section 8.4.1.4, ?Client-Side Cleartext Pluggable Authentication?.)

? --execute=statement, -e statement
??
? Command-Line Format ? --execute=statement ?
??

? Type ? String ?
??
Execute the statement and quit. The default output format is like that produced with
--batch. See Section 6.2.2.1, ?Using Options on the Command Line?, for some examples.
With this option, mysql does not use the history file.

? --force, -f
??
? Command-Line Format ? --force ?
??

Continue even if an SQL error occurs.

? --get-server-public-key
??
? Command-Line Format ? --get-server-public-key ?
??
? Type ? Boolean ?
??

Request from the server the public key required for RSA key pair-based password exchange. This option applies to clients that authenticate with the caching_sha2_password authentication plugin. For that plugin, the server does not send the public key unless requested. This option is ignored for accounts that do not authenticate with that plugin. It is also ignored if RSA-based password exchange is not used, as is the case when the client connects to the server using a secure connection.

If --server-public-key-path=file_name is given and specifies a valid public key file, it

takes precedence over --get-server-public-key.

For information about the caching_sha2_password plugin, see Section 8.4.1.2, "Caching SHA-2 Pluggable Authentication".

? --histignore

??

? Command-Line Format ? --histignore=pattern_list ?

??

? Type ? String ?

??

A list of one or more colon-separated patterns specifying statements to ignore for logging purposes. These patterns are added to the default pattern list ("*IDENTIFIED*: *PASSWORD*"). The value specified for this option affects logging of statements written to the history file, and to syslog if the --syslog option is given.

For more information, see the section called "MYSQL CLIENT LOGGING".

? --host=host_name, -h host_name

??

? Command-Line Format ? --host=host_name ?

??

? Type ? String ?

??

? Default Value ? localhost ?

??

Connect to the MySQL server on the given host.

The --dns-srv-name option takes precedence over the --host option if both are given.

--dns-srv-name causes connection establishment to use the mysql_real_connect_dns_srv() C API function rather than mysql_real_connect(). However, if the connect command is subsequently used at runtime and specifies a host name argument, that host name takes precedence over any --dns-srv-name option given at mysql startup to specify a DNS SRV record.

? --html, -H

??

? Command-Line Format ? --html ?

??

Produce HTML output.

? --ignore-spaces, -i

??

? Command-Line Format ? --ignore-spaces ?

??

Ignore spaces after function names. The effect of this is described in the discussion for the IGNORE_SPACE SQL mode (see Section 7.1.11, "Server SQL Modes").

? --init-command=str

??

? Command-Line Format ? --init-command=str ?

??

Single SQL statement to execute after connecting to the server. If auto-reconnect is enabled, the statement is executed again after reconnection occurs. The definition resets existing statements defined by it or init-command-add.

? --init-command-add=str

??

? Command-Line Format ? --init-command-add=str ?

??

Add an additional SQL statement to execute after connecting or reconnecting to the MySQL server. It's usable without --init-command but has no effect if used before it because init-command resets the list of commands to call.

? --line-numbers

??

? Command-Line Format ? --line-numbers ?

??

? Disabled by ? skip-line-numbers ?

??

Write line numbers for errors. Disable this with --skip-line-numbers.

? --load-data-local-dir=dir_name

??

? Command-Line Format ? --load-data-local-dir=dir_name ?

??

? Type ? Directory name ?

??

? Default Value ? empty string ?

??

This option affects the client-side LOCAL capability for LOAD DATA operations. It specifies the directory in which files named in LOAD DATA LOCAL statements must be located. The effect of --load-data-local-dir depends on whether LOCAL data loading is enabled or disabled:

? If LOCAL data loading is enabled, either by default in the MySQL client library or by specifying --local-infile[=1], the --load-data-local-dir option is ignored.

? If LOCAL data loading is disabled, either by default in the MySQL client library or by specifying --local-infile=0, the --load-data-local-dir option applies.

When --load-data-local-dir applies, the option value designates the directory in which local data files must be located. Comparison of the directory path name and the path name of files to be loaded is case-sensitive regardless of the case sensitivity of the underlying file system. If the option value is the empty string, it names no directory, with the result that no files are permitted for local data loading.

For example, to explicitly disable local data loading except for files located in the /my/local/data directory, invoke mysql like this:

mysql --local-infile=0 --load-data-local-dir=/my/local/data

When both --local-infile and --load-data-local-dir are given, the order in which they are given does not matter.

Successful use of LOCAL load operations within mysql also requires that the server permits local loading; see Section 8.1.6, "Security Considerations for LOAD DATA LOCAL"

? --local-infile[={0|1}]

??

? Command-Line Format ? --local-infile[={0|1}] ?

??

? Type ? Boolean ?

??

? Default Value ? FALSE ?

??

By default, LOCAL capability for LOAD DATA is determined by the default compiled into the MySQL client library. To enable or disable LOCAL data loading explicitly, use the

--local-infile option. When given with no value, the option enables LOCAL data loading. When given as --local-infile=0 or --local-infile=1, the option disables or enables LOCAL data loading.

If LOCAL capability is disabled, the --load-data-local-dir option can be used to permit restricted local loading of files located in a designated directory.

Successful use of LOCAL load operations within mysql also requires that the server permits local loading; see Section 8.1.6, "Security Considerations for LOAD DATA LOCAL"

? --login-path=name

??

? Command-Line Format ? --login-path=name ?

??

? Type ? String ?

??

Read options from the named login path in the .mylogin.cnf login path file. A ?login path? is an option group containing options that specify which MySQL server to connect to and which account to authenticate as. To create or modify a login path file, use the mysql_config_editor utility. See mysql_config_editor(1).

For additional information about this and other option-file options, see Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --no-login-paths

??

? Command-Line Format ? --no-login-paths ?

??

Skips reading options from the login path file.

See --login-path for related information.

For additional information about this and other option-file options, see Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --max-allowed-packet=value

??

? Command-Line Format ? --max-allowed-packet=value ?

??

? Type ? Numeric ?

??

? Default Value ? 16777216 ?

??

The maximum size of the buffer for client/server communication. The default is 16MB, the maximum is 1GB.

? --max-join-size=value

??

? Command-Line Format ? --max-join-size=value ?

??

? Type ? Numeric ?

??

? Default Value ? 1000000 ?

??

The automatic limit for rows in a join when using --safe-updates. (Default value is 1,000,000.)

? --named-commands, -G

??

? Command-Line Format ? --named-commands ?

??

? Disabled by ? skip-named-commands ?

??

Enable named mysql commands. Long-format commands are permitted, not just short-format commands. For example, quit and \q both are recognized. Use --skip-named-commands to disable named commands. See the section called ?MYSQL CLIENT COMMANDS?.

? --net-buffer-length=value

??

? Command-Line Format ? --net-buffer-length=value ?

??

? Type ? Numeric ?

??

? Default Value ? 16384 ?

??

The buffer size for TCP/IP and socket communication. (Default value is 16KB.)

? --network-namespace=name

??

? Command-Line Format ? --network-namespace=name ?

??

? Type ? String ?

??

The network namespace to use for TCP/IP connections. If omitted, the connection uses the default (global) namespace. For information about network namespaces, see Section 7.1.14, "Network Namespace Support".

This option is available only on platforms that implement network namespace support.

? --no-auto-rehash, -A

??

? Command-Line Format ? --no-auto-rehash ?

??

? Deprecated ? Yes ?

??

This has the same effect as --skip-auto-rehash. See the description for --auto-rehash.

? --no-beep, -b

??

? Command-Line Format ? --no-beep ?

??

Do not beep when errors occur.

? --no-defaults

??

? Command-Line Format ? --no-defaults ?

??

Do not read any option files. If program startup fails due to reading unknown options from an option file, --no-defaults can be used to prevent them from being read.

The exception is that the .mylogin.cnf file is read in all cases, if it exists. This permits passwords to be specified in a safer way than on the command line even when --no-defaults is used. To create .mylogin.cnf, use the mysql_config_editor utility. See mysql_config_editor(1).

For additional information about this and other option-file options, see

Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --oci-config-file=PATH

??

? Command-Line Format ? --oci-config-file ?

??

? Type ? String ?

??

? Default Value ? ?

??

Alternate path to the Oracle Cloud Infrastructure CLI configuration file. Specify the location of the configuration file. If your existing default profile is the correct one, you do not need to specify this option. However, if you have an existing configuration file, with multiple profiles or a different default from the tenancy of the user you want to connect with, specify this option.

? --one-database, -o

??

? Command-Line Format ? --one-database ?

??

Ignore statements except those that occur while the default database is the one named on the command line. This option is rudimentary and should be used with care. Statement filtering is based only on USE statements.

Initially, mysql executes statements in the input because specifying a database db_name on the command line is equivalent to inserting USE db_name at the beginning of the input. Then, for each USE statement encountered, mysql accepts or rejects following statements depending on whether the database named is the one on the command line. The content of the statements is immaterial.

Suppose that mysql is invoked to process this set of statements:

```
DELETE FROM db2.t2;

USE db2;

DROP TABLE db1.t1;

CREATE TABLE db1.t1 (i INT);

USE db1;

INSERT INTO t1 (i) VALUES(1);

CREATE TABLE db2.t1 (j INT);
```

If the command line is `mysql --force --one-database db1`, `mysql` handles the input as follows:

- ? The `DELETE` statement is executed because the default database is `db1`, even though the statement names a table in a different database.
- ? The `DROP TABLE` and `CREATE TABLE` statements are not executed because the default database is not `db1`, even though the statements name a table in `db1`.
- ? The `INSERT` and `CREATE TABLE` statements are executed because the default database is `db1`, even though the `CREATE TABLE` statement names a table in a different database.

? `--pager[=command]`

??

? Command-Line Format ? `--pager[=command]` ?

??

? Disabled by ? `skip-pager` ?

??

? Type ? String ?

??

Use the given command for paging query output. If the command is omitted, the default pager is the value of your `PAGER` environment variable. Valid pagers are `less`, `more`, `cat` [`> filename`], and so forth. This option works only on Unix and only in interactive mode. To disable paging, use `--skip-pager`. the section called `?MYSQL CLIENT COMMANDS?`, discusses output paging further.

? `--password[=password]`, `-p[password]`

??

? Command-Line Format ? `--password[=password]` ?

??

? Type ? String ?

??

The password of the MySQL account used for connecting to the server. The password value is optional. If not given, `mysql` prompts for one. If given, there must be no space between `--password=` or `-p` and the password following it. If no password option is specified, the default is to send no password.

Specifying a password on the command line should be considered insecure. To avoid giving the password on the command line, use an option file. See Section 8.1.2.1, `?End-User`

Guidelines for Password Security?.

To explicitly specify that there is no password and that mysql should not prompt for one, use the --skip-password option.

? --password1[=pass_val] The password for multifactor authentication factor 1 of the MySQL account used for connecting to the server. The password value is optional. If not given, mysql prompts for one. If given, there must be no space between --password1= and the password following it. If no password option is specified, the default is to send no password.

Specifying a password on the command line should be considered insecure. To avoid giving the password on the command line, use an option file. See Section 8.1.2.1, ?End-User Guidelines for Password Security?.

To explicitly specify that there is no password and that mysql should not prompt for one, use the --skip-password1 option.

--password1 and --password are synonymous, as are --skip-password1 and --skip-password.

? --password2[=pass_val] The password for multifactor authentication factor 2 of the MySQL account used for connecting to the server. The semantics of this option are similar to the semantics for --password1; see the description of that option for details.

? --password3[=pass_val] The password for multifactor authentication factor 3 of the MySQL account used for connecting to the server. The semantics of this option are similar to the semantics for --password1; see the description of that option for details.

? --pipe, -W

????????????????????????????????

? Command-Line Format ? --pipe ?

????????????????????????????????

? Type ? String ?

????????????????????????????????

On Windows, connect to the server using a named pipe. This option applies only if the server was started with the named_pipe system variable enabled to support named-pipe connections. In addition, the user making the connection must be a member of the Windows group specified by the named_pipe_full_access_group system variable.

? --plugin-authentication-kerberos-client-mode=value

??

? Command-Line Format ? --plugin-authentication-kerberos- ?

```

?          ? client-mode          ?

????????????????????????????????????????????????????????????

? Type          ? String          ?

????????????????????????????????????????????????????????????

? Default Value  ? SSPI            ?

????????????????????????????????????????????????????????????

? Valid Values   ?                  ?

?          ?          GSSAPI        ?

?          ?                  ?

?          ?          SSPI          ?

????????????????????????????????????????????????????????????

```

On Windows, the authentication_kerberos_client authentication plugin supports this plugin option. It provides two possible values that the client user can set at runtime: SSPI and GSSAPI.

The default value for the client-side plugin option uses Security Support Provider Interface (SSPI), which is capable of acquiring credentials from the Windows in-memory cache. Alternatively, the client user can select a mode that supports Generic Security Service Application Program Interface (GSSAPI) through the MIT Kerberos library on Windows. GSSAPI is capable of acquiring cached credentials previously generated by using the kinit command.

For more information, see [Commands for Windows Clients in GSSAPI Mode](#).

```

? --plugin-authentication-webauthn-client-preserve-privacy={OFF|ON}

????????????????????????????????????????????????????????????

? Command-Line Format ? --plugin-authentication-webauthn- ?

?          ? client-preserve-privacy          ?

????????????????????????????????????????????????????????????

? Type          ? Boolean          ?

????????????????????????????????????????????????????????????

? Default Value  ? OFF            ?

????????????????????????????????????????????????????????????

```

Determines how assertions are sent to server in case there is more than one discoverable credential stored for a given RP ID (a unique name given to the relying-party server, which is the MySQL server). If the FIDO2 device contains multiple resident keys for a

given RP ID, this option allows the user to choose a key to be used for assertion. It provides two possible values that the client user can set. The default value is OFF. If set to OFF, the challenge is signed by all credentials available for a given RP ID and all signatures are sent to server. If set to ON, the user is prompted to choose the credential to be used for signature.

Note

This option has no effect if the device does not support the resident-key feature. For more information, see Section 8.4.1.11, "WebAuthn Pluggable Authentication".

? --plugin-dir=dir_name

??

? Command-Line Format ? --plugin-dir=dir_name ?

??

? Type ? Directory name ?

??

The directory in which to look for plugins. Specify this option if the --default-auth option is used to specify an authentication plugin but mysql does not find it. See Section 8.2.17, "Pluggable Authentication".

? --port=port_num, -P port_num

??

? Command-Line Format ? --port=port_num ?

??

? Type ? Numeric ?

??

? Default Value ? 3306 ?

??

For TCP/IP connections, the port number to use.

? --print-defaults

??

? Command-Line Format ? --print-defaults ?

??

Print the program name and all options that it gets from option files.

For additional information about this and other option-file options, see

Section 6.2.2.3, "Command-Line Options that Affect Option-File Handling".

? --prompt=format_str

??

? Command-Line Format ? --prompt=format_str ?

??

? Type ? String ?

??

? Default Value ? mysql> ?

??

Set the prompt to the specified format. The default is mysql>. The special sequences that the prompt can contain are described in the section called ?MYSQL CLIENT COMMANDS?.

? --protocol={TCP|SOCKET|PIPE|MEMORY}

??

? Command-Line Format ? --protocol=type ?

??

? Type ? String ?

??

? Default Value ? [see text] ?

??

? Valid Values ? ?

? ? TCP ?

? ? ?

? ? SOCKET ?

? ? ?

? ? PIPE ?

? ? ?

? ? MEMORY ?

??

The transport protocol to use for connecting to the server. It is useful when the other connection parameters normally result in use of a protocol other than the one you want.

For details on the permissible values, see Section 6.2.7, ?Connection Transport Protocols?.

? --quick, -q

??

? Command-Line Format ? --quick ?

????????????????????????????????

Do not cache each query result, print each row as it is received. This may slow down the server if the output is suspended. With this option, mysql does not use the history file.

By default, mysql fetches all result rows before producing any output; while storing these, it calculates a running maximum column length from the actual value of each column in succession. When printing the output, it uses this maximum to format it. When --quick is specified, mysql does not have the rows for which to calculate the length before starting, and so uses the maximum length. In the following example, table t1 has a single column of type BIGINT and containing 4 rows. The default output is 9 characters wide; this width is equal the maximum number of characters in any of the column values in the rows returned (5), plus 2 characters each for the spaces used as padding and the | characters used as column delimiters). The output when using the --quick option is 25 characters wide; this is equal to the number of characters needed to represent -9223372036854775808, which is the longest possible value that can be stored in a (signed) BIGINT column, or 19 characters, plus the 4 characters used for padding and column delimiters. The difference can be seen here:

```
$> mysql -t test -e "SELECT * FROM t1"
```

```
+-----+
| c1  |
+-----+
| 100 |
| 1000 |
| 10000 |
| 10 |
+-----+
```

```
$> mysql --quick -t test -e "SELECT * FROM t1"
```

```
+-----+
| c1          |
+-----+
|          100 |
|          1000 |
```

```
|          10000 |
|          10 |
+-----+
```

? --raw, -r

????????????????????????????????

? Command-Line Format ? --raw ?

????????????????????????????????

For tabular output, the ?boxing? around columns enables one column value to be distinguished from another. For nontabular output (such as is produced in batch mode or when the --batch or --silent option is given), special characters are escaped in the output so they can be identified easily. Newline, tab, NUL, and backslash are written as \n, \t, \0, and \\. The --raw option disables this character escaping.

The following example demonstrates tabular versus nontabular output and the use of raw mode to disable escaping:

```
% mysql
mysql> SELECT CHAR(92);
+-----+
| CHAR(92) |
+-----+
| \      |
+-----+
```

```
% mysql -s
mysql> SELECT CHAR(92);
CHAR(92)
\\
```

```
% mysql -s -r
mysql> SELECT CHAR(92);
CHAR(92)
\
```

? --reconnect

????????????????????????????????

? Command-Line Format ? --reconnect ?

????????????????????????????????

? Disabled by ? skip-reconnect ?

??

If the connection to the server is lost, automatically try to reconnect. A single reconnect attempt is made each time the connection is lost. To suppress reconnection behavior, use --skip-reconnect.

? --register-factor=value

??

? Command-Line Format ? --register-factor=value ?

??

? Type ? String ?

??

The factor or factors for which FIDO/FIDO2 device registration must be performed before WebAuthn device-based authentication can be used. This option value must be a single value, or two values separated by commas. Each value must be 2 or 3, so the permitted option values are '2', '3', '2,3' and '3,2'.

For example, an account that requires registration for a third authentication factor invokes the mysql client as follows:

```
mysql --user=user_name --register-factor=3
```

An account that requires registration for second and third authentication factors invokes the mysql client as follows:

```
mysql --user=user_name --register-factor=2,3
```

If registration is successful, a connection is established. If there is an authentication factor with a pending registration, a connection is placed into pending registration mode when attempting to connect to the server. In this case, disconnect and reconnect with the correct --register-factor value to complete the registration.

Registration is a two-step process comprising initiate registration and finish registration steps. The initiate registration step executes this statement:

```
ALTER USER user factor INITIATE REGISTRATION
```

The statement returns a result set containing a 32 byte challenge, the user name, and the relying party ID (see authentication_webauthn_rp_id).

The finish registration step executes this statement:

```
ALTER USER user factor FINISH REGISTRATION SET CHALLENGE_RESPONSE AS 'auth_string'
```

The statement completes the registration and sends the following information to the

server as part of the auth_string: authenticator data, an optional attestation certificate in X.509 format, and a signature.

The initiate and registration steps must be performed in a single connection, as the challenge received by the client during the initiate step is saved to the client connection handler. Registration would fail if the registration step was performed by a different connection. The --register-factor option executes both the initiate and registration steps, which avoids the failure scenario described above and prevents having to execute the ALTER USER initiate and registration statements manually. The --register-factor option is only available for the mysql and MySQL Shell clients. Other MySQL client programs do not support it.

For related information, see the section called "Using WebAuthn Authentication".

? --safe-updates, --i-am-a-dummy, -U

??

? Command-Line Format ? ?

? ? --safe-updates ?

? ? ?

? ? --i-am-a-dummy ?

??

? Type ? Boolean ?

??

? Default Value ? FALSE ?

??

If this option is enabled, UPDATE and DELETE statements that do not use a key in the WHERE clause or a LIMIT clause produce an error. In addition, restrictions are placed on SELECT statements that produce (or are estimated to produce) very large result sets. If you have set this option in an option file, you can use --skip-safe-updates on the command line to override it. For more information about this option, see Using Safe-Updates Mode (--safe-updates).

? --select-limit=value

??

? Command-Line Format ? --select-limit=value ?

??

? Type ? Numeric ?

??

? Default Value ? 1000 ?

??

The automatic limit for SELECT statements when using --safe-updates. (Default value is 1,000.)

? --server-public-key-path=file_name

??

? Command-Line Format ? --server-public-key- ?

? ? path=file_name ?

??

? Type ? File name ?

??

The path name to a file in PEM format containing a client-side copy of the public key required by the server for RSA key pair-based password exchange. This option applies to clients that authenticate with the sha256_password (deprecated) or caching_sha2_password authentication plugin. This option is ignored for accounts that do not authenticate with one of those plugins. It is also ignored if RSA-based password exchange is not used, as is the case when the client connects to the server using a secure connection.

If --server-public-key-path=file_name is given and specifies a valid public key file, it takes precedence over --get-server-public-key.

For sha256_password (deprecated), this option applies only if MySQL was built using OpenSSL.

For information about the sha256_password and caching_sha2_password plugins, see Section 8.4.1.3, ?SHA-256 Pluggable Authentication?, and Section 8.4.1.2, ?Caching SHA-2 Pluggable Authentication?.

? --shared-memory-base-name=name

??

? Command-Line Format ? --shared-memory-base-name=name ?

??

? Platform Specific ? Windows ?

??

On Windows, the shared-memory name to use for connections made using shared memory to a local server. The default value is MYSQL. The shared-memory name is case-sensitive.

This option applies only if the server was started with the `shared_memory` system variable enabled to support shared-memory connections.

? --show-warnings

??

? Command-Line Format ? --show-warnings ?

??

Cause warnings to be shown after each statement if there are any. This option applies to interactive and batch mode.

? --sigint-ignore

??

? Command-Line Format ? --sigint-ignore ?

??

Ignore SIGINT signals (typically the result of typing Control+C).

Without this option, typing Control+C interrupts the current statement if there is one, or cancels any partial input line otherwise.

? --silent, -s

??

? Command-Line Format ? --silent ?

??

Silent mode. Produce less output. This option can be given multiple times to produce less and less output.

This option results in nontabular output format and escaping of special characters.

Escaping may be disabled by using raw mode; see the description for the `--raw` option.

? --skip-column-names, -N

??

? Command-Line Format ? --skip-column-names ?

??

Do not write column names in results. Use of this option causes the output to be right-aligned, as shown here:

```
$> echo "SELECT * FROM t1" | mysql -t test
```

```
+-----+
```

```
| c1  |
```

```
+-----+
```

```
| a,c,d |
```

```
| c |
```

```
+-----+
```

```
$> echo "SELECT * FROM t1" | ./mysql -uroot -Nt test
```

```
+-----+
```

```
| a,c,d |
```

```
| c |
```

```
+-----+
```

? --skip-line-numbers, -L

```
????????????????????????????????????????????????
```

? Command-Line Format ? --skip-line-numbers ?

```
????????????????????????????????????????????????
```

Do not write line numbers for errors. Useful when you want to compare result files that include error messages.

? --skip-system-command

```
????????????????????????????????????????????????
```

? Command-Line Format ? --skip-system-command ?

```
????????????????????????????????????????????????
```

Disables the system (!) command. Equivalent to --system-command=OFF.

? --socket=path, -S path

```
????????????????????????????????????????????????
```

? Command-Line Format ? --socket={file_name|pipe_name} ?

```
????????????????????????????????????????????????
```

? Type ? String ?

```
????????????????????????????????????????????????
```

For connections to localhost, the Unix socket file to use, or, on Windows, the name of the named pipe to use.

On Windows, this option applies only if the server was started with the named_pipe system variable enabled to support named-pipe connections. In addition, the user making the connection must be a member of the Windows group specified by the named_pipe_full_access_group system variable.

? --ssl* Options that begin with --ssl specify whether to connect to the server using

encryption and indicate where to find SSL keys and certificates. See the section called

?Command Options for Encrypted Connections?.

? --ssl-fips-mode={OFF|ON|STRICT}

??

? Command-Line Format ? --ssl-fips-mode={OFF|ON|STRICT} ?

??

? Deprecated ? Yes ?

??

? Type ? Enumeration ?

??

? Default Value ? OFF ?

??

? Valid Values ? ?

? ? OFF ?

? ? ?

? ? ON ?

? ? ?

? ? STRICT ?

??

Controls whether to enable FIPS mode on the client side. The --ssl-fips-mode option differs from other --ssl-xxx options in that it is not used to establish encrypted connections, but rather to affect which cryptographic operations to permit. See Section 8.8, ?FIPS Support?.

These --ssl-fips-mode values are permitted:

? OFF: Disable FIPS mode.

? ON: Enable FIPS mode.

? STRICT: Enable ?strict? FIPS mode.

Note

If the OpenSSL FIPS Object Module is not available, the only permitted value for --ssl-fips-mode is OFF. In this case, setting --ssl-fips-mode to ON or STRICT causes the client to produce a warning at startup and to operate in non-FIPS mode.

This option is deprecated. Expect it to be removed in a future version of MySQL.

? --syslog, -j

??

? Command-Line Format ? --syslog ?

????????????????????????????????

This option causes mysql to send interactive statements to the system logging facility.

On Unix, this is syslog; on Windows, it is the Windows Event Log. The destination where logged messages appear is system dependent. On Linux, the destination is often the /var/log/messages file.

Here is a sample of output generated on Linux by using --syslog. This output is formatted for readability; each logged message actually takes a single line.

```
Mar  7 12:39:25 myhost MysqlClient[20824]:
    SYSTEM_USER:'oscar', MYSQL_USER:'my_oscar', CONNECTION_ID:23,
    DB_SERVER:'127.0.0.1', DB:'--', QUERY:'USE test;'
Mar  7 12:39:28 myhost MysqlClient[20824]:
    SYSTEM_USER:'oscar', MYSQL_USER:'my_oscar', CONNECTION_ID:23,
    DB_SERVER:'127.0.0.1', DB:'test', QUERY:'SHOW TABLES;'
```

For more information, see the section called ?MYSQL CLIENT LOGGING?.

? --system-command[={ON|OFF}]

??

? Command-Line Format ? --system-command[={ON|OFF}] ?

??

? Disabled by ? skip-system-command ?

??

? Type ? Boolean ?

??

? Default Value ? ON ?

??

Enable or disable the system (!) command. When this option is disabled, either by --system-command=OFF or by --skip-system-command, the system command is rejected with an error.

(MySQL 8.4.6 and later:) --commands, when disabled (set to FALSE), causes the server to disregard any setting for this option.

? --table, -t

????????????????????????????????

? Command-Line Format ? --table ?

????????????????????????????????

Display output in table format. This is the default for interactive use, but can be used to produce table output in batch mode.

? --tee=file_name

????????????????????????????????

? Command-Line Format ? --tee=file_name ?

????????????????????????????????

? Type ? File name ?

????????????????????????????????

Append a copy of output to the given file. This option works only in interactive mode.
the section called ?MYSQL CLIENT COMMANDS?, discusses tee files further.

? --tls-ciphersuites=ciphersuite_list

????????????????????????????????

? Command-Line Format ? --tls- ?

? ? ciphersuites=ciphersuite_list ?

????????????????????????????????

? Type ? String ?

????????????????????????????????

The permissible ciphersuites for encrypted connections that use TLSv1.3. The value is a list of one or more colon-separated ciphersuite names. The ciphersuites that can be named for this option depend on the SSL library used to compile MySQL. For details, see Section 8.3.2, ?Encrypted Connection TLS Protocols and Ciphers?.

? --tls-sni-servername=server_name

????????????????????????????????

? Command-Line Format ? --tls-sni-servername=server_name ?

????????????????????????????????

? Type ? String ?

????????????????????????????????

When specified, the name is passed to the libmysqlclient C API library using the MYSQL_OPT_TLS_SNI_SERVERNAME option of mysql_options(). The server name is not case-sensitive. To show which server name the client specified for the current session, if any, check the Tls_sni_server_name status variable.

Server Name Indication (SNI) is an extension to the TLS protocol (OpenSSL must be

compiled using TLS extensions for this option to function). The MySQL implementation of SNI represents the client-side only.

? --tls-version=protocol_list

??

? Command-Line Format ? --tls-version=protocol_list ?

??

? Type ? String ?

??

? Default Value ? ?

? ? TLSv1,TLSv1.1,TLSv1.2,TLSv1.3 ?

? ? (OpenSSL 1.1.1 or ?

? ? higher) ?

? ? ?

? ? TLSv1,TLSv1.1,TLSv1.2 ?

? ? (otherwise) ?

??

The permissible TLS protocols for encrypted connections. The value is a list of one or more comma-separated protocol names. The protocols that can be named for this option depend on the SSL library used to compile MySQL. For details, see Section 8.3.2,

?Encrypted Connection TLS Protocols and Ciphers?.

? --unbuffered, -n

??

? Command-Line Format ? --unbuffered ?

??

Flush the buffer after each query.

? --user=user_name, -u user_name

??

? Command-Line Format ? --user=user_name ?

??

? Type ? String ?

??

The user name of the MySQL account to use for connecting to the server.

? --verbose, -v

????????????????????????????????

? Command-Line Format ? --verbose ?

????????????????????????????????

Verbose mode. Produce more output about what the program does. This option can be given multiple times to produce more and more output. (For example, -v -v -v produces table output format even in batch mode.)

? --version, -V

????????????????????????????????

? Command-Line Format ? --version ?

????????????????????????????????

Display version information and exit.

? --vertical, -E

????????????????????????????????

? Command-Line Format ? --vertical ?

????????????????????????????????

Print query output rows vertically (one line per column value). Without this option, you can specify vertical output for individual statements by terminating them with \G.

? --wait, -w

????????????????????????????????

? Command-Line Format ? --wait ?

????????????????????????????????

If the connection cannot be established, wait and retry instead of aborting.

? --xml, -X

????????????????????????????????

? Command-Line Format ? --xml ?

????????????????????????????????

Produce XML output.

```
<field name="column_name">NULL</field>
```

The output when --xml is used with mysql matches that of mysqldump --xml. See mysqldump(1), for details.

The XML output also uses an XML namespace, as shown here:

```
$> mysql --xml -uroot -e "SHOW VARIABLES LIKE 'version%'"
```

```
<?xml version="1.0"?>
```

<resultset statement="SHOW VARIABLES LIKE 'version%'"

xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">

<row>

<field name="Variable_name">version</field>

<field name="Value">5.0.40-debug</field>

</row>

<row>

<field name="Variable_name">version_comment</field>

<field name="Value">Source distribution</field>

</row>

<row>

<field name="Variable_name">version_compile_machine</field>

<field name="Value">i686</field>

</row>

<row>

<field name="Variable_name">version_compile_os</field>

<field name="Value">suse-linux-gnu</field>

</row>

</resultset>

? --zstd-compression-level=level

??

? Command-Line Format ? --zstd-compression-level=# ?

??

? Type ? Integer ?

??

The compression level to use for connections to the server that use the zstd compression algorithm. The permitted levels are from 1 to 22, with larger values indicating increasing levels of compression. The default zstd compression level is 3. The compression level setting has no effect on connections that do not use zstd compression. For more information, see Section 6.2.8, ?Connection Compression Control?.

? telemetry_client

??

? Command-Line Format ? --telemetry_client ?

??

? Type ? Boolean ?

??

? Default Value ? OFF ?

??

Enables the telemetry client plugin (Linux only).

For more information, see Chapter 35, Telemetry.

MYSQL CLIENT COMMANDS

mysql sends each SQL statement that you issue to the server to be executed. There is also a set of commands that mysql itself interprets. For a list of these commands, type help or \h at the mysql> prompt:

```
mysql> help
```

List of all MySQL commands:

Note that all text commands must be first on line and end with ';'.

? (\?) Synonym for `help'.

clear (\c) Clear the current input statement.

connect (\r) Reconnect to the server. Optional arguments are db and host.

delimiter (\d) Set statement delimiter.

edit (\e) Edit command with \$EDITOR.

ego (\G) Send command to mysql server, display result vertically.

exit (\q) Exit mysql. Same as quit.

go (\g) Send command to mysql server.

help (\h) Display this help.

nopager (\n) Disable pager, print to stdout.

notee (\t) Don't write into outfile.

pager (\P) Set PAGER [to_pager]. Print the query results via PAGER.

print (\p) Print current command.

prompt (\R) Change your mysql prompt.

quit (\q) Quit mysql.

rehash (\#) Rebuild completion hash.

source (\.) Execute an SQL script file. Takes a file name as an argument.

status (\s) Get status information from the server.

system (\!) Execute a system shell command.

`tee` (\T) Set outfile [to_outfile]. Append everything into given outfile.

`use` (\u) Use another database. Takes database name as argument.

`charset` (\C) Switch to another charset. Might be needed for processing binlog with multi-byte charsets.

`warnings` (\W) Show warnings after every statement.

`nowarning` (\w) Don't show warnings after every statement.

`resetconnection`(\x) Clean session context.

`query_attributes` Sets string parameters (name1 value1 name2 value2 ...) for the next query to pick up.

`ssl_session_data_print` Serializes the current SSL session data to stdout or file.

For server side help, type 'help contents'

If `mysql` is invoked with the `--binary-mode` option, all `mysql` commands are disabled except `charset` and `delimiter` in noninteractive mode (for input piped to `mysql` or loaded using the `source` command). Beginning with MySQL 8.4.6, the `--commands` option can be used to enable or disable all commands except `/C`, `delimiter`, and `use`.

Each command has both a long and short form. The long form is not case-sensitive; the short form is. The long form can be followed by an optional semicolon terminator, but the short form should not.

The use of short-form commands within multiple-line `/* ... */` comments is not supported.

Short-form commands do work within single-line `/*! ... */` version comments, as do `/*+ ... */` optimizer-hint comments, which are stored in object definitions. If there is a concern that optimizer-hint comments may be stored in object definitions so that dump files when reloaded with `mysql` would result in execution of such commands, either invoke `mysql` with the `--binary-mode` option or use a reload client other than `mysql`.

? help [arg], \h [arg], \? [arg], ? [arg]

Display a help message listing the available `mysql` commands.

If you provide an argument to the `help` command, `mysql` uses it as a search string to access server-side help from the contents of the MySQL Reference Manual. For more information, see the section called `?MYSQL CLIENT SERVER-SIDE HELP?`.

? charset charset_name, \C charset_name

Change the default character set and issue a `SET NAMES` statement. This enables the

character set to remain synchronized on the client and server if mysql is run with auto-reconnect enabled (which is not recommended), because the specified character set is used for reconnects.

? clear, \c

Clear the current input. Use this if you change your mind about executing the statement that you are entering.

? connect [db_name [host_name]], \r [db_name [host_name]]

Reconnect to the server. The optional database name and host name arguments may be given to specify the default database or the host where the server is running. If omitted, the current values are used.

If the connect command specifies a host name argument, that host takes precedence over any --dns-srv-name option given at mysql startup to specify a DNS SRV record.

? delimiter str, \d str

Change the string that mysql interprets as the separator between SQL statements. The default is the semicolon character (;).

The delimiter string can be specified as an unquoted or quoted argument on the delimiter command line. Quoting can be done with either single quote ('), double quote ("), or backtick (`) characters. To include a quote within a quoted string, either quote the string with a different quote character or escape the quote with a backslash (\) character. Backslash should be avoided outside of quoted strings because it is the escape character for MySQL. For an unquoted argument, the delimiter is read up to the first space or end of line. For a quoted argument, the delimiter is read up to the matching quote on the line.

mysql interprets instances of the delimiter string as a statement delimiter anywhere it occurs, except within quoted strings. Be careful about defining a delimiter that might occur within other words. For example, if you define the delimiter as X, it is not possible to use the word INDEX in statements. mysql interprets this as INDE followed by the delimiter X.

When the delimiter recognized by mysql is set to something other than the default of ;, instances of that character are sent to the server without interpretation. However, the server itself still interprets ; as a statement delimiter and processes statements accordingly. This behavior on the server side comes into play for multiple-statement execution (see Multiple Statement Execution Support[3]), and for parsing the body of

stored procedures and functions, triggers, and events (see Section 27.1, “Defining Stored Programs”).

? edit, \e

Edit the current input statement. mysql checks the values of the EDITOR and VISUAL environment variables to determine which editor to use. The default editor is vi if neither variable is set.

The edit command works only in Unix.

? ego, \G

Send the current statement to the server to be executed and display the result using vertical format.

? exit, \q

Exit mysql.

? go, \g

Send the current statement to the server to be executed.

? nopager, \n

Disable output paging. See the description for pager.

The nopager command works only in Unix.

? notee, \t

Disable output copying to the tee file. See the description for tee.

? nowarning, \w

Disable display of warnings after each statement.

? pager [command], \P [command]

Enable output paging. By using the --pager option when you invoke mysql, it is possible to browse or search query results in interactive mode with Unix programs such as less, more, or any other similar program. If you specify no value for the option, mysql checks the value of the PAGER environment variable and sets the pager to that. Pager functionality works only in interactive mode.

Output paging can be enabled interactively with the pager command and disabled with nopager. The command takes an optional argument; if given, the paging program is set to that. With no argument, the pager is set to the pager that was set on the command line, or stdout if no pager was specified.

Output paging works only in Unix because it uses the popen() function, which does not exist on Windows. For Windows, the tee option can be used instead to save query output,

although it is not as convenient as pager for browsing output in some situations.

? print, \p

Print the current input statement without executing it.

? prompt [str], \R [str]

Reconfigure the mysql prompt to the given string. The special character sequences that can be used in the prompt are described later in this section.

If you specify the prompt command with no argument, mysql resets the prompt to the default of mysql>.

? query_attributes name value [name value ...]

Define query attributes that apply to the next query sent to the server. For discussion of the purpose and use of query attributes, see Section 11.6, "Query Attributes".

The query_attributes command follows these rules:

- ? The format and quoting rules for attribute names and values are the same as for the delimiter command.

- ? The command permits up to 32 attribute name/value pairs. Names and values may be up to 1024 characters long. If a name is given without a value, an error occurs.

- ? If multiple query_attributes commands are issued prior to query execution, only the last command applies. After sending the query, mysql clears the attribute set.

- ? If multiple attributes are defined with the same name, attempts to retrieve the attribute value have an undefined result.

- ? An attribute defined with an empty name cannot be retrieved by name.

- ? If a reconnect occurs while mysql executes the query, mysql restores the attributes after reconnecting so the query can be executed again with the same attributes.

? quit, \q

Exit mysql.

? rehash, \#

Rebuild the completion hash that enables database, table, and column name completion while you are entering statements. (See the description for the --auto-rehash option.)

? resetconnection, \x

Reset the connection to clear the session state. This includes clearing any current query attributes defined using the query_attributes command.

Resetting a connection has effects similar to mysql_change_user() or an auto-reconnect except that the connection is not closed and reopened, and re-authentication is not

done. See `mysql_change_user()`[4], and Automatic Reconnection Control[5].

This example shows how `resetconnection` clears a value maintained in the session state:

```
mysql> SELECT LAST_INSERT_ID(3);
```

```
+-----+
```

```
| LAST_INSERT_ID(3) |
```

```
+-----+
```

```
|          3 |
```

```
+-----+
```

```
mysql> SELECT LAST_INSERT_ID();
```

```
+-----+
```

```
| LAST_INSERT_ID() |
```

```
+-----+
```

```
|          3 |
```

```
+-----+
```

```
mysql> resetconnection;
```

```
mysql> SELECT LAST_INSERT_ID();
```

```
+-----+
```

```
| LAST_INSERT_ID() |
```

```
+-----+
```

```
|          0 |
```

```
+-----+
```

? `source file_name, \. file_name`

Read the named file and executes the statements contained therein. On Windows, specify path name separators as / or \.

Quote characters are taken as part of the file name itself. For best results, the name should not include space characters.

? `ssl_session_data_print [file_name]`

Fetches, serializes, and optionally stores the session data of a successful connection.

The optional file name and arguments may be given to specify the file to store

serialized session data. If omitted, the session data is printed to stdout.

If the MySQL session is configured for reuse, session data from the file is deserialized

and supplied to the connect command to reconnect. When the session is reused

successfully, the status command contains a row showing SSL session reused: true while

the client remains reconnected to the server.

? status, \s

Provide status information about the connection and the server you are using. If you are running with --safe-updates enabled, status also prints the values for the mysql variables that affect your queries.

? system command, \! command

Execute the given command using your default command interpreter.

In MySQL 8.4.3 and later, this command can be disabled by starting the client with --system-command=OFF or --skip-system-command.

? tee [file_name], \T [file_name]

By using the --tee option when you invoke mysql, you can log statements and their output. All the data displayed on the screen is appended into a given file. This can be very useful for debugging purposes also. mysql flushes results to the file after each statement, just before it prints its next prompt. Tee functionality works only in interactive mode.

You can enable this feature interactively with the tee command. Without a parameter, the previous file is used. The tee file can be disabled with the notee command. Executing tee again re-enables logging.

? use db_name, \u db_name

Use db_name as the default database.

? warnings, \W

Enable display of warnings after each statement (if there are any).

Here are a few tips about the pager command:

? You can use it to write to a file and the results go only to the file:

```
mysql> pager cat > /tmp/log.txt
```

You can also pass any options for the program that you want to use as your pager:

```
mysql> pager less -n -i -S
```

? In the preceding example, note the -S option. You may find it very useful for browsing wide query results. Sometimes a very wide result set is difficult to read on the screen.

The -S option to less can make the result set much more readable because you can scroll it horizontally using the left-arrow and right-arrow keys. You can also use -S interactively within less to switch the horizontal-browse mode on and off. For more information, read the less manual page:

man less

? The -F and -X options may be used with less to cause it to exit if output fits on one screen, which is convenient when no scrolling is necessary:

```
mysql> pager less -n -i -S -F -X
```

? You can specify very complex pager commands for handling query output:

```
mysql> pager cat | tee /dr1/tmp/res.txt \  
      | tee /dr2/tmp/res2.txt | less -n -i -S
```

In this example, the command would send query results to two files in two different directories on two different file systems mounted on /dr1 and /dr2, yet still display the results onscreen using less.

You can also combine the tee and pager functions. Have a tee file enabled and pager set to less, and you are able to browse the results using the less program and still have everything appended into a file the same time. The difference between the Unix tee used with the pager command and the mysql built-in tee command is that the built-in tee works even if you do not have the Unix tee available. The built-in tee also logs everything that is printed on the screen, whereas the Unix tee used with pager does not log quite that much. Additionally, tee file logging can be turned on and off interactively from within mysql.

This is useful when you want to log some queries to a file, but not others.

The prompt command reconfigures the default mysql> prompt. The string for defining the prompt can contain the following special sequences.

```
r  
.br  
.br  
72  
????????????????????????????????????????????????????????????  
? Option           ? Description           ?  
????????????????????????????????????????????????????????????  
?                  ? The current connection identifier ?  
????????????????????????????????????????????????????????????  
?                  ? A counter that increments for    ?  
?                  ? each statement you issue      ?  
????????????????????????????????????????????????????????????  
?                  ? The full current date              ?
```

??

? ? The default database ?

??

? ? The server host ?

??

? ? The current delimiter ?

??

? ? Minutes of the current time ?

??

? ? A newline character ?

??

? ? The current month in three-letter ?

? ? format (Jan, Feb, ...) ?

??

? ? The current month in numeric ?

? ? format ?

??

? P ? am/pm ?

??

? ? The current TCP/IP port or socket ?

? ? file ?

??

? ? The current time, in 24-hour ?

? ? military time (0?23) ?

??

? ? The current time, standard ?

? ? 12-hour time (1?12) ?

??

? ? Semicolon ?

??

? ? Seconds of the current time ?

??

? T ? Print an asterisk (*) if the ?

? ? current session is ?

? ? inside a ?

? ? transaction block ?

??

? ? A tab character ?

??

? U ? ?

? ? Your full ?

? ? user_name@host_name ?

? ? account name ?

??

? ? Your user name ?

??

? ? The server version ?

??

? ? The current day of the week in ?

? ? three-letter format (Mon, Tue, ?

? ? ...)

??

? ? The current year, four digits ?

??

? y ? The current year, two digits ?

??

? _ ? A space ?

??

? \ ? A space (a space follows the ?

? ? backslash) ?

??

? ? ? Single quote ?

??

? ? Double quote ?

??

? T};T{ A literal backslash ?

```
? character      ?
????????????????????????????????????????????????????????????
? \lx           ?
?               ? x, for any ?x? not listed ?
?               ? above
????????????????????????????????????????????????????????????
```

You can set the prompt in several ways:

? Use an environment variable. You can set the MYSQL_PS1 environment variable to a prompt string. For example:

```
export MYSQL_PS1="(\\u@\\h) [\\d]> "
```

? Use a command-line option. You can set the --prompt option on the command line to mysql. For example:

```
$> mysql --prompt="(\\u@\\h) [\\d]> "
(user@host) [database]>
```

? Use an option file. You can set the prompt option in the [mysql] group of any MySQL option file, such as /etc/my.cnf or the .my.cnf file in your home directory. For example:

```
[mysql]
prompt=(\\u@\\h) [\\d]>\\_
```

In this example, note that the backslashes are doubled. If you set the prompt using the prompt option in an option file, it is advisable to double the backslashes when using the special prompt options. There is some overlap in the set of permissible prompt options and the set of special escape sequences that are recognized in option files. (The rules for escape sequences in option files are listed in Section 6.2.2.2, "Using Option Files".) The overlap may cause you problems if you use single backslashes. For example, \\s is interpreted as a space rather than as the current seconds value. The following example shows how to define a prompt within an option file to include the current time in hh:mm:ss> format:

```
[mysql]
prompt="(\\r:\\m:\\s> "
```

? Set the prompt interactively. You can change your prompt interactively by using the prompt (or \\R) command. For example:

```
mysql> prompt (\\u@\\h) [\\d]>\\_
```

PROMPT set to '(\u@\h) [\d]>_ '

(user@host) [database]>

(user@host) [database]> prompt

Returning to default PROMPT of mysql>

mysql>

MYSQL CLIENT LOGGING

The mysql client can do these types of logging for statements executed interactively:

- ? On Unix, mysql writes the statements to a history file. By default, this file is named .mysql_history in your home directory. To specify a different file, set the value of the MYSQL_HISTFILE environment variable.
- ? On all platforms, if the --syslog option is given, mysql writes the statements to the system logging facility. On Unix, this is syslog; on Windows, it is the Windows Event Log. The destination where logged messages appear is system dependent. On Linux, the destination is often the /var/log/messages file.

The following discussion describes characteristics that apply to all logging types and provides information specific to each logging type.

- ? How Logging Occurs
- ? Controlling the History File
- ? syslog Logging Characteristics

How Logging Occurs

For each enabled logging destination, statement logging occurs as follows:

- ? Statements are logged only when executed interactively. Statements are noninteractive, for example, when read from a file or a pipe. It is also possible to suppress statement logging by using the --batch or --execute option.
- ? Statements are ignored and not logged if they match any pattern in the ?ignore? list. This list is described later.
- ? mysql logs each nonignored, nonempty statement line individually.
- ? If a nonignored statement spans multiple lines (not including the terminating delimiter), mysql concatenates the lines to form the complete statement, maps newlines to spaces, and logs the result, plus a delimiter.

Consequently, an input statement that spans multiple lines can be logged twice. Consider this input:

mysql> SELECT

```
-> 'Today is'
-> ,
-> CURDATE()
-> ;
```

In this case, mysql logs the `?SELECT?, ?'Today is'?, ?,?, ?CURDATE()?,` and `?;?` lines as it reads them. It also logs the complete statement, after mapping `SELECT\n'Today is'\n,\nCURDATE()` to `SELECT 'Today is' , CURDATE()`, plus a delimiter. Thus, these lines appear in logged output:

```
SELECT
'Today is'
,
CURDATE()
;
SELECT 'Today is' , CURDATE();
```

mysql ignores for logging purposes statements that match any pattern in the `?ignore?` list.

By default, the pattern list is `"*IDENTIFIED*:PASSWORD*"`, to ignore statements that refer to passwords. Pattern matching is not case-sensitive. Within patterns, two characters are special:

`? ?` matches any single character.

`? *` matches any sequence of zero or more characters.

To specify additional patterns, use the `--histignore` option or set the `MYSQL_HISTIGNORE` environment variable. (If both are specified, the option value takes precedence.) The value should be a list of one or more colon-separated patterns, which are appended to the default pattern list.

Patterns specified on the command line might need to be quoted or escaped to prevent your command interpreter from treating them specially. For example, to suppress logging for `UPDATE` and `DELETE` statements in addition to statements that refer to passwords, invoke mysql like this:

```
mysql --histignore="*UPDATE*:DELETE*"
```

Controlling the History File

The `.mysql_history` file should be protected with a restrictive access mode because sensitive information might be written to it, such as the text of SQL statements that contain

passwords. See Section 8.1.2.1, `?End-User Guidelines for Password Security?`. Statements in

the file are accessible from the mysql client when the up-arrow key is used to recall the history. See Disabling Interactive History.

If you do not want to maintain a history file, first remove .mysql_history if it exists.

Then use either of the following techniques to prevent it from being created again:

- ? Set the MYSQL_HISTFILE environment variable to /dev/null. To cause this setting to take effect each time you log in, put it in one of your shell's startup files.
- ? Create .mysql_history as a symbolic link to /dev/null; this need be done only once:

```
In -s /dev/null $HOME/.mysql_history
```

syslog Logging Characteristics

If the --syslog option is given, mysql writes interactive statements to the system logging facility. Message logging has the following characteristics.

Logging occurs at the ?information? level. This corresponds to the LOG_INFO priority for syslog on Unix/Linux syslog capability and to EVENTLOG_INFORMATION_TYPE for the Windows Event Log. Consult your system documentation for configuration of your logging capability.

Message size is limited to 1024 bytes.

Messages consist of the identifier MySQLClient followed by these values:

? SYSTEM_USER

The operating system user name (login name) or -- if the user is unknown.

? MYSQL_USER

The MySQL user name (specified with the --user option) or -- if the user is unknown.

? CONNECTION_ID:

The client connection identifier. This is the same as the CONNECTION_ID() function value within the session.

? DB_SERVER

The server host or -- if the host is unknown.

? DB

The default database or -- if no database has been selected.

? QUERY

The text of the logged statement.

Here is a sample of output generated on Linux by using --syslog. This output is formatted for readability; each logged message actually takes a single line.

```
Mar  7 12:39:25 myhost MySQLClient[20824]:
```

```
SYSTEM_USER:'oscar', MYSQL_USER:'my_oscar', CONNECTION_ID:23,
```

```
DB_SERVER:'127.0.0.1', DB:'--', QUERY:'USE test;'
```

```
Mar  7 12:39:28 myhost MysqlClient[20824]:
```

```
SYSTEM_USER:'oscar', MYSQL_USER:'my_oscar', CONNECTION_ID:23,
```

```
DB_SERVER:'127.0.0.1', DB:'test', QUERY:'SHOW TABLES;'
```

MYSQL CLIENT SERVER-SIDE HELP

```
mysql> help search_string
```

If you provide an argument to the help command, mysql uses it as a search string to access server-side help from the contents of the MySQL Reference Manual. The proper operation of this command requires that the help tables in the mysql database be initialized with help topic information (see Section 7.1.17, [?Server-Side Help Support?](#)).

If there is no match for the search string, the search fails:

```
mysql> help me
```

Nothing found

Please try to run 'help contents' for a list of all accessible topics

Use help contents to see a list of the help categories:

```
mysql> help contents
```

You asked for help about help category: "Contents"

For more information, type 'help <item>', where <item> is one of the following categories:

Account Management

Administration

Data Definition

Data Manipulation

Data Types

Functions

Functions and Modifiers for Use with GROUP BY

Geographic Features

Language Structure

Plugins

Storage Engines

Stored Routines

Table Maintenance

Transactions

Triggers

If the search string matches multiple items, mysql shows a list of matching topics:

```
mysql> help logs
```

Many help items for your request exist.

To make a more specific request, please type 'help <item>',

where <item> is one of the following topics:

SHOW

SHOW BINARY LOGS

SHOW ENGINE

SHOW LOGS

Use a topic as the search string to see the help entry for that topic:

```
mysql> help show binary logs
```

Name: 'SHOW BINARY LOGS'

Description:

Syntax:

SHOW BINARY LOGS

Lists the binary log files on the server. This statement is used as part of the procedure described in [purge-binary-logs], that shows how to determine which logs can be purged.

```
mysql> SHOW BINARY LOGS;
```

```
+-----+-----+-----+
| Log_name   | File_size | Encrypted |
+-----+-----+-----+
| binlog.000015 | 724935 | Yes      |
| binlog.000016 | 733481 | Yes      |
+-----+-----+-----+
```

The search string can contain the wildcard characters % and _. These have the same meaning as for pattern-matching operations performed with the LIKE operator. For example, HELP rep% returns a list of topics that begin with rep:

```
mysql> HELP rep%
```

Many help items for your request exist.

To make a more specific request, please type 'help <item>',

where <item> is one of the following

topics:

REPAIR TABLE

REPEAT FUNCTION

REPEAT LOOP

REPLACE

REPLACE FUNCTION

EXECUTING SQL STATEMENTS FROM A TEXT FILE

The mysql client typically is used interactively, like this:

```
mysql db_name
```

However, it is also possible to put your SQL statements in a file and then tell mysql to read its input from that file. To do so, create a text file `text_file` that contains the statements you wish to execute. Then invoke mysql as shown here:

```
mysql db_name < text_file
```

If you place a `USE db_name` statement as the first statement in the file, it is unnecessary to specify the database name on the command line:

```
mysql < text_file
```

If you are already running mysql, you can execute an SQL script file using the `source` command or `\.` command:

```
mysql> source file_name
```

```
mysql> \. file_name
```

Sometimes you may want your script to display progress information to the user. For this you can insert statements like this:

```
SELECT '<info_to_display>' AS ' ';
```

The statement shown outputs `<info_to_display>`.

You can also invoke mysql with the `--verbose` option, which causes each statement to be displayed before the result that it produces.

mysql ignores Unicode byte order mark (BOM) characters at the beginning of input files.

Previously, it read them and sent them to the server, resulting in a syntax error. Presence of a BOM does not cause mysql to change its default character set. To do that, invoke mysql with an option such as `--default-character-set=utf8mb4`.

For more information about batch mode, see Section 5.5, "Using mysql in Batch Mode".

MYSQL CLIENT TIPS

This section provides information about techniques for more effective use of mysql and about

mysql operational behavior.

- ? Input-Line Editing
- ? Disabling Interactive History
- ? Unicode Support on Windows
- ? Displaying Query Results Vertically
- ? Using Safe-Updates Mode (--safe-updates)
- ? Disabling mysql Auto-Reconnect
- ? mysql Client Parser Versus Server Parser

Input-Line Editing

mysql supports input-line editing, which enables you to modify the current input line in place or recall previous input lines. For example, the left-arrow and right-arrow keys move horizontally within the current input line, and the up-arrow and down-arrow keys move up and down through the set of previously entered lines. Backspace deletes the character before the cursor and typing new characters enters them at the cursor position. To enter the line, press Enter.

On Windows, the editing key sequences are the same as supported for command editing in console windows. On Unix, the key sequences depend on the input library used to build mysql (for example, the libedit or readline library).

Documentation for the libedit and readline libraries is available online. To change the set of key sequences permitted by a given input library, define key bindings in the library startup file. This is a file in your home directory: .editrc for libedit and .inputrc for readline.

For example, in libedit, Control+W deletes everything before the current cursor position and Control+U deletes the entire line. In readline, Control+W deletes the word before the cursor and Control+U deletes everything before the current cursor position. If mysql was built using libedit, a user who prefers the readline behavior for these two keys can put the following lines in the .editrc file (creating the file if necessary):

```
bind "^W" ed-delete-prev-word  
bind "^U" vi-kill-line-prev
```

To see the current set of key bindings, temporarily put a line that says only bind at the end of .editrc. mysql shows the bindings when it starts. Disabling Interactive History
The up-arrow key enables you to recall input lines from current and previous sessions. In cases where a console is shared, this behavior may be unsuitable. mysql supports disabling

the interactive history partially or fully, depending on the host platform.

On Windows, the history is stored in memory. Alt+F7 deletes all input lines stored in memory for the current history buffer. It also deletes the list of sequential numbers in front of the input lines displayed with F7 and recalled (by number) with F9. New input lines entered after you press Alt+F7 repopulate the current history buffer. Clearing the buffer does not prevent logging to the Windows Event Viewer, if the --syslog option was used to start mysql. Closing the console window also clears the current history buffer.

To disable interactive history on Unix, first delete the .mysql_history file, if it exists (previous entries are recalled otherwise). Then start mysql with the --histignore="" option to ignore all new input lines. To re-enable the recall (and logging) behavior, restart mysql without the option.

If you prevent the .mysql_history file from being created (see Controlling the History File) and use --histignore="" to start the mysql client, the interactive history recall facility is disabled fully. Alternatively, if you omit the --histignore option, you can recall the input lines entered during the current session.

Unicode Support on Windows

Windows provides APIs based on UTF-16LE for reading from and writing to the console; the mysql client for Windows is able to use these APIs. The Windows installer creates an item in the MySQL menu named MySQL command line client - Unicode. This item invokes the mysql client with properties set to communicate through the console to the MySQL server using Unicode.

To take advantage of this support manually, run mysql within a console that uses a compatible Unicode font and set the default character set to a Unicode character set that is supported for communication with the server:

1. Open a console window.
2. Go to the console window properties, select the font tab, and choose Lucida Console or some other compatible Unicode font. This is necessary because console windows start by default using a DOS raster font that is inadequate for Unicode.
3. Execute mysql.exe with the --default-character-set=utf8mb4 (or utf8mb3) option. This option is necessary because utf16le is one of the character sets that cannot be used as the client character set. See the section called ?Impermissible Client Character Sets?.

With those changes, mysql uses the Windows APIs to communicate with the console using UTF-16LE, and communicate with the server using UTF-8. (The menu item mentioned previously sets the font and character set as just described.)

To avoid those steps each time you run mysql, you can create a shortcut that invokes

mysql.exe. The shortcut should set the console font to Lucida Console or some other compatible Unicode font, and pass the --default-character-set=utf8mb4 (or utf8mb3) option to mysql.exe.

Alternatively, create a shortcut that only sets the console font, and set the character set in the [mysql] group of your my.ini file:

```
[mysql]

default-character-set=utf8mb4 # or utf8mb3
```

Displaying Query Results Vertically

Some query results are much more readable when displayed vertically, instead of in the usual horizontal table format. Queries can be displayed vertically by terminating the query with \G instead of a semicolon. For example, longer text values that include newlines often are much easier to read with vertical output:

```
mysql> SELECT * FROM mails WHERE LENGTH(txt) < 300 LIMIT 300,1\G
```

```
***** 1. row *****
```

```
msg_nro: 3068
```

```
date: 2000-03-01 23:29:50
```

```
time_zone: +0200
```

```
mail_from: Jones
```

```
reply: jones@example.com
```

```
mail_to: "John Smith" <smith@example.com>
```

```
sbj: UTF-8
```

```
txt: >>>> "John" == John Smith writes:
```

```
John> Hi. I think this is a good idea. Is anyone familiar
```

```
John> with UTF-8 or Unicode? Otherwise, I'll put this on my
```

```
John> TODO list and see what happens.
```

```
Yes, please do that.
```

```
Regards,
```

```
Jones
```

```
file: inbox-jani-1
```

```
hash: 190402944
```

```
1 row in set (0.09 sec)
```

Using Safe-Updates Mode (--safe-updates)

For beginners, a useful startup option is --safe-updates (or --i-am-a-dummy, which has the

same effect). Safe-updates mode is helpful for cases when you might have issued an UPDATE or DELETE statement but forgotten the WHERE clause indicating which rows to modify. Normally, such statements update or delete all rows in the table. With --safe-updates, you can modify rows only by specifying the key values that identify them, or a LIMIT clause, or both. This helps prevent accidents. Safe-updates mode also restricts SELECT statements that produce (or are estimated to produce) very large result sets.

The --safe-updates option causes mysql to execute the following statement when it connects to the MySQL server, to set the session values of the sql_safe_updates, sql_select_limit, and max_join_size system variables:

```
SET sql_safe_updates=1, sql_select_limit=1000, max_join_size=1000000;
```

The SET statement affects statement processing as follows:

- ? Enabling sql_safe_updates causes UPDATE and DELETE statements to produce an error if they do not specify a key constraint in the WHERE clause, or provide a LIMIT clause, or both. For example:

```
UPDATE tbl_name SET not_key_column=val WHERE key_column=val;
```

```
UPDATE tbl_name SET not_key_column=val LIMIT 1;
```

- ? Setting sql_select_limit to 1,000 causes the server to limit all SELECT result sets to 1,000 rows unless the statement includes a LIMIT clause.
- ? Setting max_join_size to 1,000,000 causes multiple-table SELECT statements to produce an error if the server estimates it must examine more than 1,000,000 row combinations.

To specify result set limits different from 1,000 and 1,000,000, you can override the defaults by using the --select-limit and --max-join-size options when you invoke mysql:

```
mysql --safe-updates --select-limit=500 --max-join-size=10000
```

It is possible for UPDATE and DELETE statements to produce an error in safe-updates mode even with a key specified in the WHERE clause, if the optimizer decides not to use the index on the key column:

- ? Range access on the index cannot be used if memory usage exceeds that permitted by the range_optimizer_max_mem_size system variable. The optimizer then falls back to a table scan. See the section called ?Limiting Memory Use for Range Optimization?.
- ? If key comparisons require type conversion, the index may not be used (see Section 10.3.1, ?How MySQL Uses Indexes?). Suppose that an indexed string column c1 is compared to a numeric value using WHERE c1 = 2222. For such comparisons, the string value is converted to a number and the operands are compared numerically (see

Section 14.3, "Type Conversion in Expression Evaluation"), preventing use of the index.

If safe-updates mode is enabled, an error occurs.

These behaviors are included in safe-updates mode:

- ? EXPLAIN with UPDATE and DELETE statements does not produce safe-updates errors. This enables use of EXPLAIN plus SHOW WARNINGS to see why an index is not used, which can be helpful in cases such as when a range_optimizer_max_mem_size violation or type conversion occurs and the optimizer does not use an index even though a key column was specified in the WHERE clause.
- ? When a safe-updates error occurs, the error message includes the first diagnostic that was produced, to provide information about the reason for failure. For example, the message may indicate that the range_optimizer_max_mem_size value was exceeded or type conversion occurred, either of which can preclude use of an index.
- ? For multiple-table deletes and updates, an error is produced with safe updates enabled only if any target table uses a table scan.

Disabling mysql Auto-Reconnect

If the mysql client loses its connection to the server while sending a statement, it immediately and automatically tries to reconnect once to the server and send the statement again. However, even if mysql succeeds in reconnecting, your first connection has ended and all your previous session objects and settings are lost: temporary tables, the autocommit mode, and user-defined and session variables. Also, any current transaction rolls back. This behavior may be dangerous for you, as in the following example where the server was shut down and restarted between the first and second statements without you knowing it:

```
mysql> SET @a=1;
Query OK, 0 rows affected (0.05 sec)
mysql> INSERT INTO t VALUES(@a);
ERROR 2006: MySQL server has gone away
No connection. Trying to reconnect...
Connection id: 1
Current database: test
Query OK, 1 row affected (1.30 sec)
mysql> SELECT * FROM t;
+-----+
| a |
```

```
+-----+
```

```
| NULL |
```

```
+-----+
```

```
1 row in set (0.05 sec)
```

The @a user variable has been lost with the connection, and after the reconnection it is undefined. If it is important to have mysql terminate with an error if the connection has been lost, you can start the mysql client with the --skip-reconnect option.

For more information about auto-reconnect and its effect on state information when a reconnection occurs, see Automatic Reconnection Control[5]. mysql Client Parser Versus Server Parser

The mysql client uses a parser on the client side that is not a duplicate of the complete parser used by the mysqld server on the server side. This can lead to differences in treatment of certain constructs. Examples:

? The server parser treats strings delimited by " characters as identifiers rather than as plain strings if the ANSI_QUOTES SQL mode is enabled.

The mysql client parser does not take the ANSI_QUOTES SQL mode into account. It treats strings delimited by ", ', and ` characters the same, regardless of whether ANSI_QUOTES is enabled.

? Within /*! ... */ and /*+ ... */ comments, the mysql client parser interprets short-form mysql commands. The server parser does not interpret them because these commands have no meaning on the server side.

If it is desirable for mysql not to interpret short-form commands within comments, a partial workaround is to use the --binary-mode option, which causes all mysql commands to be disabled except \C and \d in noninteractive mode (for input piped to mysql or loaded using the source command).

COPYRIGHT

Copyright ? 1997, 2026, Oracle and/or its affiliates.

This documentation is free software; you can redistribute it and/or modify it only under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 of the License.

This documentation is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with the program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA or see <http://www.gnu.org/licenses/>.

NOTES

1. MySQL Shell 8.4

<https://dev.mysql.com/doc/mysql-shell/8.4/en/>

2. C API Basic Data Structures

<https://dev.mysql.com/doc/c-api/8.4/en/c-api-data-structures.html>

3. Multiple Statement Execution Support

<https://dev.mysql.com/doc/c-api/8.4/en/c-api-multiple-queries.html>

4. `mysql_change_user()`

<https://dev.mysql.com/doc/c-api/8.4/en/mysql-change-user.html>

5. Automatic Reconnection Control

<https://dev.mysql.com/doc/c-api/8.4/en/c-api-auto-reconnect.html>

SEE ALSO

For more information, please refer to the MySQL Reference Manual, which may already be installed locally and which is also available online at <http://dev.mysql.com/doc/>.

AUTHOR

Oracle Corporation (<http://dev.mysql.com/>).

MySQL 8.4

03/23/2026

MYSQL(1)