



Linux Ubuntu 26.04 Manual Pages on command 'powerprofilesctl.1'

\$ man powerprofilesctl.1

POWERPROFILESCTL(1) Power Profiles Daemon Control Program POWERPROFILESCTL(1)

NAME

powerprofilesctl - Command line utility to control Power Profiles Daemon

SYNOPSIS

powerprofilesctl [-h] {list,list-holds,list-actions,get,set,configure-action,configure-bat?
tery-aware,query-battery-aware,launch,version} ...

POSITIONAL ARGUMENTS

powerprofilesctl list

List available power profiles

usage: powerprofilesctl list [-h]

powerprofilesctl list-holds

List current power profile holds

usage: powerprofilesctl list-holds [-h]

powerprofilesctl list-actions

List available power profile actions

usage: powerprofilesctl list-actions [-h]

powerprofilesctl get

Print the currently active power profile

usage: powerprofilesctl get [-h]

powerprofilesctl set

Set the currently active power profile

usage: powerprofilesctl set [-h] {}

arguments:

{ } Profile to use for set command

powerprofilesctl configure-action

Configure the action to be taken for the profile

usage: powerprofilesctl configure-action [-h] [--enable] [--disable] action

arguments:

action action to change for configure-action

options:

--enable

enable action

--disable

disable action

powerprofilesctl configure-battery-aware

Turn on or off dynamic changes from battery level or power adapter

usage: powerprofilesctl configure-battery-aware [-h] [--enable] [--disable]

options:

--enable

enable battery aware

--disable

disable battery aware

powerprofilesctl query-battery-aware

Query if dynamic changes from battery level or power adapter are enabled

usage: powerprofilesctl query-battery-aware [-h]

powerprofilesctl launch

Launch a command while holding a power profile

usage: powerprofilesctl launch [-h] [--profile PROFILE] [--reason REASON]

[--appid APPID]

[arguments ...]

Launch the command while holding a power profile, either performance, or power-saver. By default,

the profile hold is for the performance profile, but it might not be available on all

systems. See the list command for a list of available profiles.

arguments:

arguments

Command to launch

options:

--profile PROFILE, -p PROFILE

Profile to use for launch command

--reason REASON, -r REASON

Reason to use for launch command

--appid APPID, -i APPID

AppId to use for launch command

powerprofilesctl version

Print version information and exit

usage: powerprofilesctl version [-h]

COMMENTS

Use ?powerprofilesctl COMMAND --help? to get detailed help for individual commands

AUTHOR

Bastien Nocera

Mario Limonciello

DISTRIBUTION

The latest version of power-profiles-daemon may be downloaded from <https://gitlab.freedesktop.org/upower/power-profiles-daemon>

power-profiles-daemon 0.30

2025-11-05

POWERPROFILESCTL(1)