



Linux Ubuntu 26.04 Manual Pages on command 'pthread_cleanup_pop.3'

\$ man pthread_cleanup_pop.3

pthread_cleanup_push(3) Library Functions Manual pthread_cleanup_push(3)

NAME

pthread_cleanup_push, pthread_cleanup_pop - push and pop thread cancelation clean-up handlers

LIBRARY

POSIX threads library (libpthread, -lpthread)

SYNOPSIS

```
#include <pthread.h>

void pthread_cleanup_push(typeof(void (*)(void *)) *routine, void *arg);

void pthread_cleanup_pop(int execute);
```

DESCRIPTION

These functions manipulate the calling thread's stack of thread-cancelation clean-up handlers. A clean-up handler is a function that is automatically executed when a thread is canceled (or in various other circumstances described below); it might, for example, unlock a mutex so that it becomes available to other threads in the process.

The pthread_cleanup_push() function pushes routine onto the top of the stack of clean-up handlers. When routine is later invoked, it will be given arg as its argument.

The pthread_cleanup_pop() function removes the routine at the top of the stack of clean-up handlers, and optionally executes it if execute is nonzero.

A cancelation clean-up handler is popped from the stack and executed in the following circumstances:

? When a thread is canceled, all of the stacked clean-up handlers are popped and executed in the reverse of the order in which they were pushed onto the stack.

? When a thread calls `pthread_cleanup_pop()` with a nonzero execute argument, the top-most clean-up handler is popped and executed.

Calling `longjmp(3)` (`siglongjmp(3)`) produces undefined results if any call has been made to `pthread_cleanup_push()` or `pthread_cleanup_pop()` without the matching call of the pair since the jump buffer was filled by `setjmp(3)` (`sigsetjmp(3)`). Likewise, calling `longjmp(3)` (`siglongjmp(3)`) from inside a clean-up handler produces undefined results unless the jump buffer was also filled by `setjmp(3)` (`sigsetjmp(3)`) inside the handler.

These functions do not return a value.

There are no errors.

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

? Interface		? Attribute		? Value		?
-------------	--	-------------	--	---------	--	---

[illegible]

? pthread_cleanup_push(), pthread_cleanup_pop()

[illegible]

On glibc, the `pthread_cleanup_push()` and `pthread_cleanup_pop()` functions are implemented as macros that expand to text containing '{' and '}', respectively. This means that variables declared within the scope of paired calls to these functions will be visible within only that scope.

applications should avoid doing this.

STANDARDS

POSIX.1-2008.

HISTORY

POSIX.1-2001. glibc 2.0.

EXAMPLES

The program below provides a simple example of the use of the functions described in this page. The program creates a thread that executes a loop bracketed by `pthread_cleanup_push()` and `pthread_cleanup_pop()`. This loop increments a global variable, `cnt`, once each second. Depending on what command-line arguments are supplied, the main thread sends the other thread a cancelation request, or sets a global variable that causes the other thread to exit its loop and terminate normally (by doing a `return`).

In the following shell session, the main thread sends a cancelation request to the other thread:

```
$ ./a.out;  
New thread started  
cnt = 0  
cnt = 1  
Canceling thread  
Called clean-up handler  
Thread was canceled; cnt = 0
```

From the above, we see that the thread was canceled, and that the cancelation clean-up handler was called and it reset the value of the global variable `cnt` to 0.

In the next run, the main program sets a global variable that causes other thread to terminate normally:

```
$ ./a.out x;  
New thread started  
cnt = 0  
cnt = 1  
Thread terminated normally; cnt = 2
```

From the above, we see that the clean-up handler was not executed (because `cleanup_pop_arg` was 0), and therefore the value of `cnt` was not reset.

In the next run, the main program sets a global variable that causes the other thread to

terminate normally, and supplies a nonzero value for cleanup_pop_arg:

```
$ ./a.out x 1;
```

```
New thread started
```

```
cnt = 0
```

```
cnt = 1
```

```
Called clean-up handler
```

```
Thread terminated normally; cnt = 0
```

In the above, we see that although the thread was not canceled, the clean-up handler was executed, because the argument given to pthread_cleanup_pop() was nonzero.

Program source

```
#include <err.h>
#include <errno.h>
#include <pthread.h>
#include <stdio.h>
#include <stdlib.h>
#include <sys/types.h>
#include <unistd.h>

static int done = 0;
static int cleanup_pop_arg = 0;
static int cnt = 0;
static void
cleanup_handler(void *arg)
{
    printf("Called clean-up handler\n");
    cnt = 0;
}

static void *
thread_start(void *arg)
{
    time_t curr;
    printf("New thread started\n");
    pthread_cleanup_push(cleanup_handler, NULL);
    curr = time(NULL);
```

```

while (!done) {
    pthread_testcancel();      /* A cancelation point */
    if (curr < time(NULL)) {
        curr = time(NULL);
        printf("cnt = %d\n", cnt); /* A cancelation point */
        cnt++;
    }
}

pthread_cleanup_pop(cleanup_pop_arg);
return NULL;
}

int
main(int argc, char *argv[])
{
    pthread_t thr;
    int s;
    void *res;
    s = pthread_create(&thr, NULL, thread_start, NULL);
    if (s != 0)
        errc(EXIT_FAILURE, s, "pthread_create");
    sleep(2);      /* Allow new thread to run a while */
    if (argc > 1) {
        if (argc > 2)
            cleanup_pop_arg = atoi(argv[2]);
        done = 1;
    } else {
        printf("Canceling thread\n");
        s = pthread_cancel(thr);
        if (s != 0)
            errc(EXIT_FAILURE, s, "pthread_cancel");
    }
    s = pthread_join(thr, &res);
    if (s != 0)

```

```
    errc(EXIT_FAILURE, s, "pthread_join");  
if (res == PTHREAD_CANCELED)  
    printf("Thread was canceled; cnt = %d\n", cnt);  
else  
    printf("Thread terminated normally; cnt = %d\n", cnt);  
exit(EXIT_SUCCESS);  
}
```

SEE ALSO

pthread_cancel(3), pthread_cleanup_push_defer_np(3), pthread_setcancelstate(3),
pthread_testcancel(3), pthreads(7)

Linux man-pages 6.17

2025-08-20

pthread_cleanup_push(3)