



Linux Ubuntu 26.04 Manual Pages on command 'pthread_spin_trylock.3'

\$ man pthread_spin_trylock.3

pthread_spin_lock(3) Library Functions Manual pthread_spin_lock(3)

NAME

pthread_spin_lock, pthread_spin_trylock, pthread_spin_unlock - lock and unlock a spin lock

LIBRARY

POSIX threads library (libpthread, -lpthread)

SYNOPSIS

```
#include <pthread.h>

int pthread_spin_lock(pthread_spinlock_t *lock);

int pthread_spin_trylock(pthread_spinlock_t *lock);

int pthread_spin_unlock(pthread_spinlock_t *lock);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
pthread_spin_lock(), pthread_spin_trylock():

    _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

The `pthread_spin_lock()` function locks the spin lock referred to by `lock`. If the spin lock is currently unlocked, the calling thread acquires the lock immediately. If the spin lock is currently locked by another thread, the calling thread spins, testing the lock until it becomes available, at which point the calling thread acquires the lock.

Calling `pthread_spin_lock()` on a lock that is already held by the caller or a lock that has not been initialized with `pthread_spin_init(3)` results in undefined behavior.

The `pthread_spin_trylock()` function is like `pthread_spin_lock()`, except that if the spin lock referred to by `lock` is currently locked, then, instead of spinning, the call returns immediately with the error `EBUSY`.

The `pthread_spin_unlock()` function unlocks the spin lock referred to `lock`. If any threads are spinning on the lock, one of those threads will then acquire the lock.

Calling `pthread_spin_unlock()` on a lock that is not held by the caller results in undefined behavior.

RETURN VALUE

On success, these functions return zero. On failure, they return an error number.

ERRORS

`pthread_spin_lock()` may fail with the following errors:

EDEADLOCK

The system detected a deadlock condition.

`pthread_spin_trylock()` fails with the following errors:

EBUSY The spin lock is currently locked by another thread.

STANDARDS

POSIX.1-2008.

HISTORY

glibc 2.2. POSIX.1-2001.

CAVEATS

Applying any of the functions described on this page to an uninitialized spin lock results in undefined behavior.

Carefully read NOTES in `pthread_spin_init(3)`.

SEE ALSO

`pthread_spin_destroy(3)`, `pthread_spin_init(3)`, `pthread(7)`

Linux man-pages 6.17

2026-02-08

`pthread_spin_lock(3)`