



## ***Linux Ubuntu 26.04 Manual Pages on command 'pw-profiler.1'***

***\$ man pw-profiler.1***

pw-profiler(1)

General Commands Manual

pw-profiler(1)

### NAME

pw-profiler - The PipeWire profiler

### SYNOPSIS

pw-profiler [options]

### DESCRIPTION

Start profiling a PipeWire instance.

If the server has the profiler module loaded, this program will connect to it and log the profiler data. Profiler data contains times and durations when processing nodes and devices started and completed.

When this program is stopped, a set of gnuplot files and a script to generate SVG files from the .plot files is generated, along with a .html file to visualize the profiling results in a browser.

This function uses the same data used by pw-top.

### OPTIONS

-r | --remote=NAME

The name the remote instance to monitor. If left unspecified, a connection is made to the default PipeWire instance.

-h | --help

Show help.

--version

Show version information.

-o | --output=FILE

Profiler output name (default "profiler.log").

#### AUTHORS

The PipeWire Developers <<https://gitlab.freedesktop.org/pipewire/pipewire/issues>>; PipeWire  
is available from <<https://pipewire.org>>

#### SEE ALSO

pipewire(1), pw-top(1)

|          |       |                |
|----------|-------|----------------|
| PipeWire | 1.6.2 | pw-profiler(1) |
|----------|-------|----------------|