



Linux Ubuntu 26.04 Manual Pages on command 'restic-features.1'

\$ man restic-features.1

restic backup(1) restic backup(1)

NAME

restic-features - Print list of feature flags

SYNOPSIS

restic features [flags]

DESCRIPTION

The "features" command prints a list of supported feature flags.

To pass feature flags to restic, set the RESTIC_FEATURES environment variable to "featureA=true,featureB=false". Specifying an unknown feature flag is an error.

A feature can either be in alpha, beta, stable or deprecated state. An alpha feature is disabled by default and may change in arbitrary ways between restic versions or be removed.

A beta feature is enabled by default, but still can change in minor ways or be removed. A stable feature is always enabled and cannot be disabled. The flag will be removed in a future restic version. A deprecated feature is always disabled and cannot be enabled. The flag will be removed in a future restic version.

EXIT STATUS

Exit status is 0 if the command was successful. Exit status is 1 if there was any error.

OPTIONS

-h, --help[=false] help for features

OPTIONS INHERITED FROM PARENT COMMANDS

--cacert=[] file to load root certificates from (default: use system certificates or \$RESTIC_CACERT)

--cache-dir="" set the cache directory. (default: use system default cache directory)

`--cleanup-cache[=false]` auto remove old cache directories
`--compression=auto` compression mode (only available for repository format version 2), one of (auto|off|max) (default: `$RESTIC_COMPRESSION`)
`--http-user-agent=""` set a http user agent for outgoing http requests
`--insecure-no-password[=false]` use an empty password for the repository, must be passed to every restic command (insecure)
`--insecure-tls[=false]` skip TLS certificate verification when connecting to the repository (insecure)
`--json[=false]` set output mode to JSON for commands that support it
`--key-hint=""` key ID of key to try decrypting first (default: `$RESTIC_KEY_HINT`)
`--limit-download=0` limits downloads to a maximum rate in KiB/s. (default: unlimited)
`--limit-upload=0` limits uploads to a maximum rate in KiB/s. (default: unlimited)
`--no-cache[=false]` do not use a local cache
`--no-extra-verify[=false]` skip additional verification of data before upload (see documentation)
`--no-lock[=false]` do not lock the repository, this allows some operations on read-only repositories
`-o, --option=[]` set extended option (key=value, can be specified multiple times)
`--pack-size=0` set target pack size in MiB, created pack files may be larger (default: `$RESTIC_PACK_SIZE`)
`--password-command=""` shell command to obtain the repository password from (default: `$RESTIC_PASSWORD_COMMAND`)
`-p, --password-file=""` file to read the repository password from (default: `$RESTIC_PASSWORD_FILE`)
`-q, --quiet[=false]` do not output comprehensive progress report
`-r, --repo=""` repository to backup to or restore from (default: `$RESTIC_REPOSITORY`)
`--repository-file=""` file to read the repository location from (default: `$RESTIC_REPOSITORY_FILE`)
`--retry-lock=0s` retry to lock the repository if it is already locked, takes a value like 5m or 2h (default: no retries)
`--stuck-request-timeout=5m0s` duration after which to retry stuck requests
`--tls-client-cert=""` path to a file containing PEM encoded TLS client certificate and private key (default: `$RESTIC_TLS_CLIENT_CERT`)

-v, --verbose[=0] be verbose (specify multiple times or a level using --verbose=n``,
max level/times is 2)

SEE ALSO

restic(1)

generated by restic generate

Jan 2017

restic backup(1)