



Linux Ubuntu 26.04 Manual Pages on command 'restic-generate.1'

\$ man restic-generate.1

restic backup(1) restic backup(1)

NAME

restic-generate - Generate manual pages and auto-completion files (bash, fish, zsh, power?
shell)

SYNOPSIS

restic generate [flags]

DESCRIPTION

The "generate" command writes automatically generated files (like the man pages and the auto-completion files for bash, fish and zsh).

EXIT STATUS

Exit status is 0 if the command was successful. Exit status is 1 if there was any error.

OPTIONS

--bash-completion="" write bash completion file (- for stdout)
--fish-completion="" write fish completion file (- for stdout)
-h, --help[=false] help for generate
--man="" write man pages to directory
--powershell-completion="" write powershell completion file (- for stdout)
--zsh-completion="" write zsh completion file (- for stdout)

OPTIONS INHERITED FROM PARENT COMMANDS

--cacert=[] file to load root certificates from (default: use system certificates or \$RESTIC_CACERT)
--cache-dir="" set the cache directory. (default: use system default cache directory)
--cleanup-cache[=false] auto remove old cache directories

--compression=auto compression mode (only available for repository format version 2), one of (auto|off|max) (default: \$RESTIC_COMPRESSION)

--http-user-agent="" set a http user agent for outgoing http requests

--insecure-no-password[=false] use an empty password for the repository, must be passed to every restic command (insecure)

--insecure-tls[=false] skip TLS certificate verification when connecting to the repository (insecure)

--json[=false] set output mode to JSON for commands that support it

--key-hint="" key ID of key to try decrypting first (default: \$RESTIC_KEY_HINT)

--limit-download=0 limits downloads to a maximum rate in KiB/s. (default: unlimited)

--limit-upload=0 limits uploads to a maximum rate in KiB/s. (default: unlimited)

--no-cache[=false] do not use a local cache

--no-extra-verify[=false] skip additional verification of data before upload (see documentation)

--no-lock[=false] do not lock the repository, this allows some operations on read-only repositories

-o, --option=[] set extended option (key=value, can be specified multiple times)

--pack-size=0 set target pack size in MiB, created pack files may be larger (default: \$RESTIC_PACK_SIZE)

--password-command="" shell command to obtain the repository password from (default: \$RESTIC_PASSWORD_COMMAND)

-p, --password-file="" file to read the repository password from (default: \$RESTIC_PASSWORD_FILE)

-q, --quiet[=false] do not output comprehensive progress report

-r, --repo="" repository to backup to or restore from (default: \$RESTIC_REPOSITORY)

--repository-file="" file to read the repository location from (default: \$RESTIC_REPOSITORY_FILE)

--retry-lock=0s retry to lock the repository if it is already locked, takes a value like 5m or 2h (default: no retries)

--stuck-request-timeout=5m0s duration after which to retry stuck requests

--tls-client-cert="" path to a file containing PEM encoded TLS client certificate and private key (default: \$RESTIC_TLS_CLIENT_CERT)

-v, --verbose[=0] be verbose (specify multiple times or a level using --verbose=n,`

max level/times is 2)

SEE ALSO

restic(1)

generated by restic generate

Jan 2017

restic backup(1)