



Linux Ubuntu 26.04 Manual Pages on command 'round.3'

\$ man round.3

round(3) Library Functions Manual round(3)

NAME

round, roundf, roundl - round to nearest integer, away from zero

LIBRARY

Math library (libm, -lm)

SYNOPSIS

```
#include <math.h>
```

```
double round(double x);
```

```
float roundf(float x);
```

```
long double roundl(long double x);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
round(), roundf(), roundl():
```

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

These functions round *x* to the nearest integer, but round halfway cases away from zero (regardless of the current rounding direction, see [fenv\(3\)](#)), instead of to the nearest even integer like [rint\(3\)](#).

For example, `round(0.5)` is 1.0, and `round(-0.5)` is -1.0.

RETURN VALUE

These functions return the rounded integer value.

If *x* is integral, +0, -0, NaN, or infinite, *x* itself is returned.

ERRORS

No errors occur.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

?	Interface	?	Attribute	?	Value	?
---	-----------	---	-----------	---	-------	---

[illegible]

? round(), roundf(), roundl() ? Thread safety ? MT-Safe ?

[illegible]

STANDARDS

C11, POSIX.1-2008.

HISTORY

glibc 2.1. C99, POSIX.1-2001.

POSIX.1-2001 contains text about overflow (which might set `errno` to `ERANGE`, or raise an `FE_OVERFLOW` exception). In practice, the result cannot overflow on any current machine, so this error-handling stuff was just nonsense. (More precisely, overflow can happen only when the maximum value of the exponent is smaller than the number of mantissa bits. For the IEEE-754 standard 32-bit and 64-bit floating-point numbers the maximum value of the exponent is 127 (respectively, 1023), and the number of mantissa bits including the implicit bit is 24 (respectively, 53).) This was removed in POSIX.1-2008.

If you want to store the rounded value in an integer type, you probably want to use `one` of the functions described in `lround(3)` instead.

SEE ALSO

ceil(3), floor(3), lround(3), nearbyint(3), rint(3), trunc(3)

Linux man-pages 6.17

2026-02-08

round(3)