



Linux Ubuntu 26.04 Manual Pages on command 'runcon.1'

\$ man runcon.1

RUNCON(1)

General Commands Manual

RUNCON(1)

NAME

runcon - Run command with specified security context under SELinux enabled systems.

SYNOPSIS

```
runcon [-c|--compute] [-u|--user] [-r|--role] [-t|--type] [-l|--range] [-h|--help]
[-V|--version] [ARG]
```

DESCRIPTION

Run command with specified security context under SELinux enabled systems.

OPTIONS

-c, --compute

Compute process transition context before modifying.

-u, --user <USER>

Set user USER in the target security context.

-r, --role <ROLE>

Set role ROLE in the target security context.

-t, --type <TYPE>

Set type TYPE in the target security context.

-l, --range <RANGE>

Set range RANGE in the target security context.

-h, --help

Print help

-V, --version

Print version

[ARG]

EXTRA

Run COMMAND with completely-specified CONTEXT, or with current or transitioned security context modified by one or more of LEVEL, ROLE, TYPE, and USER.

If none of --compute, --type, --user, --role or --range is specified, then the first argument is used as the complete context.

Note that only carefully-chosen contexts are likely to successfully run.

If neither CONTEXT nor COMMAND is specified, the current security context is printed.

VERSION

v(utils coreutils) 0.8.0

2026-04-16

RUNCON(1)