



Linux Ubuntu 26.04 Manual Pages on command 'rust-base32.1'

\$ man rust-base32.1

BASE32(1) General Commands Manual BASE32(1)

NAME

base32 - encode/decode data and print to standard output With no FILE, or when FILE is -, read standard input.

The data are encoded as described for the base32 alphabet in RFC 4648. When decoding, the input may contain newlines in addition to the bytes of the formal base32 alphabet. Use --ig?nore-garbage to attempt to recover from any other non-alphabet bytes in the encoded stream.

SYNOPSIS

base32 [-d|--decode] [-i|--ignore-garbage] [-w|--wrap] [-h|--help] [-V|--version] [file]

DESCRIPTION

encode/decode data and print to standard output With no FILE, or when FILE is -, read standard input.

The data are encoded as described for the base32 alphabet in RFC 4648. When decoding, the input may contain newlines in addition to the bytes of the formal base32 alphabet. Use --ig?nore-garbage to attempt to recover from any other non-alphabet bytes in the encoded stream.

OPTIONS

-d, --decode

decode data

-i, --ignore-garbage

when decoding, ignore non-alphabetic characters

-w, --wrap <COLS>

wrap encoded lines after COLS character (default 76, 0 to disable wrapping)

-h, --help

Print help

-V, --version

Print version

[file]

VERSION

v(utils coreutils) 0.8.0

2026-04-16

BASE32(1)