



## ***Linux Ubuntu 26.04 Manual Pages on command 'rust-chgrp.1'***

***\$ man rust-chgrp.1***

CHGRP(1)

General Commands Manual

CHGRP(1)

NAME

chgrp - Change the group of each FILE to GROUP.

SYNOPSIS

chgrp [--help] [-c|--changes] [-f|--silent] [--quiet] [-v|--verbose] [--preserve-root]  
[--no-preserve-root] [--reference] [--from] [-R|--recursive] [-H ] [-L ] [-P ] [--derefer?  
ence] [-h|--no-dereference] [-V|--version]

DESCRIPTION

Change the group of each FILE to GROUP.

OPTIONS

--help Print help information.

-c, --changes

like verbose but report only when a change is made

-f, --silent

--quiet

suppress most error messages

-v, --verbose

output a diagnostic for every file processed

--preserve-root

fail to operate recursively on '/'

--no-preserve-root

do not treat '/' specially (the default)

--reference <RFILE>

use RFILE's group rather than specifying GROUP values

--from <GROUP>

change the group only if its current group matches GROUP

-R, --recursive

operate on files and directories recursively

-H if a command line argument is a symbolic link to a directory, traverse it

-L traverse every symbolic link to a directory encountered

-P do not traverse any symbolic links (default)

--dereference

affect the referent of each symbolic link (this is the default), rather than the sym?

bolic link itself

-h, --no-dereference

affect symbolic links instead of any referenced file (useful only on systems that can

change the ownership of a symlink)

-V, --version

Print version

VERSION

v(utils coreutils) 0.8.0

2026-04-16

CHGRP(1)