



Linux Ubuntu 26.04 Manual Pages on command 'rust-mktemp.1'

\$ man rust-mktemp.1

MKTEMP(1)

General Commands Manual

MKTEMP(1)

NAME

mktemp - Create a temporary file or directory.

SYNOPSIS

mktemp [-d|--directory] [-u|--dry-run] [-q|--quiet] [--suffix] [-p] [--tmpdir] [-t]
[-h|--help] [-V|--version] [template]

DESCRIPTION

Create a temporary file or directory.

OPTIONS

-d, --directory

Make a directory instead of a file

-u, --dry-run

do not create anything; merely print a name (unsafe)

-q, --quiet

Fail silently if an error occurs.

--suffix <SUFFIX>

append SUFFIX to TEMPLATE; SUFFIX must not contain a path separator. This option is implied if TEMPLATE does not end with X.

-p <DIR>

short form of --tmpdir

--tmpdir[=<DIR>]

interpret TEMPLATE relative to DIR; if DIR is not specified, use \$TMPDIR (\$TMP on windows) if set, else /tmp. With this option, TEMPLATE must not be an absolute name;

unlike with -t, TEMPLATE may contain slashes, but mktemp creates only the final component

-t Generate a template (using the supplied prefix and TMPDIR (TMP on windows) if set) to create a filename template [deprecated]

-h, --help

Print help

-V, --version

Print version

[template]

VERSION

v(utils coreutils) 0.8.0

2026-04-16

MKTEMP(1)