



Linux Ubuntu 26.04 Manual Pages on command 'sem_timedwait.3'

\$ man sem_timedwait.3

sem_wait(3) Library Functions Manual sem_wait(3)

NAME

sem_wait, sem_timedwait, sem_trywait - lock a semaphore

LIBRARY

POSIX threads library (libpthread, -lpthread)

SYNOPSIS

```
#include <semaphore.h>

int sem_wait(sem_t *sem);

int sem_trywait(sem_t *sem);

int sem_timedwait(sem_t *restrict sem,
                  const struct timespec *restrict abs_timeout);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
sem_timedwait():
    _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

sem_wait() decrements (locks) the semaphore pointed to by sem. If the semaphore's value is greater than zero, then the decrement proceeds, and the function returns, immediately. If the semaphore currently has the value zero, then the call blocks until either it becomes possible to perform the decrement (i.e., the semaphore value rises above zero), or a signal handler interrupts the call.

sem_trywait() is the same as sem_wait(), except that if the decrement cannot be immediately performed, then call returns an error (errno set to EAGAIN) instead of blocking.

sem_timedwait() is the same as sem_wait(), except that abs_timeout specifies a limit on the

The `abs_timeout` argument points to a `timespec(3)` structure that specifies an absolute time out in seconds and nanoseconds since the Epoch, 1970-01-01 00:00:00 +0000 (UTC).

If the operation can be performed immediately, then `sem_timedwait()` never fails with a timeout error, regardless of the value of `abs_timeout`. Furthermore, the validity of `abs_timeout` is not checked in this case.

All of these functions return 0 on success; on error, the value of the semaphore is left unchanged, -1 is returned, and `errno` is set to indicate the error.

EAGAIN (sem_trywait()) The operation could not be performed without blocking (i.e., the semaphore currently has the value zero).

EINVAL sem is not a valid semaphore.

ETIMEDOUT

ATTRIBUTES

[illegible][illegible][illegible]

POSIX.1-2008.

POSIX.1-2001.

Page 2/5

The (somewhat trivial) program shown below operates on an unnamed semaphore. The program expects two command-line arguments. The first argument specifies a seconds value that is used to set an alarm timer to generate a SIGALRM signal. This handler performs a `sem_post(3)` to increment the semaphore that is being waited on in `main()` using `sem_timedwait()`. The second command-line argument specifies the length of the timeout, in seconds, for `sem_timedwait()`. The following shows what happens on two different runs of the program:

```
$ ./a.out 2 3
```

```
About to call sem_timedwait()
```

```
sem_post() from handler
```

```
sem_timedwait() succeeded
```

```
$ ./a.out 2 1
```

```
About to call sem_timedwait()
```

```
sem_timedwait() timed out
```

Program source

```
#include <err.h>
#include <errno.h>
#include <semaphore.h>
#include <signal.h>
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
#include <unistd.h>
#include <assert.h>

sem_t sem;

static void
handler(int sig)
{
    write(STDOUT_FILENO, "sem_post() from handler\n", 24);
    if (sem_post(&sem) == -1) {
        write(STDERR_FILENO, "sem_post() failed\n", 18);
        _exit(EXIT_FAILURE);
    }
}
```

```

int
main(int argc, char *argv[])
{
    struct sigaction sa;

    struct timespec ts;

    int s;

    if (argc != 3) {
        fprintf(stderr, "Usage: %s <alarm-secs> <wait-secs>\n",
            argv[0]);
        exit(EXIT_FAILURE);
    }

    if (sem_init(&sem, 0, 0) == -1)
        err(EXIT_FAILURE, "sem_init");

    /* Establish SIGALRM handler; set alarm timer using argv[1]. */
    sa.sa_handler = handler;
    sigemptyset(&sa.sa_mask);
    sa.sa_flags = 0;

    if (sigaction(SIGALRM, &sa, NULL) == -1)
        err(EXIT_FAILURE, "sigaction");

    alarm(atoi(argv[1]));

    /* Calculate relative interval as current time plus
       number of seconds given argv[2]. */
    if (clock_gettime(CLOCK_REALTIME, &ts) == -1)
        err(EXIT_FAILURE, "clock_gettime");

    ts.tv_sec += atoi(argv[2]);

    printf("%s() about to call sem_timedwait()\n", __func__);

    while ((s = sem_timedwait(&sem, &ts)) == -1 && errno == EINTR)
        continue;    /* Restart if interrupted by handler. */

    /* Check what happened. */

    if (s == -1) {
        if (errno == ETIMEDOUT)
            printf("sem_timedwait() timed out\n");
        else

```

```
    perror("sem_timedwait");  
} else  
    printf("sem_timedwait() succeeded\n");  
exit((s == 0) ? EXIT_SUCCESS : EXIT_FAILURE);  
}
```

SEE ALSO

[clock_gettime\(2\)](#), [sem_getvalue\(3\)](#), [sem_post\(3\)](#), [timespec\(3\)](#), [sem_overview\(7\)](#), [time\(7\)](#)

Linux man-pages 6.17

2026-02-08

[sem_wait\(3\)](#)