



Linux Ubuntu 26.04 Manual Pages on command 'sigaltstack.2'

\$ man sigaltstack.2

sigaltstack(2) System Calls Manual sigaltstack(2)

NAME

sigaltstack - set and/or get signal stack context

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <signal.h>
```

```
int sigaltstack(const stack_t *_Nullable restrict ss,  
                stack_t *_Nullable restrict old_ss);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

sigaltstack():

```
_XOPEN_SOURCE >= 500
```

```
|| /* Since glibc 2.12: */ _POSIX_C_SOURCE >= 200809L
```

```
|| /* glibc <= 2.19: */ _BSD_SOURCE
```

DESCRIPTION

sigaltstack() allows a thread to define a new alternate signal stack and/or retrieve the state of an existing alternate signal stack. An alternate signal stack is used during the execution of a signal handler if the establishment of that handler (see sigaction(2)) requested it.

The normal sequence of events for using an alternate signal stack is the following:

1. Allocate an area of memory to be used for the alternate signal stack.
2. Use sigaltstack() to inform the system of the existence and location of the alternate signal stack.

3. When establishing a signal handler using `sigaction(2)`, inform the system that the signal handler should be executed on the alternate signal stack by specifying the `SA_ONSTACK` flag.

The `ss` argument is used to specify a new alternate signal stack, while the `old_ss` argument is used to retrieve information about the currently established signal stack. If we are interested in performing just one of these tasks, then the other argument can be specified as `NULL`.

The `stack_t` type used to type the arguments of this function is defined as follows:

```
typedef struct {  
    void *ss_sp; /* Base address of stack */  
    int ss_flags; /* Flags */  
    size_t ss_size; /* Number of bytes in stack */  
} stack_t;
```

To establish a new alternate signal stack, the fields of this structure are set as follows:

`ss.ss_flags`

This field contains either 0, or the following flag:

`SS_AUTODISARM` (since Linux 4.7)

Clear the alternate signal stack settings on entry to the signal handler.

When the signal handler returns, the previous alternate signal stack settings are restored.

This flag was added in order to make it safe to switch away from the signal handler with `swapcontext(3)`. Without this flag, a subsequently handled signal will corrupt the state of the switched-away signal handler. On kernels where this flag is not supported, `sigaltstack()` fails with the error `EINVAL` when this flag is supplied.

`ss.ss_sp`

This field specifies the starting address of the stack. When a signal handler is invoked on the alternate stack, the kernel automatically aligns the address given in `ss.ss_sp` to a suitable address boundary for the underlying hardware architecture.

`ss.ss_size`

This field specifies the size of the stack. The constant `SIGSTKSZ` is defined to be large enough to cover the usual size requirements for an alternate signal stack, and the constant `MINSIGSTKSZ` defines the minimum size required to execute a signal han?

dlr.

To disable an existing stack, specify `ss.ss_flags` as `SS_DISABLE`. In this case, the kernel ignores any other flags in `ss.ss_flags` and the remaining fields in `ss`.

If `old_ss` is not `NULL`, then it is used to return information about the alternate signal stack which was in effect prior to the call to `sigaltstack()`. The `old_ss.ss_sp` and `old_ss.ss_size` fields return the starting address and size of that stack. The `old_ss.ss_flags` may return either of the following values:

`SS_ONSTACK`

The thread is currently executing on the alternate signal stack. (Note that it is not possible to change the alternate signal stack if the thread is currently executing on it.)

`SS_DISABLE`

The alternate signal stack is currently disabled.

Alternatively, this value is returned if the thread is currently executing on an alternate signal stack that was established using the `SS_AUTODISARM` flag. In this case, it is safe to switch away from the signal handler with `swapcontext(3)`. It is also possible to set up a different alternative signal stack using a further call to `sigaltstack()`.

`SS_AUTODISARM`

The alternate signal stack has been marked to be autodisarmed as described above.

By specifying `ss` as `NULL`, and `old_ss` as a non-`NULL` value, one can obtain the current settings for the alternate signal stack without changing them.

RETURN VALUE

`sigaltstack()` returns 0 on success, or -1 on failure with `errno` set to indicate the error.

ERRORS

EFAULT Either `ss` or `old_ss` is not `NULL` and points to an area outside of the process's address space.

EINVAL `ss` is not `NULL` and the `ss_flags` field contains an invalid flag.

ENOMEM The specified size of the new alternate signal stack `ss.ss_size` was less than `MIN_SIGSTKSZ`.

EPERM An attempt was made to change the alternate signal stack while it was active (i.e., the thread was already executing on the current alternate signal stack).

ATTRIBUTES

[illegible]

SS AUTODISARM is a Linux extension.

POSIX.1-2001, SUSv2, SVr4.

The most common usage of an alternate signal stack is to handle the SIGSEGV signal that is generated if the space available for the standard stack is exhausted: in this case, a signal handler for SIGSEGV cannot be invoked on the standard stack; if we wish to handle it, we must use an alternate signal stack.

Establishing an alternate signal stack is useful if a thread expects that it may exhaust its standard stack. This may occur, for example, because the stack grows so large that it encounters the upwardly growing heap, or it reaches a limit established by a call to `setrlimit(RLIMIT_STACK, &rlim)`. If the standard stack is exhausted, the kernel sends the thread a `SIGSEGV` signal. In these circumstances the only way to catch this signal is on an alternate signal stack.

On most hardware architectures supported by Linux, stacks grow downward. `sigaltstack()` automatically takes account of the direction of stack growth.

Functions called from a signal handler executing on an alternate signal stack will also use the alternate signal stack. (This also applies to any handlers invoked for other signals while the thread is executing on the alternate signal stack.) Unlike the standard stack, the system does not automatically extend the alternate signal stack. Exceeding the allocated size of the alternate signal stack will lead to unpredictable results.

A successful call to `execve(2)` removes any existing alternate signal stack. A child process created via `fork(2)` inherits a copy of its parent's alternate signal stack settings. The same is also true for a child process created using `clone(2)`, unless the clone flags include

Page 4/6

established in the parent is disabled in the child process.

sigaltstack() supersedes the older sigstack() call. For backward compatibility, glibc also provides sigstack(). All new applications should be written using sigaltstack().

History

4.2BSD had a sigstack() system call. It used a slightly different struct, and had the major disadvantage that the caller had to know the direction of stack growth.

BUGS

In Linux 2.2 and earlier, the only flag that could be specified in `ss.sa_flags` was `SS_DISABLE`. In the lead up to the release of the Linux 2.4 kernel, a change was made to allow `sigaltstack()` to allow `ss.ss_flags==SS_ONSTACK` with the same meaning as `ss.ss_flags==0` (i.e., the inclusion of `SS_ONSTACK` in `ss.ss_flags` is a no-op). On other implementations, and according to POSIX.1, `SS_ONSTACK` appears only as a reported flag in `old_ss.ss_flags`. On Linux, there is no need ever to specify `SS_ONSTACK` in `ss.ss_flags`, and indeed doing so should be avoided on portability grounds: various other systems give an error if `SS_ONSTACK` is specified in `ss.ss_flags`.

EXAMPLES

The following code segment demonstrates the use of `sigaltstack()` (and `sigaction(2)`) to install an alternate signal stack that is employed by a handler for the `SIGSEGV` signal:

```
stack_t ss;

ss.ss_sp = malloc(SIGSTKSZ);

if (ss.ss_sp == NULL) {
    perror("malloc");
    exit(EXIT_FAILURE);
}

ss.ss_size = SIGSTKSZ;
ss.ss_flags = 0;

if (sigaltstack(&ss, NULL) == -1) {
    perror("sigaltstack");
    exit(EXIT_FAILURE);
}

sa.sa_flags = SA_ONSTACK;

sa.sa_handler = handler(); /* Address of a signal handler */

sigemptyset(&sa.sa_mask);
```

```
if (sigaction(SIGSEGV, &sa, NULL) == -1) {  
    perror("sigaction");  
    exit(EXIT_FAILURE);  
}
```

SEE ALSO

[execve\(2\)](#), [setrlimit\(2\)](#), [sigaction\(2\)](#), [siglongjmp\(3\)](#), [sigsetjmp\(3\)](#), [signal\(7\)](#)

Linux man-pages 6.17

2026-02-08

[sigaltstack\(2\)](#)