



Linux Ubuntu 26.04 Manual Pages on command 'stdio_ext.3'

\$ man stdio_ext.3

stdio_ext(3) Library Functions Manual stdio_ext(3)

NAME

__fbufsize, __flbf, __fpending, __fpurge, __freadable, __freading, __fsetlocking,
__fwritable, __fwriting, _flushlbf - interfaces to stdio FILE structure

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <stdio.h>

#include <stdio_ext.h>

size_t __fbufsize(FILE *stream);

size_t __fpending(FILE *stream);

int __flbf(FILE *stream);

int __freadable(FILE *stream);

int __fwritable(FILE *stream);

int __freading(FILE *stream);

int __fwriting(FILE *stream);

int __fsetlocking(FILE *stream, int type);

void _flushlbf(void);

void __fpurge(FILE *stream);
```

DESCRIPTION

Solaris introduced routines to allow portable access to the internals of the FILE structure, and glibc also implemented these.

The __fbufsize() function returns the size of the buffer currently used by the given stream.

The `__flbf()` function returns a nonzero value if the stream is line-buffered, and zero otherwise.

The `__freadable()` function returns a nonzero value if the stream allows reading, and zero otherwise.

The `__fwritable()` function returns a nonzero value if the stream allows writing, and zero otherwise.

The `__freading()` function returns a nonzero value if the stream is read-only, or if the last operation on the stream was a read operation, and zero otherwise.

The `__fwriting()` function returns a nonzero value if the stream is write-only (or append-only), or if the last operation on the stream was a write operation, and zero otherwise.

The `__fsetlocking()` function can be used to select the desired type of locking on the stream. It returns the current type. The type argument can take the following three values:

Perform implicit locking around every operation on the given stream (except for the *_unlocked ones). This is the default.

The caller will take care of the locking (possibly using flockfile(3) in case there is more than one thread), and the stdio routines will not do locking until the state is reset to FSETLOCKING_INTERNAL.

Don't change the type of locking. (Only return it.)

The `_flushlbf()` function flushes all line-buffered streams. (Presumably so that output to a terminal is forced out, say before reading keyboard input.)

The `fpurge()` function discards the contents of the stream's buffer.

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

? Interface	? Attribute	? Value	?
-------------	-------------	---------	---

Page 2/3

? __fbufsize(), __fpending(), __fpurge(), ? Thread safety ? MT-Safe race:stream ?

? __fsetlocking() ? ? ?

??

? __flbf(), __freadable(), __freading(), ? Thread safety ? MT-Safe ?

? __fwritable(), __fwriting(), _flushlbf() ? ? ?

??

SEE ALSO

flockfile(3), fpurge(3)

Linux man-pages 6.17

2026-02-08

stdio_ext(3)