



Linux Ubuntu 26.04 Manual Pages on command 'systemd-cgls.1'

\$ man systemd-cgls.1

SYSTEMD-CGLS(1) systemd-cgls SYSTEMD-CGLS(1)

NAME

systemd-cgls - Recursively show control group contents

SYNOPSIS

systemd-cgls [OPTIONS...] [CGROUP...]

systemd-cgls [OPTIONS...] --unit|--user-unit [UNIT...]

DESCRIPTION

systemd-cgls recursively shows the contents of the selected Linux control group hierarchy in a tree. If arguments are specified, shows all member processes of the specified control groups plus all their subgroups and their members. The control groups may either be specified by their full file paths or are assumed in the systemd control group hierarchy. If no argument is specified and the current working directory is beneath the control group mount point `/sys/fs/cgroup/`, shows the contents of the control group the working directory refers to. Otherwise, the full systemd control group hierarchy is shown.

By default, empty control groups are not shown.

OPTIONS

The following options are understood:

`--all`

Do not hide empty control groups in the output.

`-l, --full`

Do not ellipsize process tree members.

Added in version 198.

`-u, --unit`

Show cgroup subtrees for the specified units.

Added in version 233.

`--user-unit`

Show cgroup subtrees for the specified user units.

Added in version 233.

`-k`

Include kernel threads in output.

`-M MACHINE, --machine=MACHINE`

Limit control groups shown to the part corresponding to the container MACHINE.

Added in version 203.

`-x, --xattr=`

Controls whether to include information about extended attributes of the listed control groups in the output. With the long option, expects a boolean value. Defaults to no.

Added in version 250.

`-c, --cgroup-id=`

Controls whether to include the numeric ID of the listed control groups in the output.

With the long option, expects a boolean value. Defaults to no.

Added in version 250.

`-h, --help`

Print a short help text and exit.

`--version`

Print a short version string and exit.

`--no-pager`

Do not pipe output into a pager.

EXIT STATUS

On success, 0 is returned, a non-zero failure code otherwise.

SEE ALSO

`systemd(1)`, `systemctl(1)`, `systemd-cgtop(1)`, `systemd-nspawn(1)`, `ps(1)`

systemd 259.5

SYSTEMD-CGLS(1)