



Linux Ubuntu 26.04 Manual Pages on command 'tap-parser.1'

\$ man tap-parser.1

TAP-PARSER(1) User Commands TAP-PARSER(1)

NAME

tap-parser - Test-Anything-Protocol parser for Node.js

DESCRIPTION

Usage:

tap-parser <options>

Parses TAP data from stdin, and outputs the parsed result in the format specified by the options. Default output uses node's `util.inspect()` method.

OPTIONS

-j [<indent>] | --json[=*indent*]

Output event data as JSON with the specified indentation (default=2)

-t | --tap

Output data as reconstituted TAP based on parsed results

-l | --lines

Output each parsed line as it is recognized by the parser

-b | --bail

Emit a `Bail out!` at the first failed test point encountered

-B | --no-bail

Do not bail out at the first failed test point encountered (Default)

-f | --flat

Flatten all assertions to the top level parser

-F | --no-flat

Do not flatten all assertions to the top level parser (Default)

-w | --ignore-all-whitespace

Skip over blank lines outside of YAML blocks

-o | --omit-version

Ignore the `TAP version 13` or `TAP version 14` line at the start of tests

--strict

Run the parser in strict mode

--no-strict

Do not run the parser in strict mode

-s | --silent

Do not print output, just exit success/failure based on TAP stream

tap-parser 13.0.1

October 2025

TAP-PARSER(1)