



Linux Ubuntu 26.04 Manual Pages on command 'truncate.2'

\$ man truncate.2

truncate(2) System Calls Manual truncate(2)

NAME

truncate, ftruncate - truncate a file to a specified length

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <unistd.h>
```

```
int truncate(const char *path, off_t length);
```

```
int ftruncate(int fd, off_t length);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

truncate():

```
_XOPEN_SOURCE >= 500
```

```
|| /* Since glibc 2.12: */ _POSIX_C_SOURCE >= 200809L
```

```
|| /* glibc <= 2.19: */ _BSD_SOURCE
```

ftruncate():

```
_XOPEN_SOURCE >= 500
```

```
|| /* Since glibc 2.3.5: */ _POSIX_C_SOURCE >= 200112L
```

```
|| /* glibc <= 2.19: */ _BSD_SOURCE
```

DESCRIPTION

The `truncate()` and `ftruncate()` functions cause the regular file named by `path` or referenced by `fd` to be truncated to a size of precisely `length` bytes.

If the file previously was larger than this size, the extra data is lost. If the file previously

was shorter, it is extended, and the extended part reads as null bytes ('\0').

The file offset is not changed.

If the size changed, then the `st_ctime` and `st_mtime` fields (respectively, time of last status change and time of last modification; see `inode(7)`) for the file are updated, and the set-user-ID and set-group-ID mode bits may be cleared.

With `ftruncate()`, the file must be open for writing; with `truncate()`, the file must be writable.

RETURN VALUE

On success, zero is returned. On error, -1 is returned, and `errno` is set to indicate the error.

ERRORS

For `truncate()`:

EACCES Search permission is denied for a component of the path prefix, or the named file is not writable by the user. (See also `path_resolution(7)`.)

EFAULT The argument `path` points outside the process's allocated address space.

EFBIG The argument length is larger than the maximum file size. (XSI)

EINTR While blocked waiting to complete, the call was interrupted by a signal handler; see `fcntl(2)` and `signal(7)`.

EINVAL The argument length is negative or larger than the maximum file size.

EIO An I/O error occurred updating the inode.

EISDIR The named file is a directory.

ELOOP Too many symbolic links were encountered in translating the pathname.

ENAMETOOLONG

A component of a pathname exceeded 255 characters, or an entire pathname exceeded 1023 characters.

ENOENT The named file does not exist.

ENOTDIR

A component of the path prefix is not a directory.

EPERM The underlying filesystem does not support extending a file beyond its current size.

EPERM The operation was prevented by a file seal; see `fcntl(2)`.

EROFS The named file resides on a read-only filesystem.

ETXTBSY

The file is an executable file that is being executed.

For `ftruncate()` the same errors apply, but instead of things that can be wrong with path, we

now have things that can be wrong with the file descriptor, fd:

EBADF fd is not a valid file descriptor.

EBADF or EINVAL

fd is not open for writing.

EINVAL fd does not reference a regular file or a POSIX shared memory object.

EINVAL or EBADF

The file descriptor fd is not open for writing. POSIX permits, and portable applications should handle, either error for this case. (Linux produces EINVAL.)

VERSIONS

The details in DESCRIPTION are for XSI-compliant systems. For non-XSI-compliant systems, the POSIX standard allows two behaviors for `ftruncate()` when length exceeds the file length (note that `truncate()` is not specified at all in such an environment): either returning an error, or extending the file. Like most UNIX implementations, Linux follows the XSI requirement when dealing with native filesystems. However, some nonnative filesystems do not permit `truncate()` and `ftruncate()` to be used to extend a file beyond its current length: a notable example on Linux is VFAT.

On some 32-bit architectures, the calling signature for these system calls differ, for the reasons described in `syscall(2)`.

STANDARDS

POSIX.1-2024.

HISTORY

POSIX.1-2001, SVr4, 4.2BSD.

The original Linux `truncate()` and `ftruncate()` system calls were not designed to handle large file offsets. Consequently, Linux 2.4 added `truncate64()` and `ftruncate64()` system calls that handle large files. However, these details can be ignored by applications using glibc, whose wrapper functions transparently employ the more recent system calls where they are available.

NOTES

`ftruncate()` can also be used to set the size of a POSIX shared memory object; see `shm_open(3)`.

BUGS

A header file bug in glibc 2.12 meant that the minimum value of `_POSIX_C_SOURCE` required to expose the declaration of `ftruncate()` was 200809L instead of 200112L. This has been fixed

in later glibc versions.

SEE ALSO

truncate(1), open(2), stat(2), path_resolution(7)

Linux man-pages 6.17

2025-10-29

truncate(2)