



Linux Ubuntu 26.04 Manual Pages on command 'ubuntu-insights_completion_bash.1'

\$ man ubuntu-insights_completion_bash.1

Ubuntu-insights: ubuntu-insights(1)

Ubuntu-insights: ubuntu-insights(1)

NAME

ubuntu-insights-completion-bash - Generate the autocompletion script for bash

SYNOPSIS

ubuntu-insights completion bash

DESCRIPTION

Generate the autocompletion script for the bash shell.

This script depends on the 'bash-completion' package. If it is not installed already, you can install it via your OS's package manager.

To load completions in your current shell session:

```
source <(ubuntu-insights completion bash)
```

To load completions for every new session, execute once:

Linux:

```
ubuntu-insights completion bash > /etc/bash_completion.d/ubuntu-insights
```

macOS:

```
ubuntu-insights completion bash > $(brew --prefix)/etc/bash_completion.d/ubuntu-insights
```

You will need to start a new shell for this setup to take effect.

OPTIONS

-h, --help[=false] help for bash

--no-descriptions[=false] disable completion descriptions

OPTIONS INHERITED FROM PARENT COMMANDS

--config="" use a specific configuration file

--consent-dir="" the base directory of the consent state files

--insights-dir="" the base directory of the insights report cache

--quiet[=false] suppress all output except errors

-v, --verbose[=0] issue INFO (-v), DEBUG (-vv)

SEE ALSO

ubuntu-insights-completion(1)

HISTORY

13-Feb-2026 Auto generated by spf13/cobra

Auto generated by spf13/cobra

Feb 2026

Ubuntu-insights: ubuntu-insights(1)