



## ***Linux Ubuntu 26.04 Manual Pages on command 'ubuntu-insights\_completion\_zsh.1'***

***\$ man ubuntu-insights\_completion\_zsh.1***

Ubuntu-insights: ubuntu-insights(1)

Ubuntu-insights: ubuntu-insights(1)

### **NAME**

ubuntu-insights-completion-zsh - Generate the autocompletion script for zsh

### **SYNOPSIS**

ubuntu-insights completion zsh [flags]

### **DESCRIPTION**

Generate the autocompletion script for the zsh shell.

If shell completion is not already enabled in your environment you will need to enable it.

You can execute the following once:

```
echo "autoload -U compinit; compinit" >> ~/.zshrc
```

To load completions in your current shell session:

```
source <(ubuntu-insights completion zsh)
```

To load completions for every new session, execute once:

ubuntu-insights completion zsh > "\${fpath[1]}/\_ubuntu-insights"

macOS:

ubuntu-insights completion zsh > \$(brew --prefix)/share/zsh/site-functions/\_ubuntu-insights

You will need to start a new shell for this setup to take effect.

## OPTIONS

-h, --help[=false]    help for zsh

--no-descriptions[=false]    disable completion descriptions

## OPTIONS INHERITED FROM PARENT COMMANDS

--config=""    use a specific configuration file

--consent-dir=""    the base directory of the consent state files

--insights-dir=""    the base directory of the insights report cache

--quiet[=false]    suppress all output except errors

-v, --verbose[=0]    issue INFO (-v), DEBUG (-vv)

## SEE ALSO

ubuntu-insights-completion(1)

## HISTORY

13-Feb-2026 Auto generated by spf13/cobra