



Linux Ubuntu 26.04 Manual Pages on command 'uuid.3'

\$ man uuid.3

UUID(3) Programmers Manual UUID(3)

NAME

uuid - DCE compatible Universally Unique Identifier library

SYNOPSIS

```
#include <uuid.h>
```

DESCRIPTION

The UUID library is used to generate unique identifiers for objects that may be accessible beyond the local system. This library generates UUIDs compatible with those created by the Open Software Foundation (OSF) Distributed Computing Environment (DCE) utility uuidgen(1).

The UUIDs generated by this library can be reasonably expected to be unique within a system, and unique across all systems. They could be used, for instance, to generate unique HTTP cookies across multiple web servers without communication between the servers, and without fear of a name clash.

CONFORMING TO

This library generates UUIDs compatible with OSF DCE 1.1, and hash based UUIDs V3 and V5 compatible with RFC-4122 <<https://tools.ietf.org/html/rfc4122>>.

AUTHORS

SEE ALSO

`uuid_clear(3)`, `uuid_compare(3)`, `uuid_copy(3)`, `uuid_generate(3)`, `uuid_is_null(3)`,
`uuid_parse(3)`, `uuid_time(3)`, `uuid_unparse(3)`

REPORTING BUGS

For bug reports, use the issue tracker <<https://github.com/util-linux/util-linux/issues>>.

AVAILABILITY

The `libuuid` library is part of the `util-linux` package since version 2.15.1. It can be downloaded from Linux Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.

util-linux 2.41.3	2025-12-15	UUID(3)
-------------------	------------	---------