



Linux Ubuntu 26.04 Manual Pages on command 'vwarnx.3'

\$ man vwarnx.3

err(3) Library Functions Manual err(3)

NAME

err, verr, errx, verrx, warn, vwarn, warnx, vwarnx - formatted error messages

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <err.h>

[[noreturn]] void err(int eval, const char *fmt, ...);
[[noreturn]] void errx(int eval, const char *fmt, ...);

void warn(const char *fmt, ...);
void warnx(const char *fmt, ...);

#include <stdarg.h>

[[noreturn]] void verr(int eval, const char *fmt, va_list args);
[[noreturn]] void verrx(int eval, const char *fmt, va_list args);

void vwarn(const char *fmt, va_list args);
void vwarnx(const char *fmt, va_list args);
```

DESCRIPTION

The `err()` and `warn()` family of functions display a formatted error message on the standard error output. In all cases, the last component of the program name, a colon character, and a space are output. If the `fmt` argument is not `NULL`, the `printf(3)`-like formatted error message is output. The output is terminated by a newline character.

The `err()`, `verr()`, `warn()`, and `vwarn()` functions append an error message obtained from `strerror(3)` based on the global variable `errno`, preceded by another colon and space unless the

The `err()`, `verr()`, `errx()`, and `verrx()` functions do not return, but exit with the value of the argument `eval`.

```
    raw_device, strerror(errno));  
fd = open(block_device, O_RDONLY, 0);  
if (fd == -1)  
    err(EXIT_FAILURE, "%s", block_device);
```

SEE ALSO

[error\(3\)](#), [exit\(3\)](#), [perror\(3\)](#), [printf\(3\)](#), [strerror\(3\)](#)

Linux man-pages 6.17

2025-05-17

[err\(3\)](#)