



Linux Ubuntu 26.04 Manual Pages on command 'wcschr.3'

\$ man wcschr.3

wcschr(3) Library Functions Manual wcschr(3)

NAME _____

wcschr - search a wide character in a wide-character string

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <wchar.h>
```

```
wchar_t *wcschr(const wchar_t *wcs, wchar_t wc);
```

DESCRIPTION

The `wcschr()` function is the wide-character equivalent of the `strchr(3)` function. It searches the first occurrence of `wc` in the wide-character string pointed to by `wcs`.

RETURN VALUE

The `wcschr()` function returns a pointer to the first occurrence of `wc` in the wide-character string pointed to by `wcs`, or `NULL` if `wc` does not occur in the string.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

?	Interface	?	Attribute	?	Value	?
---	-----------	---	-----------	---	-------	---

[illegible]

? wcschr()	? Thread safety ? MT-Safe ?
------------	-----------------------------

[illegible]

STANDARDS

C11, POSIX.1-2008.

HISTORY

POSIX.1-2001, C99.

SEE ALSO

[strchr\(3\)](#), [wcpbrk\(3\)](#), [wcsrchr\(3\)](#), [wcsstr\(3\)](#), [wmemchr\(3\)](#)

Linux man-pages 6.17

2026-02-08

[wcschr\(3\)](#)