



Linux Ubuntu 26.04 Manual Pages on command 'wcpbrk.3'

\$ man wcspbrk.3

wcspbrk(3) Library Functions Manual wcspbrk(3)

NAME

wcspbrk - search a wide-character string for any of a set of wide characters

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <wchar.h>
```

```
wchar_t *wcsprk(const wchar_t *wcs, const wchar_t *accept);
```

DESCRIPTION

The `wcspbrk()` function is the wide-character equivalent of the `strpbrk(3)` function. It searches for the first occurrence in the wide-character string pointed to by `wcs` of any of the characters in the wide-character string pointed to by `accept`.

RETURN VALUE

The `wcspbrk()` function returns a pointer to the first occurrence in `wcs` of any of the characters listed in `accept`. If `wcs` contains none of these characters, `NULL` is returned.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

Interface	Attribute	Value
?	?	?

[illegible]

? wcpbrk() ? Thread safety ? MT-Safe ?

Page 1/2

STANDARDS

C11, POSIX.1-2008.

HISTORY

POSIX.1-2001, C99.

SEE ALSO

[strpbrk\(3\)](#), [wcschr\(3\)](#), [wcscspn\(3\)](#)

Linux man-pages 6.17

2026-02-08

[wcpbrk\(3\)](#)