



Linux Ubuntu 26.04 Manual Pages on command 'wordfree.3'

\$ man wordfree.3

wordexp(3) Library Functions Manual wordexp(3)

NAME

wordexp, wordfree - perform word expansion like a posix-shell

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <wordexp.h>

int wordexp(const char *restrict s, wordexp_t *restrict p, int flags);

void wordfree(wordexp_t *p);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
wordexp(), wordfree():
    _XOPEN_SOURCE
```

DESCRIPTION

The function `wordexp()` performs a shell-like expansion of the string `s` and returns the result in the structure pointed to by `p`. The data type `wordexp_t` is a structure that at least has the fields `we_wordc`, `we_wordv`, and `we_offs`. The field `we_wordc` is a `size_t` that gives the number of words in the expansion of `s`. The field `we_wordv` is a `char **` that points to the array of words found. The field `we_offs` of type `size_t` is sometimes (depending on flags, see below) used to indicate the number of initial elements in the `we_wordv` array that should be filled with `NULL`s.

The function `wordfree()` frees the allocated memory again. More precisely, it does not free its argument, but it frees the array `we_wordv` and the strings that points to.

The string argument

Since the expansion is the same as the expansion by the shell (see `sh(1)`) of the parameters to a command, the string `s` must not contain characters that would be illegal in shell command parameters. In particular, there must not be any unescaped newline or `|`, `&`, `;`, `<`, `>`, `(`, `)`, `{`, `}` characters outside a command substitution or parameter substitution context.

If the argument `s` contains a word that starts with an unquoted comment character `#`, then it is unspecified whether that word and all following words are ignored, or the `#` is treated as a non-comment character.

The expansion

The expansion done consists of the following stages: tilde expansion (replacing `~user` by user's home directory), variable substitution (replacing `$FOO` by the value of the environment variable `FOO`), command substitution (replacing `$(command)` or ``command`` by the output of command), arithmetic expansion, field splitting, wildcard expansion, quote removal.

The result of expansion of special parameters (`$@`, `$*`, `$#`, `$?`, `$-`, `$$`, `$!`, `$0`) is unspecified.

Field splitting is done using the environment variable `$IFS`. If it is not set, the field separators are space, tab, and newline.

The output array

The array `we_wordv` contains the words found, followed by a `NULL`.

The flags argument

The flag argument is a bitwise inclusive OR of the following values:

`WRDE_APPEND`

Append the words found to the array resulting from a previous call.

`WRDE_DOOFFS`

Insert `we_offs` initial `NULL`s in the array `we_wordv`. (These are not counted in the returned `we_wordc`.)

`WRDE_NOCMD`

Don't do command substitution.

`WRDE_REUSE`

The argument `p` resulted from a previous call to `wordexp()`, and `wordfree()` was not called. Reuse the allocated storage.

`WRDE_SHOWERR`

Normally during command substitution `stderr` is redirected to `/dev/null`. This flag specifies that `stderr` is not to be redirected.

WRDE_UNDEF

Consider it an error if an undefined shell variable is expanded.

RETURN VALUE

On success, wordexp() returns 0. On failure, wordexp() returns one of the following nonzero values:

WRDE_BADCHAR

Illegal occurrence of newline or one of |, &, :, <, >, (,), {, }.

WRDE_BADVAL

An undefined shell variable was referenced, and the WRDE_UNDEF flag told us to consider this an error.

WRDE_CMDSUB

Command substitution requested, but the WRDE_NOCMD flag told us to consider this an error.

WRDE_NOSPACE

Out of memory.

WRDE_SYNTAX

Shell syntax error, such as unbalanced parentheses or unmatched quotes.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

Interface	Attribute	Value
wordexp()	Thread safety	MT-Unsafe race:utent const:env env sig:ALRM timer locale
wordfree()	Thread safety	MT-Safe

In the above table, utent in race:utent signifies that if any of the functions setutent(3), getutent(3), or endutent(3) are used in parallel in different threads of a program, then data races could occur. wordexp() calls those functions, so we use race:utent to remind users.

STANDARDS

POSIX.1-2008.

HISTORY

EXAMPLES

The output of the following example program is approximately that of "ls [a-c]*.c".

```
#include <stdio.h>

#include <stdlib.h>

#include <wordexp.h>

int

main(void)

{
    wordexp_t p;
    char **w;
    wordexp("[a-c]*.c", &p, 0);
    w = p.we_wordv;
    for (size_t i = 0; i < p.we_wordc; i++)
        printf("%s\n", w[i]);
    wordfree(&p);
    exit(EXIT_SUCCESS);
}
```

SEE ALSO

fnmatch(3), glob(3)

Linux man-pages 6.17

2026-02-08

wordexp(3)