



Linux Ubuntu 26.04 Manual Pages on command 'xencrypt.3'

\$ man xencrypt.3

XCRYPT(3) Library Functions Manual XCRYPT(3)

NAME

xencrypt, xdecrypt, passwd2des - RFS password encryption

LIBRARY

Standard C library (libc, -lc)

SYNOPSIS

```
#include <rpc/des_crypt.h>

void passwd2des(char *passwd, char *key);

int xencrypt(char *secret, char *passwd);

int xdecrypt(char *secret, char *passwd);
```

DESCRIPTION

WARNING: Do not use these functions in new code. They do not achieve any type of acceptable cryptographic security guarantees.

The function `passwd2des()` takes a character string `passwd` of arbitrary length and fills a character array `key` of length 8. The array `key` is suitable for use as DES key. It has `odd` parity set in bit 0 of each byte. Both other functions described here use this function to turn their argument `passwd` into a DES key.

The `xencrypt()` function takes the ASCII character string `secret` given in `hex`, which must have a length that is a multiple of 16, encrypts it using the DES key derived from `passwd` by `passwd2des()`, and outputs the result again in `secret` as a hex string of the same length.

The `xdecrypt()` function performs the converse operation.

RETURN VALUE

The functions `xencrypt()` and `xdecrypt()` return 1 on success and 0 on error.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

[illegible]

? Interface	? Attribute	? Value	?
-------------	-------------	---------	---

[illegible]

? passwd2des(), xencrypt(), xdecrypt() ? Thread safety ? MT-Safe ?

[illegible]

VERSIONS

These functions are available since glibc 2.1.

BUGS

The prototypes are missing from the abovementioned include file.

SEE ALSO

```
cbc_crypt(3)
```

Linux man-pages 6.17

2026-02-08

XCRYPT(3)