



Linux Ubuntu 26.04 Manual Pages on command 'xlsfonts.1'

\$ man xlsfonts.1

xlsfonts(1) General Commands Manual xlsfonts(1)

NAME

xlsfonts - list fonts available to X server

SYNOPSIS

xlsfonts [-display host:dpy] [-l] [-ll] [-lll] [-m] [-C] [-1] [-w width] [-n columns] [-u]
[-o] [-fn pattern] [-v]

DESCRIPTION

xlsfonts lists the fonts available on an X server that match the given pattern. The wildcard character "*" may be used to match any sequence of characters (including none), and "?" to match any single character. If no pattern is given, "*" is assumed.

The "*" and "?" characters must be quoted to prevent them from being expanded by the shell.

OPTIONS

-display host:dpy

This option specifies the X server to contact.

-d host:dpy

Same as -display host:dpy.

-l Lists some attributes of the font on one line in addition to its name.

-ll Lists font properties in addition to -l output.

-lll Lists character metrics in addition to -ll output.

-m This option indicates that long listings should also print the minimum and maximum bounds of each font.

-C This option indicates that listings should use multiple columns. This is the same as

-n 0.

-1 This option indicates that listings should use a single column. This is the same as -n 1.

-w width

This option specifies the width in characters that should be used in figuring out how many columns to print. The default is 79.

-n columns

This option specifies the number of columns to use in displaying the output. By default, it will attempt to fit as many columns of font names into the number of character specified by -w width.

-u This option indicates that the output should be left unsorted.

-o This option indicates that xlsfonts should do an OpenFont (and QueryFont, if appropriate) rather than a ListFonts. This is useful if ListFonts or ListFontsWithInfo fail to list a known font (as is the case with some scaled font systems).

-fn pattern

This option specifies the font name pattern to match.

-v This option indicates that xlsfonts should print out the program version and exit.

SEE ALSO

X(7), Xserver(1), xset(1), xfd(1), X Logical Font Description Conventions

ENVIRONMENT

DISPLAY

DISPLAY must be set to get the default host and display to use.

BUGS

Doing ``xlsfonts -l'' can tie up your X server for a very long time. This is really a bug with single-threaded non-preemptable servers, not with this program.

AUTHOR

Mark Lillibridge

Jim Fulton

Phil Karlton

Roland Mainz

X Version 11

xlsfonts 1.0.8

xlsfonts(1)